

<b>SANYO</b>	No.781F	<b>2SA1208/2SC2910</b>
		PNP/NPN Epitaxial Planar Silicon Transistors High-Voltage Switching, Audio 80W Output Predriver Applications

**Features**

- Adoption of FBET process.
- High breakdown voltage.
- Excellent linearity of  $h_{FE}$  and small  $c_{ob}$ .
- Fast switching speed.

( ) : 2SA1208

**Absolute Maximum Ratings at  $T_a = 25^\circ\text{C}$**

			unit
Collector to Base Voltage	$V_{CBO}$	(-)	180 V
Collector to Emitter Voltage	$V_{CEO}$	(-)	160 V
Emitter to Base Voltage	$V_{EBO}$	(-)	5 V
Collector Current	$I_C$	(-)	70 mA
Collector Current(Pulse)	$I_{CP}$	(-)	140 mA
Collector Dissipation	$P_C$		900 mW
Junction Temperature	$T_j$		150 $^\circ\text{C}$
Storage Temperature	$T_{stg}$		- 55 to + 150 $^\circ\text{C}$


**Electrical Characteristics at  $T_a = 25^\circ\text{C}$**

			min	typ	max	unit
Collector Cutoff Current	$I_{CBO}$	$V_{CB} = (-)80\text{V}, I_E = 0$			(-)	0.1 $\mu\text{A}$
Emitter Cutoff Current	$I_{EBO}$	$V_{EB} = (-)4\text{V}, I_C = 0$			(-)	0.1 $\mu\text{A}$
DC Current Gain	$h_{FE}$	$V_{CE} = (-)5\text{V}, I_C = (-)10\text{mA}$	100*		400*	
Gain-Bandwidth Product	$f_T$	$V_{CE} = (-)10\text{V}, I_C = (-)10\text{mA}$		150		MHz
Output Capacitance	$c_{ob}$	$V_{CB} = (-)10\text{V}, f = 1\text{MHz}$		(2.5)2.0		pF
C-E Saturation Voltage	$V_{CE(sat)}$	$I_C = (-)30\text{mA}, I_B = (-)3\text{mA}$		(-0.14)	(-0.4)	V
				0.08	0.3	V
Turn-ON Time	$t_{on}$	See specified Test Circuit.		0.1		$\mu\text{s}$
Fall Time	$t_f$	"		0.2		$\mu\text{s}$
Storage Time	$t_{stg}$	"		1.0		$\mu\text{s}$

\* : The 2SA1208/2SC2910 are classified by 10mA  $h_{FE}$  as follows :


100 R 200	140 S 280	200 T 400
-----------	-----------	-----------

**Switching Time Test Circuit**











Unit(Resistance :  $\Omega$  , Capacitance : F)









**Package Dimensions 2006A**  
(unit: mm)



2SA1208/2SC2910



2SA1208/2SC2910



- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
  - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use:
  - ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.