

NPN SILICON RF POWER TRANSISTOR

DESCRIPTION:

The **ASI ASAT25** is Designed for

FEATURES:

-
-
- **Omnigold™** Metalization System

MAXIMUM RATINGS

I_C	2.6 A
V_{CBO}	45 V
V_{CEO}	12 V
V_{EBO}	3.0 V
P_{DISS}	50 W @ T _C = 25 °C
T_J	-65 °C to +200 °C
T_{STG}	-65 °C to +150 °C
θ_{JC}	3.5 °C/W

PACKAGE STYLE .250 2L FLG(A)

DIM	MINIMUM inches / mm	MAXIMUM inches / mm
A	.055 / 1.40	.065 / 1.65
B	.124 / 3.15	
C	.243 / 6.17	.253 / 6.43
D	.635 / 16.13	.665 / 16.89
E	.555 / 14.10	.565 / 14.35
F	.739 / 18.77	.749 / 19.02
G	.315 / 8.00	.325 / 8.26
H	.002 / 0.05	.006 / 0.15
I	.065 / 1.40	.065 / 1.65
J	.075 / 1.91	.095 / 2.41
K		.190 / 4.83
L	.245 / 6.22	.255 / 6.48
M	.092 / 2.34	

ORDER CODE: ASI10520

CHARACTERISTICS T_C = 25 °C

SYMBOL	TEST CONDITIONS			MINIMUM	TYPICAL	MAXIMUM	UNITS
BV_{CBO}	I _C = 6 mA			45			V
BV_{CEO}	I _C = 6 mA			12			V
BV_{EBO}	I _E = 6 mA			3.0			V
h_{FE}	V _{CE} = 5.0 V	I _C = 1.2 A		15		150	---
P_G	V _{CC} = 28 V	P _{OUT} = 25 W	f = 1.65	9.0			dB
η_c	GHz			50			%