


SOT23 PNP SILICON PLANAR GENERAL PURPOSE TRANSISTOR

ISSUE 2 - MARCH 1995



FMMT4402
FMMT4403

PARTMARKING DETAILS: FMMT4402 - 2K
FMMT4403 - 2L



ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE		UNIT
Collector-Base Voltage	V_{CBO}	-40		V
Collector-Emitter Voltage	V_{CEO}	-40		V
Emitter-Base Voltage	V_{EBO}	-5		V
Continuous Collector Current	I_C	-600		A
Power Dissipation at $T_{amb}=25^\circ\text{C}$	P_{tot}	330		mW
Operating and Storage Temperature Range	$T_j:T_{stg}$	-55 to +150		°C

ELECTRICAL CHARACTERISTICS (at $T_{amb}=25^\circ\text{C}$ unless otherwise stated)

PARAMETER	SYMBOL	FMMT4402		FMMT4403		UNIT	CONDITIONS
		MIN.	MAX.	MIN.	MAX.		
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	-40		-40		V	$I_C=-1\text{mA}, I_B=0$
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	-40		-40		V	$I_C=-0.1\text{mA}, I_E=0$
Emitter-Base Breakdown Current	$V_{(BR)EBO}$	-5		-5		V	$I_E=-0.1\text{mA}, I_C=0$
Collector-Emitter Cut-Off Current	I_{CEX}		-0.1		-0.1	μA	$V_{CE}=-35\text{V}$ $V_{EB(\text{off})} = -0.4\text{V}$
Base Cut-Off Current	I_{BEX}		-0.1		-0.1	μA	$V_{CE}=-35\text{V}$ $V_{EB(\text{off})} = -0.4\text{V}$
Static Forward Current Transfer Ratio	h_{FE}	30 50 50 20		30 60 100 100 20		300	$I_C=-0.1\text{mA}, V_{CE}=-1\text{V}$ $I_C=1\text{mA}, V_{CE}=-1\text{V}$ $I_C=10\text{mA}, V_{CE}=-1\text{V}$ $I_C=150\text{mA}, V_{CE}=-2\text{V}^*$ $I_C=500\text{mA}, V_{CE}=-2\text{V}^*$
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$		-0.4 -0.75		-0.4 -0.75	V	$I_C=150\text{mA}, I_B=15\text{mA}^*$ $I_C=500\text{mA}, I_B=50\text{mA}^*$
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	-0.75	-0.95 -1.3	-0.75	-0.95 -1.3	V	$I_C=150\text{mA}, I_B=15\text{mA}^*$ $I_C=500\text{mA}, I_B=50\text{mA}^*$
Transition Frequency	f_T	150		200		MHz	$I_C=20\text{mA}, V_{CE}=-10\text{V}$ $f=100\text{MHz}$
Output Capacitance	C_{obo}		8.5		8.5	pF	$V_{CB}=-10\text{V}, I_E=0$ $f=100\text{kHz}$
Input Capacitance	C_{ibo}		30		30	pF	$V_{BE}=0.5\text{V}$ $I_C=0, f=100\text{kHz}$

*Measured under pulsed conditions. Pulse width=300μs. Duty cycle ≤ 2%

FMMT4402
FMMT4403

SWITCHING CHARACTERISTICS (at $T_{amb} = 25^\circ C$)

PARAMETER	SYMBOL	MIN.	MAX.	UNIT	CONDITIONS
Turn-On Time	t_{on}		35	ns	$V_{CC}=-30V, V_{BE(off)}=-2V$ $I_C=150mA, I_B=15mA$ (See Fig. 1)
Turn-Off Time	t_{off}		255	ns	$V_{CC}=-30V, I_C=-150mA$ $I_{B1}=I_{B2}=-15mA$ (See Fig. 2)