

MOSPEC

HORIZONTAL DEFLECTION TRANSISTORS

...designed for use in large screen color deflection circuits

FEATURES:



- * Collector-Emitter Sustaining Voltage
 $V_{CE(sus)} = 600V(\text{Min})$
- * Fast Switching Time
 $t_f = 0.8 \mu\text{s} @ I_C = 5.0\text{A}$
- * Glass Passivated Collector-Base Junction

NPN
2SC1325A

6.0 AMPERE
NPN SILICON
POWER TRANSISTORS
1500 VOLTS
80 WATTS

MAXIMUM RATINGS

Characteristic	Symbol	2SC1325A	Unit
Collector-Emitter Voltage	V_{CEO}	600	V
Collector-Base Voltage	V_{CBO}	1500	V
Emitter-Base Voltage	V_{EBO}	6.0	V
Collector Current - Continuous - Peak	I_C I_{CM}	6.0 12	A
Base current	I_B	2.0	A
Total Power Dissipation @ $T_c = 25^\circ\text{C}$ Derate above 25°C	P_D	80 0.64	W W/ $^\circ\text{C}$
Operating and Storage Junction Temperature Range	T_J, T_{STG}	-65 to +150	$^\circ\text{C}$




PIN 1.BASE
2.EMITTER
COLLECTOR(CASE)

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Thermal Resistance Junction to Case	$R_{\theta jc}$	1.56	$^\circ\text{C}/\text{W}$

FIGURE -1 POWER DERATING



DIM	MILLIMETERS	
	MIN	MAX
A	38.75	39.96
B	19.28	22.23
C	7.96	9.28
D	11.18	12.19
E	25.20	26.67
F	0.92	1.09
G	1.38	1.62
H	29.90	30.40
I	16.64	17.30
J	3.88	4.36
K	10.67	11.18

ELECTRICAL CHARACTERISTICS ($T_c = 25^\circ\text{C}$ unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
----------------	--------	-----	-----	------

OFF CHARACTERISTICS

Collector-Emitter Voltage ($I_c = 100 \text{ mA}$, $I_B = 0$)	V_{CEO}	600		V
Collector Cutoff Current ($V_{CE} = 1500 \text{ V}$, $V_{BE} = 0$)	I_{CES}		1.0	mA
Collector Cutoff Current ($V_{CB} = 1000 \text{ V}$, $I_E = 0$)	I_{CBO}		20	uA
Emitter Cutoff Current ($V_{EB} = 5.0 \text{ V}$, $I_C = 0$)	I_{EBO}		200	uA

ON CHARACTERISTICS (1)


DC Current Gain ($I_c = 1.0 \text{ A}$, $V_{CE} = 15 \text{ V}$) ($I_c = 5.0 \text{ A}$, $V_{CE} = 15 \text{ V}$)	hFE	10 5.0	45 35	
Collector-Emitter Saturation Voltage ($I_c = 5.0 \text{ A}$, $I_B = 1.2 \text{ A}$)	$V_{CE(\text{sat})}$		4.0	V
Base-Emitter Saturation Voltage ($I_c = 5.0 \text{ A}$, $I_B = 1.2 \text{ A}$)	$V_{BE(\text{sat})}$		1.1	V

SWITCHING CHARATERISTICS

Storage Time	$I_c = 5.0 \text{ A}$, $I_{B1} = -I_{B2} = 1.0 \text{ A}$ $Pw = 20 \mu\text{s}$	t_s		10	μs
Fall Time		t_f		0.8	μs

(1) Pulse Test: Pulse Width = $300 \mu\text{s}$, Duty Cycle $\leq 2.0\%$


ACTIVE-REGION SAFE OPERATING AREA (SOA)





There are two limitation on the power handling ability of a transistor: average junction temperature and second breakdown safe operating area curves indicate I_c-V_{ce} limits of the transistor that must be observed for reliable operation i.e., the transistor must not be subjected to greater dissipation than curves indicate.

The data of SOA curve is base on $T_{J(PK)}=150^\circ\text{C}$; T_c is variable depending on conditions. second breakdown pulse limits are valid for duty cycles to 10% provided $T_{J(PK)} \leq 150^\circ\text{C}$. At high case temperatures, thermal limitation will reduce the power that can be handled to values less than the limitations imposed by second breakdown.

DC CURRENT GAIN



SWITCHING TIME- AMBIENT TEMPERATURE

 $I_c - V_{ce}$ 

COLLECTOR SATURATION REGION

