


N-CHANNEL ENHANCEMENT MODE VERTICAL DMOS FET

ISSUE 2 - MARCH 94

ZVNL535A

FEATURES

- * 350 Volt V_{DS}
- * $R_{DS(on)}=40\Omega$



ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE	UNIT
Drain-Source Voltage	V_{DS}	350	V
Continuous Drain Current at $T_{amb}=25^\circ C$	I_D	90	mA
Pulsed Drain Current	I_{DM}	800	mA
Gate Source Voltage	V_{GS}	± 20	V
Power Dissipation at $T_{amb}=25^\circ C$	P_{tot}	700	mW
Operating and Storage Temperature Range	$T_j:T_{stg}$	-55 to +150	°C

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^\circ C$ unless otherwise stated).

PARAMETER	SYMBOL	MIN.	MAX.	UNIT	CONDITIONS.
Drain-Source Breakdown Voltage	BV_{DSS}	350		V	$I_D=1\text{mA}$, $V_{GS}=0\text{V}$
Gate-Source Threshold Voltage	$V_{GS(th)}$	0.5	1.5	V	$ID=1\text{mA}$, $V_{DS}=V_{GS}$
Gate-Body Leakage	I_{GSS}		100	nA	$V_{GS}=\pm 20\text{V}$, $V_{DS}=0\text{V}$
Zero Gate Voltage Drain Current	I_{DSS}		50 400	μA μA	$V_{DS}=350\text{ V}$, $V_{GS}=0$ $V_{DS}=280\text{ V}$, $V_{GS}=0\text{V}$, $T=125^\circ C(2)$
On-State Drain Current(1)	$I_{D(on)}$	200		mA	$V_{DS}=25\text{ V}$, $V_{GS}=5\text{V}$
Static Drain-Source On-State Resistance (1)	$R_{DS(on)}$		40 40	Ω Ω	$V_{GS}=5\text{V}$, $I_D=100\text{mA}$ $V_{GS}=3\text{V}$, $I_D=50\text{mA}$
Forward Transconductance (1)(2)	g_{fs}	100		mS	$V_{DS}=25\text{V}$, $I_D=100\text{mA}$
Input Capacitance (2)	C_{iss}		70	pF	$V_{DS}=25\text{ V}$, $V_{GS}=0\text{V}$, $f=1\text{MHz}$
Common Source Output Capacitance (2)	C_{oss}		10	pF	
Reverse Transfer Capacitance (2)	C_{rss}		4	pF	
Turn-On Delay Time (2)(3)	$t_{d(on)}$		7	ns	
Rise Time (2)(3)	t_r		7	ns	$V_{DD}\approx 25\text{V}$, $I_D=100\text{mA}$
Turn-Off Delay Time (2)(3)	$t_{d(off)}$		16	ns	
Fall Time (2)(3)	t_f		10	ns	