

MICRO

ELECTRONIC

MSG1557A/C
THREE COLOR
EMITTED LED DOT
MATRIX DISPLAY

FEATURES :

Three emitted color : High efficiency red, green, orange
(The mixture of high efficiency red and green)
Anode column, Cathode row (MSG1557A);
Cathode column, Anode row (MSG1557C)
High contrast
Wide viewing angle
5 x 7 matrix array with row-column select
Regged encapsulation (Filled reflector construction)
End & side stackable

ABSOLUTE MAXIMUM RATINGS

Power Dissipation / Dot	75mW
Peak Forward Current / Dot*	100mA
Continuous Forward Current / Dot	25mA
Reverse Voltage / Dot	5V
Operating Temperature Range	-25 to +80°C
Storage Temperature Range	-20 to +75°C

* Note : Pulse Width = 1mS, Duty Ratio = 1/10.

ELECTRO-OPTICAL CHARACTERISTICS (Ta=25°C)

PARAMETER	SYMBOL	Hi-Eff. Red	Green	UNIT	CONDITIONS
Forward Voltage	MAX VF	3.0	3.0	V	IF=20mA
Luminous Intensity	MIN IV	1200	1800	μ cd	IF=10mA
	TYP	2000	3000	μ cd	
Dot to Dot Luminous Intensity Ratio	MAX	2:1	2:1		IF=10mA
Reverse Current	MAX IR	100	100	μ A	VR=5V
Peak Wavelength	TYP λ_p	650	565	nm	IF=20mA
Spectral Line Half Width	TYP $\Delta\lambda$	35	30	nm	IF=20mA



MICRO ELECTRONICS LTD.

38, Hung To Road, Microtron Building, Kwun Tong, Kowloon, Hong Kong.

Kwun Tong P.O. Box 69477 Hong Kong. Fax No. 2341 0321 Telex:43510 Micro Hx. Tel: 2343 0181-5

Dec-97

