



1	2	3	4	5	6	7	8	9	10	11	12	13	14
V _{dd}	V _{ss}	V ₀	RS	R/W	E	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7

NOTES:

- | | |
|-----------------------------|--------------------------------|
| 1. DISPLAY TYPE: | FSTN |
| 2. DRIVE METHOD: | 1/16 DUTY 1/4 BIAS |
| 3. VIEWING DIRECTION: | 12:00 |
| 4. POLARIZER MODE: | TRANSMISSIVE/NEGATIVE |
| 5. LCD OPERATING VOLTAGE: | 4.5V |
| 6. OPERATING TEMP: | 0°C-+50°C |
| 7. STORAGE TEMP: | -20°C-+60°C |
| 8. BACKLIGHT TYPE: | LED(GREEN,3.3V±0.1,DNE LAMP) |
| 9. CONTROLLER: | S6A0069X01-C0CXXKS0066UP-00CC) |
| 10. BEZEL IS TO BE PAINTED | BLACK |
| 11. ALL UNMARKED TOLERANCE: | ±0.3mm |

TIAN-MA MICROELECTRONICS CO.
 6/F, CASTLE Building, Sherman Road, Dertal, Shenzhen, China

DRAWN BY:	TTTLR: TM62A9GFU7	SCALE:	1:1
CHECKED BY:	DWG NO: G-2	DATE:	2008
APPROVED BY:	DWG NAME: TM62A9GFU7-2	SHEET NO:	1 OF 1
CONFIRMED BY:			