

AudioCodes Enabling Technology Products

AC48304 Voice over Packet Processor for Client Applications



- Low per-channel cost and power
- Independent channel operation
- Toll quality voice compression
- Robust bandwidth-saving fax relay
- Small footprint
- Proprietary evaluation & development tools

The **AC48304** is an ideal voice processing engine for a variety of Voice over IP, Voice over DSL and other voice over packet client applications. The AC48304 VoP processor is a four ports voice over packet processor that combines toll quality low bit rate voice compression, T.38 compliant fax relay and other voice band processing functions. Field-proven, feature-rich software enables the rapid development and fast time-to-market of the complete solution.

DELIVER FEATURE-RICH SOLUTION

The AC48304 voice over packet processor combines four channels of toll quality low bit rate voice compression, with an adaptive G.168-2000 compliant echo canceller, and complete voice band processing functions in a single device. Field-proven G3 Fax Relay, compliant with the T.38 ASN.1 standard, is a major enhancement to the AC48304 offering. Other advanced features include dynamic packet size programming, high quality DTMF/MF R1/MF R2/Call Progress Tones, detection and generation of user defined tones and Caller ID, silence suppression, and automatic voice/fax/data discriminator.

FAST INTEGRATION WITH SOFTWARE STACKS

The AC48304 is supported by the VoicePacketizer™ software stack which enables the processor to create a VoIP-compliant media stream as part of a client entity. The VoicePacketizer is an ANSI-C software stack that supports the RTP/RTCP protocol. The software stack also provides a simple API for initialization and configuration of the AC48304 and for run-time call control.

SOFTWARE UPGRADES

The complete functionality of the AC48304 is implemented in the internal DSP software. The software image is downloaded into the AC48304 by the host processor prior to start of operation. This allows the addition of new features in future product releases without any system hardware modifications.

BENEFIT FROM EXTENSIVE EXPERIENCE

AudioCodes is one of the world's leading providers of DSP solutions since 1996. During this period, the company successfully passed numerous interoperability tests while maintaining high levels of performance. AudioCodes' commitment to innovation yields consistently high-quality voice processing products that are feature-rich and field-proven. AudioCodes has deployed close to 10 million VoP ports to date.

AC48304 FEATURES

- Low bit rate Vocoders
- Low power consumption & small footprint
- G.168-2000 compliant Echo Canceller
- T.38 and FRF.11 compliant Fax Relay
- In Band Signaling detection & generation
- Caller ID detection & generation

AudioCodes Enabling Technology Products

AC48304

SPECIFICATIONS

Software Specifications

Channel Density	Four low bit rate
Voice Coders	G.729 A CS-ACELP at 8 kbps G.723.1 MP-MLQ at 6.3 kbps, ACELP at 5.3 kbps G.727 E-ADPCM at 16-40 kbps G.726 ADPCM at 16-40 kbps G.711 PCM (μ -Law/A-Law) at 64 kbps NetCoder® at 6.4-9.6 kbps, 800 bps steps Optional: G.728 LD-CELP at 16 kbps (2 channels only)
Voice/Fax/Data	Automatic switching
Fax Support	G3 2.4 - 14.4 kbps, T.38 compliant fax relay or automatic switch to PCM
Modem Support	Up to V.92 rates, automatic switch to PCM
Echo Canceller	G.168-2000 compliant 25 msec tail length
Caller ID Detection and Generation	Bellcore Type 1 & 2, ETSI Type 1 & 2 NTT Number Display
In-band Signaling Detection and Generation	DTMF (TIA 464B), MFR1, MFR2, AC15, SS4, SS5, User Defined and Call Progress tones
Out-of-band Signaling	CAS ABCD (when connected to Standard Framers)
E&M Sampling Resolution	1 msec
Input/Output Gain Control	-31dB +31dB, 1.0 dB steps

Hardware Specifications

PCM Interface	2.048, 4.096 or 8.192 Mbps, μ -Law/A-Law (selectable)
Host Port Interface	8 bit Bidirectional
Power Supply	+1.8V (core), +3.3V (I/O)
Digital Interface Levels	3.3V logic compatible
Power Consumption	180 mW (typ)
Package	144 pin TQFP

APPLICATIONS

- Small Residential Gateways and IADs
- Cable Telephony Access Devices
- Voice over IP Gateways
- SOHO Voice/data/fax Access Devices
- DSL Access Devices
- Voice-enabled Set-top Boxes

ABOUT AUDIOCODES

AudioCodes Ltd. (NASDAQ: AUDC) enables the new voice infrastructure by providing innovative, reliable and cost-effective technology, products and system solutions to network equipment providers and system integrators. AudioCodes provides its customers and partners with a diverse range of flexible, comprehensive voice-over-packet media gateway and media processing technologies and systems, leading the transition to converged voice and data communications networks. The company is a market leader in voice compression technology and the key originator of the ITU G.723.1 standard for the emerging Voice over IP market. AudioCodes' product lines include media gateway system solutions for packet networks in the wireline, wireless, broadband access, media server and enhanced voice services markets, as well as enabling technology products such as VoIP communication boards, VoIP media gateway modules and CPE devices.

International Headquarters

4 HaHoresh Street
Yehud, Israel 56470
Tel: +972-3-539-4000
Fax: +972-3-539-4040

US Headquarters

2890 Zanker Road, Suite 200
San Jose, CA 95134
Tel: +1-408-577-0488
Fax: +1-408-577-0492

AudioCodes Offices Worldwide

Boston, Chicago, Beijing, Tokyo, Paris

info@audiocodes.com

www.audiocodes.com

© 2003 AudioCodes Ltd. All rights reserved. AC, AudioCodes, AudioCodes logo, AudioCoded, IPmedia, Mediant, MediaPack, MP-MLQ, NetCoder, Stretto, TrunkPack, VoicePacketizer and VolPerfect are trademarks or registered trademarks of AudioCodes Ltd. All other marks are the property of their respective owners. The information and specifications in this document and the product(s) are subject to change without notice. Ref # LTRT-00215 10/03 V.6

