


SPECIFICATION

Customer :	K.C.Dwg.No. :								
Customer's P/N:	K.C.P/N. : PJ1623MT								
(1) P/N FLM - 1 6 0 8 0 8 - R22 Inductance Inductance Tolerance Packaging Inductance Tolerance: J:± 5% , K:± 10% , M:± 20% Packaging Style: B: Bulk , T: Tape and Reel									
(2) Mechanical Dim.	(3) Electrical Characteristics								
	Type	L (uH)	Q	RDC	SRF	A	B	C	D
	Spec.	25 MHz	25 MHz	(OHM)	MHz	(m/m)	(m/m)	(m/m)	(m/m)
	Your								
	Suggest.	0.22±10%	15 ⁻⁰	0.8 ⁺⁰	150 ⁻⁰	1.6±0.2	0.8±0.2	0.8±0.2	0.3±0.2
	1	0.232	31.0	0.318	306.0	1.58	0.82	0.78	0.26
	2	0.220	31.0	0.346	306.0	1.62	0.84	0.82	0.32
	3	0.238	30.0	0.242	294.0	1.60	0.86	0.82	0.3
	4	0.230	32.0	0.308	296.0	1.62	0.80	0.78	0.26
	5	0.234	31.0	0.273	300.0	1.58	0.84	0.82	0.24
	6	0.227	31.0	0.308	301.0	1.54	0.82	0.81	0.26
	7	0.230	31.0	0.276	306.0	1.52	0.84	0.83	0.26
	8	0.240	31.0	0.274	302.0	1.56	0.86	0.82	0.24
	9	0.218	32.0	0.301	306.0	1.54	0.82	0.88	0.26
	10	0.208	30.0	0.304	306.0	1.56	0.80	0.84	0.26
	X	0.228	31.0	0.295	302.3	1.57	0.83	0.82	0.27
R	0.032	2.0	0.104	12.0	0.10	0.06	0.10	0.08	
(5) Condition In Testing:		(6) Test Instruments:							
..... Temp. 25 ⁰ C Humidity 55%		Inductance: HP 4291B RF impedance/material analyzer ...RDC : millohm meter 4338B ..Rated Current MAX:50mA							
Drawn by:	Checked by:	Approved by:							

ER029



King Core Electronics Inc.
 Tel:886-3-4782511(Rep.)
 Fax:886-3-4759923
 E-mail : kc@mail.kingcore.com.tw