

# Inductors

## For Power Line SMD

## RLF Series RLF12560 Type

Accompanying large current power supplies, these inductors have secured efficient characteristics by improving its magnetic circuit based on existing products. These products meet resistance reducing and current enlargement.

### FEATURES

- Comparing with existing products(RLF12545), DC current superimposition characteristic have improved. Especially, inductance rises about 10% in spite of high temperature at 100°C. In addition, inductance have risen about 30% at normal temperature.
- Using flat-square wire for winding, that is rising space factor, these inductors can reduce current resistance and suppress calorific value.
- Forming internal gap, their structure suppress outgoing magnetic flux leakage.
- Completely Pb free for both inside of products and terminal electrodes.


### APPLICATIONS

- Choke coils in power circuit of personal computers, crystal liquid television monitors, set top boxes, amusement equipments, etc.

### SPECIFICATIONS

Type	Operating temperature range [Including self-temperature rise]	Storage temperature range [Unit of products]
RLF12560	-20 to +105°C	-40 to +105°C

### RECOMMENDED REFLOW SOLDERING CONDITIONS



### PRODUCT IDENTIFICATIONS

RLF	12560	T-	1R0	N	140
(1)	(2)	(3)	(4)	(5)	(6)
(1) Series name					
(2) Dimensions L×W×T					
12560			12.5×12.5×6.0mm		
(3) Packaging style					
T			Taping(reel)		
(4) Inductance value					
1R0			1μH		
100			10μH		
(5) Inductance tolerance					
M			±20%		
N			±30%		
(6) Rated current					
8R2			8.2A		
140			14.4A		

### PACKAGING STYLE AND QUANTITIES

Packaging style	Type	Quantity
Taping	RLF12560T	500 pieces/reel



# Inductors

## For Power Line

### SMD

## RLF Series RLF12560 Type

### SHAPES AND DIMENSIONS/RECOMMENDED PC BOARD PATTERN



### ELECTRICAL CHARACTERISTICS


Inductance (μH)	Inductance tolerance (%)	Test frequency L (kHz)	DC resistance (mΩ)±20%	Rated current(A)		Part No.
				Based on inductance change	Based on temperature rise	
1.0	±30	100	2.8	18.5 max.	14.4 typ.	RLF12560T-1R0N140
1.9	±30	100	3.6	15.6 max.	12.7 typ.	RLF12560T-1R9N120
2.7	±30	100	4.5	14.4 max.	11.5 typ.	RLF12560T-2R7N110
4.2	±30	100	7.4	10.2 max.	10.0 typ.	RLF12560T-4R2N100
5.6	±30	100	8.5	9.7 max.	9.2 typ.	RLF12560T-5R6N9R2
7.8	±30	100	10.2	8.2 max.	8.4 typ.	RLF12560T-7R8N8R2
10	±20	100	12.4	7.5 max.	7.8 typ.	RLF12560T-100M7R5

\* Rated current: Value obtained when current flows and the temperature has risen to 40°C or when DC current flows and the initial value of inductance has fallen by 50%, whichever is smaller.

- Test equipment Inductance: YHP 4194A IMPEDANCE GAIN/PHASE ANALYZER, or equivalent
- DC resistance: DIGITAL MILLIOHM METER VP-2941A MATSUSHITA, or equivalent

### TYPICAL ELECTRICAL CHARACTERISTICS

#### INDUCTANCE CHANGE vs. DC SUPERPOSITION CHARACTERISTICS



#### MEASURING CIRCUIT

