

HMC387MS8


HIGH IP3 GaAs MMIC MIXER, 450 - 500 MHz

Typical Applications

High Dynamic Range Infrastructure:

- GSM 450 & GSM 480
- CDMA 450
- Private Land Mobile Radio

Functional Diagram



Features

- +32 dBm Input IP3
- Conversion Loss: 9.5 dB
- Low External Part Count
- Ultra Small MSOP8 Package: 14.8 mm²

General Description

The HMC387MS8 is a high dynamic range passive MMIC mixer in a plastic surface mount 8 lead Mini Small Outline Package (MSOP) covering 450 to 500 MHz. Excellent input IP3 performance of +32 dBm for down conversion and +29 dBm for up conversion is provided for both GSM/CDMA based cellular and Private Land Mobile Radio applications at an LO drive of +17dBm. The mixer also has excellent performance with as little as +13 dBm LO drive yielding a +30 dBm input IP3. With a 1 dB compression of +22 dBm, the RF port will accept a wide range of input signal levels. Conversion loss is 9.5 dB typical. The DC to 150 MHz IF frequency response will satisfy many cellular transmit or receive frequency plans. The HMC387MS8 input IP3 performance coupled with its high P1dB rivals traditional active FET mixers while offering a much smaller 14.8mm² standard IC footprint and no DC bias.


Electrical Specifications, $T_A = +25^\circ\text{C}$, LO = +17 dBm, IF = 70 MHz*

Parameter	Min.	Typ.	Max.	Units
Frequency Range, RF	450 - 500			MHz
Frequency Range, LO**	300 - 500			MHz
Frequency Range, IF	DC - 150			MHz
Conversion Loss		9.5	11	dB
Noise Figure (SSB)		9.5	11	dB
LO to RF Isolation	17	20		dB
LO to IF Isolation	20	23		dB
IP3 (Input)	29	32		dBm
1 dB Gain Compression (Input)	19	22		dBm
LO Input Drive Level (Typical)	+13 to +19			dBm


* Unless otherwise noted, all measurements performed as a downconverter with low side LO & IF = 70 MHz

** LO Frequency optimized. See application circuit herein.


**Conversion Gain vs.
Temperature @ LO = +17 dBm**




Isolation @ LO = +17 dBm




Conversion Gain vs. LO Drive




Return Loss @ LO = +17 dBm



IF Bandwidth @ LO = +17 dBm



**Upconverter Conversion Gain vs.
LO Drive**




* Unless otherwise noted, all measurements performed as a downconverter with low side LO & IF = 70 MHz


** LO Frequency optimized. See application circuit herein.

HIGH IP3 GaAs MMIC MIXER, 450 - 500 MHz


Input IP3 vs. Temperature
IF = 70 MHz, LO = +17 dBm




Input IP3 vs. LO Drive
IF = 70 MHz




Input IP3 vs. LO Drive
IF = 97 MHz




Input IP3 vs. LO Drive
IF = 117 MHz



Input IP3 vs. LO Drive
IF = 137 MHz




Upconverter Input IP3 vs. LO Drive
IF = 70 MHz




* Unless otherwise noted, all measurements performed as a downconverter with low side LO & IF = 70 MHz

** LO Frequency optimized. See application circuit herein.


Input IP2 vs. Temperature @ LO = +17 dBm



Input IP2 vs. LO Drive



Input P1dB vs. Temperature IF = 70 MHz



MxN Spurious Outputs

mRF	nLO				
	0	1	2	3	4
0	xx	-5	13	13	6
1	1.5	0	27	25	42
2	54	65	47	53	61
3	83	77	85	74	70
4	85	85	85	85	85

RF Freq = 0.45 GHz @ 0 dBm
LO Freq = 0.38 GHz @ +17 dBm
All values in dBc relative to the IF output power.

Harmonics of LO

LO Freq (GHz)	nLO Spur @ RF Port			
	1	2	3	4
0.35	27	37	38	39
0.37	26	35	43	39
0.39	25	34	44	41
0.41	24	33	41	43
0.43	23	32	38	44
0.45	22	31	37	45

LO = +17 dBm
All values are in dBc below input LO level @ RF port.




* LO Frequency optimized. See application circuit herein.

For price, delivery, and to place orders, please contact Hittite Microwave Corporation:
12 Elizabeth Drive, Chelmsford, MA 01824 Phone: 978-250-3343 Fax: 978-250-3373
Order Online at www.hittite.com

Absolute Maximum Ratings

RF/IF Input	+25 dBm
LO Drive	+27 dBm
Channel Temperature (Tc)	150 °C
Thermal Resistance	175 °C/W
Storage Temperature	-65 to +150 °C
Operating Temperature	-40 to +85 °C
IF DC Current	±40 mA





Outline Drawing




NOTES:

1. PACKAGE BODY MATERIAL: LOW STRESS INJECTION MOLDED PLASTIC SILICA AND SILICON IMPREGNATED.
 2. LEAD MATERIAL: COPPER ALLOY
 3. LEAD PLATING: Sn/Pb SOLDER
 4. DIMENSIONS ARE IN INCHES [MILLIMETERS]
 5. DIMENSION DOES NOT INCLUDE MOLDFLASH OF 0.15mm PER SIDE.
- △ DIMENSION DOES NOT INCLUDE MOLDFLASH OF 0.25mm PER SIDE.
 △ ALL GROUND LEADS MUST BE SOLDERED TO THE PCB RF GROUND

Pin Descriptions

Pin Number	Function	Description	Interface Schematic
1	LO	This pin is AC coupled & matched to 50 Ohms when an external series inductor (L1) and shunt capacitor (C1) is connected to the LO. Choose values of L1 and C1 to optimize LO frequency response. See Application Circuit herein.	
2, 4	N/C	Not connected.	
3, 6, 7	GND	This pin must be connected to RF ground.	
5	IF Port	This pin is DC coupled. For applications not requiring operation to DC this port should be DC blocked externally using a series capacitor. Choose value of C1 to pass IF frequency desired. For operation to DC, this pin must not sink/source more than 40 mA of current or failure may result.	
8	RF Port	This pin is DC coupled & matched to 50 Ohms from 450 - 500 MHz	

Evaluation PCB



List of Material


Item	Description
J1 - J3	PC Mount SMA RF Connector
C1	4 pF Chip Capacitor, 0603 Pkg
L1	47 nH Chip Inductor, 0805 Pkg
U1	HMC387MS8 Mixer
PCB*	106307 Eval Board
* Circuit Board Material: Rogers 4350	

The circuit board used in the final application should use RF circuit design techniques. Signal lines should have 50 ohm impedance while the package ground leads should be connected directly to the ground plane similar to that shown. A sufficient number of VIA holes should be used to connect the top and bottom ground planes. The evaluation circuit board shown is available from Hittite upon request.

* Unless otherwise noted, all measurements performed as a downconverter with low side LO & IF = 70 MHz

** LO Frequency optimized. See application circuit herein.

Application Circuit



Selection of L1 & C1 for Optimal LO Frequency $\pm 10\%$

Choose value of L1 & C1 to optimize LO Frequency response. For best results use an 0805 size RF inductor or smaller.

LO Frequency (MHz)	L1 (nH)	C1 (pF)
400	47	4

Note: Position L1 and C1 as close to Pin 1 as possible.

* Unless otherwise noted, all measurements performed as a downconverter with low side LO & IF = 70 MHz

** LO Frequency optimized. See application circuit herein.