

TOSHIBA TRANSISTOR SILICON NPN TRIPLE DIFFUSED TYPE

2SC5307


HIGH VOLTAGE SWITCHING APPLICATIONS

Unit in mm

- High Voltage : $V_{CE0} = 400V$
- Low Saturation Voltage
: $V_{CE(sat)} = 0.4V$ (Typ.) ($I_C = 20mA, I_B = 0.5mA$)

MAXIMUM RATINGS ($T_a = 25^\circ C$)

CHARACTERISTIC		SYMBOL	RATING	UNIT
Collector-Base Voltage		V_{CB0}	400	V
Collector-Emitter Voltage		V_{CE0}	400	V
Emitter-Base Voltage		V_{EB0}	7	V
Collector Current	DC	I_C	50	mA
	Pulse	I_{CP}	100	
Base Current		I_B	25	mA
Collector Power Dissipation	$T_a = 25^\circ C$	P_C	500	mW
	$T_a = 25^\circ C$ (Note)		1000	
Junction Temperature		T_j	150	$^\circ C$
Storage Temperature Range		T_{stg}	-55~150	$^\circ C$



(Note) : Mounted on Ceramic Substrate (250mm²×0.8t)

ELECTRICAL CHARACTERISTICS ($T_a = 25^\circ C$)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Collector Cut-off Current	I_{CB0}	$V_{CB} = 400V, I_E = 0$	—	—	1	μA
Emitter Cut-off Current	I_{EB0}	$V_{EB} = 7V, I_C = 0$	—	—	1	μA
Collector-Emitter Breakdown Voltage	V_{CE0}	$I_C = 1mA, I_B = 0$	400	—	—	V
DC Current Gain	$h_{FE(1)}$	$V_{CE} = 5V, I_C = 1mA$	80	—	—	
	$h_{FE(2)}$	$V_{CE} = 5V, I_C = 20mA$	100	—	300	
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 20mA, I_B = 0.5mA$	—	0.4	1.0	V
Base-Emitter Voltage	V_{BE}	$V_{CE} = 5V, I_C = 20mA$	—	0.7	0.85	V
Collector Output Capacitance	C_{ob}	$V_{CB} = 10V, I_E = 0, f = 1MHz$	—	4.0	—	pF

961001EAA2

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

