

# NPN SILICON RF POWER TRANSISTOR

**DESCRIPTION:**


The **ASI MRF374** is Designed for broadband commercial and industrial applications in 470 to 860 MHz band.

**FEATURES:**

- $P_G = 13.5$  dB typ. at 100 W/875 MHz
- $\eta_D = 36$  % Typical
- **Omnigold™** Metalization System

**MAXIMUM RATINGS**


$I_D$	7.0 A
$V_{DSS}$	65 V
$V_{GS}$	$\pm 20$ V
$P_{DISS}$	270 W @ $T_C = 25$ °C
$T_J$	-65 °C to +200 °C
$T_{STG}$	-65 °C to +150 °C
$\theta_{JC}$	0.65 °C/W


**CHARACTERISTICS**  $T_C = 25$  °C

SYMBOL	TEST CONDITIONS		MINIMUM	TYPICAL	MAXIMUM	UNITS
$V_{DSS}$	$I_{DS} = 1.0$ $\mu$ A		65			V
$I_{DSS}$	$V_{DS} = 28$ V				1.0	$\mu$ A
$I_{GSS}$	$V_{GS} = 20$ V				1.0	$\mu$ A
$V_{GS(th)}$	$V_{DS} = 10$ V	$I_D = 200$ $\mu$ A	2.0	3.5	4.0	V
$V_{GS(Q)}$	$V_{DS} = 28$ V	$I_D = 100$ mA	3.0	4.2	5.0	V
$V_{DS(ON)}$	$V_{DS} = 10$ V	$I_D = 3.0$ A		0.56	0.8	V
$G_{FS}$	$V_{DS} = 10$ V	$I_D = 3.0$ A	2.2	2.8		S

## CHARACTERISTICS $T_C = 25^\circ\text{C}$

SYMBOL	TEST CONDITIONS	MINIMUM	TYPICAL	MAXIMUM	UNITS
$C_{ISS}$ $C_{OSS}$ $C_{RSS}$	$V_{DS} = 28\text{ V}$ $V_{GS} = 0\text{ V}$ $f = 1.0\text{ MHz}$		80 45 3.5		pF
$P_G$ $\eta_D$ IMD VSWR	$V_{DD} = 28\text{ V}$ $I_{DQ} = 400\text{ mA}$ $P_{OUT} = 100\text{ W}$ $f_1 = 857\text{ MHz}$ , $f_2 = 863\text{ MHz}$	12.5 30 -28	13.5 36 -31		dB % dB ---
$P_G$ $\eta_D$ IMD	$V_{DD} = 28\text{ V}$ $I_{DQ} = 500\text{ mA}$ $P_{OUT} = 100\text{ W}$ $f_1 = 857\text{ MHz}$ , $f_2 = 863\text{ MHz}$		12 36 -34		dB % dB



- NOTES
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1994.
  2. CONTROLLING DIMENSION: INCH.
  3. DIMENSION H IS MEASURED 0.030 (0.762) AWAY FROM PACKAGE BODY.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	1.125	1.145	28.90	29.18
B	0.225	0.235	5.72	5.97
C	0.135	0.175	3.43	4.52
D	0.210	0.220	5.33	5.59
E	0.055	0.085	1.40	1.65
F	0.004	0.006	0.11	0.15
G	0.900 BSC		22.86 BSC	
H	0.077	0.087	1.95	2.21
K	0.220	0.250	5.60	6.35
L	0.160 BSC		4.06 BSC	
M	0.643	0.657	16.33	16.69
N	0.638	0.650	16.20	16.51
Q	0.125 @ 0.135	0.175 @ 0.185	3.18 @ 3.43	4.43 @ 4.69
R	0.227	0.233	5.77	5.92
S	0.225	0.235	5.73	5.97
bbb	0.018 BSC		0.454 BSC	
ooc	0.015 BSC		0.381 BSC	

- STYLE 1:  
PIN 1: DRAIN  
2: DRAIN  
3: GATE  
4: GATE  
5: SOURCE