


SOT23 NPN SILICON PLANAR GENERAL PURPOSE TRANSISTORS

ISSUE 4 – FEBRUARY 1997

**FMMT4400
FMMT4401**

PARTMARKING DETAILS: FMMT4400 - 1KZ
 FMMT4401 - 1L



ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE		UNIT
Collector-Base Voltage	V_{CBO}	60		V
Collector-Emitter Voltage	V_{CEO}	40		V
Emitter-Base Voltage	V_{EBO}	6		V
Continuous Collector Current	I_C	600		mA
Power Dissipation at $T_{amb}=25^\circ\text{C}$	P_{tot}	330		mW
Operating and Storage Temperature Range	$T_j:T_{stg}$	-55 to +150		°C

ELECTRICAL CHARACTERISTICS (at $T_{amb}=25^\circ\text{C}$ unless otherwise stated)

PARAMETER	SYMBOL	FMMT4400		FMMT4401		UNIT	CONDITIONS
		MIN.	MAX.	MIN.	MAX.		
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	40		40		V	$I_C=1\text{mA}, I_B=0$
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	60		60		V	$I_C=0.1\text{mA}, I_E=0$
Emitter-Base Breakdown Current	$V_{(BR)EBO}$	6		6		V	$I_E=0.1\text{mA}, I_C=0$
Collector-Emitter Cut-Off Current	I_{CEX}		0.1		0.1	μA	$V_{CE}=35\text{V}$ $V_{EB(\text{off})}=0.4\text{V}$
Base Cut-Off Current	I_{BEX}		0.1		0.1	μA	$V_{CE}=35\text{V}$ $V_{EB(\text{off})}=3\text{V}$
Static Forward Current Transfer Ratio	h_{FE}	20 40 50 20	150	20 40 80 100 40	300		$I_C=0.1\text{mA}, V_{CE}=1\text{V}$ $I_C=1\text{mA}, V_{CE}=1\text{V}$ $I_C=10\text{mA}, V_{CE}=1\text{V}$ $I_C=150\text{mA}, V_{CE}=1\text{V}^*$ $I_C=500\text{mA}, V_{CE}=2\text{V}^*$
Collector-Emitter Saturation Voltage	$V_{CE(\text{sat})}$		0.4 0.75		0.4 0.75	V	$I_C=150\text{mA}, I_B=15\text{mA}^*$ $I_C=500\text{mA}, I_B=50\text{mA}^*$
Base-Emitter Saturation Voltage	$V_{BE(\text{sat})}$	0.75	0.95 1.2	0.75	0.95 1.2	V	$I_C=150\text{mA}, I_B=15\text{mA}^*$ $I_C=500\text{mA}, I_B=50\text{mA}^*$
Transition Frequency	f_T	200		250		MHz	$I_C=20\text{mA}, V_{CE}=10\text{V}$ $f=100\text{kHz}$
Output Capacitance	C_{obo}		6.5		6.5	pF	$V_{CB}=5\text{V}, I_E=0$ $f=100\text{kHz}$
Input Capacitance	C_{ibo}		30		30	pF	$V_{BE}=0.5\text{V}, I_C=0$ $f=100\text{kHz}$

*Measured under pulsed conditions. Pulse width=300μs. Duty cycle ≤ 2%

**FMMT4400
FMMT4401**

SWITCHING CHARACTERISTICS (at $T_{amb} = 25^{\circ}C$)

PARAMETER	SYMBOL	MIN.	MAX.	UNIT	CONDITIONS
Turn-On Time	t_{on}		35	ns	$V_{CC}=30V$, $V_{BE(off)}=2V$ $I_C=150mA$, $I_{B1}=15mA$ (See Fig. 1)
Turn-Off Time	t_{off}		255	ns	$V_{CC}=30V$, $I_C=150mA$ $I_{B1}=I_{B2}=15mA$ (See Fig. 2)