



* 0.95mm high version available on request.

Features

- ▄▄▄▄ **High shock & vibration resistance**
- ▄▄▄▄ **Military temperature range option**
- ▄▄▄▄ **Low power consumption**
- ▄▄▄▄ **Miniature ceramic package**

Standard Calibration Tolerances

32.0 ~ 200kHz	201 ~ 560kHz	561kHz ~ 1.0MHz
±30ppm	±100ppm	±100ppm
±100ppm	±250ppm	±500ppm

Specifications

Parameters	Product	Option
	CC4V	Code
Terminations: Gold plated pads Ni+Sn plated pads	<input checked="" type="checkbox"/> <input type="checkbox"/>	T1 T2
Frequency range: 32.768kHz 32.0kHz ~ 1.0MHz	<input checked="" type="checkbox"/> <input type="checkbox"/>	
Calibration tolerance: see table Other	<input checked="" type="checkbox"/> <input type="checkbox"/>	specify
Operating temperature range: -40 to +85°C -55 to +125°C	<input checked="" type="checkbox"/> <input type="checkbox"/>	I M
Storage temperature range: -55 to +125°C	<input checked="" type="checkbox"/>	
Circuit condition: 9pF (32.0 ~ 200kHz) 4pF (201 ~ 560kHz) 10pF (560kHz ~ 1.0MHz)	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	
Static capacitance (C₀): 1.4pF typ	<input checked="" type="checkbox"/>	
Motional capacitance (C₁): 2.35fF typ	<input checked="" type="checkbox"/>	
Equivalent series resistance: 50kΩ typ, 80kΩ max	<input checked="" type="checkbox"/>	
Ageing: ±3ppm max first year	<input checked="" type="checkbox"/>	
Drive level: 1.0μW max	<input checked="" type="checkbox"/>	
Turnover temperature (T₀): +25°C ±5°C	<input checked="" type="checkbox"/>	
Frequency / temp coefficient: -0.038ppm/°C ² typ	<input checked="" type="checkbox"/>	
Shock resistance: ±5ppm, 5,000g, 0.3ms, ½ sine	<input checked="" type="checkbox"/>	
Vibration resistance: ±5ppm, 20g, 10.0 ~ 2,000Hz	<input checked="" type="checkbox"/>	
Soldering condition: Reflow, 260°C, 20 sec max	<input checked="" type="checkbox"/>	

■ Standard. □ Optional - Please specify required code(s) when ordering

Ordering Information

Product name + termination + option codes + frequency + calibration tolerance

eg: **CC4V-T1/I 32.768kHz ±30ppm** -40+85°C

CC4V-T1/M 32.0kHz ±10ppm -55+125°C

Option code X (eg CC4V-T1/X) denotes a custom specification.

- ◆ Available on T&R (2k or 10k pcs/reel) or trays (100pcs/tray).
- ◆ Refer to our website for T&R and soldering details.
- ◆ Ask about higher shock & vibration specifications.