


ZXMHC3A01T8

COMPLEMENTARY 30V ENHANCEMENT MODE MOSFET H-BRIDGE

SUMMARY

N-Channel = $V_{(BR)DSS} = 30V$: $R_{DS(on)} = 0.12\Omega$; $I_D = 3.1A$
P-Channel = $V_{(BR)DSS} = -30V$: $R_{DS(on)} = 0.21\Omega$; $I_D = -2.3A$



SM8

DESCRIPTION


This new generation of trench MOSFETs from Zetex utilizes a unique structure that combines the benefits of low on-resistance with fast switching speed. This makes them ideal for high efficiency, low voltage, power management applications.

FEATURES

- Low on-resistance
- Fast switching speed
- Low threshold
- Low gate drive
- Single SM-8 surface mount package

APPLICATIONS


- Single phase DC fan motor drive



ORDERING INFORMATION

| DEVICE | REEL SIZE | TAPE WIDTH | QUANTITY PER REEL |
|---------------|-----------|------------|-------------------|
| ZXMHC3A01T8TA | 7" | 12mm | 1,000 units |
| ZXMHC3A01T8TC | 13" | 12mm | 4,000 units |

PINOUT



Top View

DEVICE MARKING

- ZXMH
C3A01

ZXMHC3A01T8

ABSOLUTE MAXIMUM RATINGS

| PARAMETER | SYMBOL | N-Channel | P-channel | UNIT |
|--|-----------------------------------|-------------------|----------------------|-------|
| Drain-source voltage | V _{DSS} | 30 | -30 | V |
| Gate-source voltage | V _{GS} | ±20 | ±20 | V |
| Continuous drain current (V _{GS} = 10V; T _A =25°C) ^{(b)(d)} (V _{GS} = 10V; T _A =70°C) ^{(b)(d)} (V _{GS} = 10V; T _A =25°C) ^{(a)(d)} | I _D | 3.1 2.5 2.7 | -2.3 -1.8 -2.0 | A |
| Pulsed drain current ^(c) | I _{DM} | 14.5 | -10.8 | A |
| Continuous source current (body diode) ^(b) | I _S | 2.3 | -2.2 | A |
| Pulsed source current (body diode) ^(c) | I _{SM} | 14.5 | -10.8 | A |
| Power dissipation at T _A =25°C ^{(a) (d)} | P _D | 1.3 | | W |
| Linear derating factor | | 10.4 | | mW/°C |
| Power dissipation at T _A =25°C ^{(b) (d)} | P _D | 1.7 | | W |
| Linear derating factor | | 13.6 | | mW/°C |
| Operating and storage temperature range | T _j , T _{stg} | -55 to +150 | | °C |

THERMAL RESISTANCE


| PARAMETER | SYMBOL | VALUE | UNIT |
|--|------------------|-------|------|
| Junction to ambient ^{(a) (d)} | R _{θJA} | 96 | °C/W |
| Junction to ambient ^{(b) (d)} | R _{θJA} | 73 | °C/W |

NOTES

- (a) For a device surface mounted on 50mm x 50mm x 1.6mm FR4 PCB with high coverage of single sided 2oz copper, in still air conditions.
- (b) For a device surface mounted on FR4 PCB measured at t ≤ 10 sec.
- (c) Repetitive rating on 50mm x 50mm x 1.6mm FR4, D= 0.02, pulse width 300µS · pulse width limited by maximum junction temperature. Refer to transient thermal impedance graph.
- (d) For device with one active die.

ZXMHC3A01T8

CHARACTERISTICS



ZXMHC3A01T8

N-channel

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^\circ C$ unless otherwise stated)

| PARAMETER | SYMBOL | MIN. | TYP. | MAX. | UNIT | CONDITIONS |
|--|---------------|------|------|--------------|----------|---|
| STATIC | | | | | | |
| Drain-source breakdown voltage | $V_{(BR)DSS}$ | 30 | | | V | $I_D = 250\mu A, V_{GS}=0V$ |
| Zero gate voltage drain current | I_{DSS} | | | 1.0 | μA | $V_{DS}=30V, V_{GS}=0V$ |
| Gate-body leakage | I_{GSS} | | | 100 | nA | $V_{GS}=\pm 20V, V_{DS}=0V$ |
| Gate-source threshold voltage | $V_{GS(th)}$ | 1.0 | | 3.0 | V | $I_D = 250\mu A, V_{DS}=V_{GS}$ |
| Static drain-source on-state resistance ⁽¹⁾ | $R_{DS(on)}$ | | | 0.12 0.18 | Ω | $V_{GS} = 10V, I_D = 2.5A$ $V_{GS} = 4.5V, I_D = 2.0A$ |
| Forward transconductance ^{(1) (3)} | g_{fs} | | 3.5 | | S | $V_{DS}=4.5V, I_D= 2.5A$ |
| DYNAMIC ⁽³⁾ | | | | | | |
| Input capacitance | C_{iss} | | 190 | | pF | $V_{DS}= 25V, V_{GS}=0V$ |
| Output capacitance | C_{oss} | | 38 | | pF | $f=1MHz$ |
| Reverse transfer capacitance | C_{rss} | | 20 | | pF | |
| SWITCHING^{(2) (3)} | | | | | | |
| Turn-on-delay time | $t_{d(on)}$ | | 1.7 | | ns | $V_{DD} = 15V, I_D = 2.5A$ $R_G \approx 6.0\Omega, V_{GS} = 10V$ |
| Rise time | t_r | | 2.3 | | ns | |
| Turn-off delay time | $t_{d(off)}$ | | 6.6 | | ns | |
| Fall time | t_f | | 2.9 | | ns | |
| Total gate charge | Q_g | | 3.9 | | nC | $V_{DS} = 15V, V_{GS} = 10V$ $I_D = 2.5A$ |
| Gate-source charge | Q_{gs} | | 0.6 | | nC | |
| Gate drain charge | Q_{gd} | | 0.9 | | nC | |
| SOURCE-DRAIN DIODE | | | | | | |
| Diode forward voltage ⁽¹⁾ | V_{SD} | | | 0.95 | V | $T_j=25^\circ C, I_S = 1.7A,$ $V_{GS}=0V$ |
| Reverse recovery time ⁽³⁾ | t_{rr} | | 17.7 | | ns | $T_j=25^\circ C, I_S = 2.5A,$ $di/dt=100A/\mu s$ |
| Reverse recovery charge ⁽³⁾ | Q_{rr} | | 13.0 | | nC | |


NOTES

- (1) Measured under pulsed conditions. Pulse width $\leq 300\mu s$; duty cycle $\leq 2\%$.
 (2) Switching characteristics are independent of operating junction temperature.
 (3) For design aid only, not subject to production testing.

ZXMHC3A01T8

N-channel


TYPICAL CHARACTERISTICS



ZXMHC3A01T8

N-channel

TYPICAL CHARACTERISTICS



ZXMHC3A01T8

P-channel

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^\circ C$ unless otherwise stated)

| PARAMETER | SYMBOL | MIN. | TYP. | MAX. | UNIT | CONDITIONS |
|--|---------------|------|-------|--------------|----------|---|
| STATIC | | | | | | |
| Drain-source breakdown voltage | $V_{(BR)DSS}$ | -30 | | | V | $I_D = -250\mu A, V_{GS}=0V$ |
| Zero gate voltage drain current | I_{DSS} | | | -1.0 | μA | $V_{DS} = -30V, V_{GS}=0V$ |
| Gate-body leakage | I_{GSS} | | | 100 | nA | $V_{GS} = \pm 20V, V_{DS}=0V$ |
| Gate-source threshold voltage | $V_{GS(th)}$ | -1.0 | | -3.0 | V | $I_D = -250\mu A, V_{DS}=V_{GS}$ |
| Static drain-source on-state resistance ⁽¹⁾ | $R_{DS(on)}$ | | | 0.21 0.33 | Ω | $V_{GS} = -10V, I_D = -1.4A$ $V_{GS} = -4.5V, I_D = -1.1A$ |
| Forward transconductance ^{(1) (3)} | g_{fs} | | 2.5 | | S | $V_{DS} = -15V, I_D = -1.4A$ |
| DYNAMIC ⁽³⁾ | | | | | | |
| Input capacitance | C_{iss} | | 204 | | pF | $V_{DS} = -15V, V_{GS}=0V$ |
| Output capacitance | C_{oss} | | 39.8 | | pF | $f=1MHz$ |
| Reverse transfer capacitance | C_{rss} | | 25.8 | | pF | |
| SWITCHING^{(2) (3)} | | | | | | |
| Turn-on-delay time | $t_{d(on)}$ | | 1.2 | | ns | $V_{DD} = -15V, I_D = -1A$ |
| Rise time | t_r | | 2.3 | | ns | $R_G \equiv 6.0\Omega, V_{GS} = -10V$ |
| Turn-off delay time | $t_{d(off)}$ | | 12.1 | | ns | |
| Fall time | t_f | | 7.5 | | ns | |
| Total gate charge | | | 2.6 | | nC | $V_{DS} = -15V, V_{GS} = -5V$ $I_D = -1.4A$ |
| Total gate charge | Q_g | | 5.2 | | nC | $V_{DS} = -15V, V_{GS} = -10V$ $I_D = -1.4A$ |
| Gate-source charge | Q_{gs} | | 0.7 | | nC | |
| Gate drain charge | Q_{gd} | | 0.9 | | nC | |
| SOURCE-DRAIN DIODE | | | | | | |
| Diode forward voltage ⁽¹⁾ | V_{SD} | | -0.85 | -0.95 | V | $T_j = 25^\circ C, I_S = -1.1A,$ $V_{GS}=0V$ |
| Reverse recovery time ⁽³⁾ | t_{rr} | | 19 | | ns | $T_j = 25^\circ C, I_S = -0.95A,$ $di/dt = 100A/\mu s$ |
| Reverse recovery charge ⁽³⁾ | Q_{rr} | | 15 | | nC | |


NOTES

- (1) Measured under pulsed conditions. Pulse width $\leq 300\mu s$; duty cycle $\leq 2\%$.
- (2) Switching characteristics are independent of operating junction temperature.
- (3) For design aid only, not subject to production testing.

ZXMHC3A01T8

P-channel


TYPICAL CHARACTERISTICS



ZXMHC3A01T8


P-channel

TYPICAL CHARACTERISTICS



ZXMHC3A01T8

PACKAGE OUTLINE



Controlling dimensions are in millimeters. Approximate conversions are given in inches

PACKAGE DIMENSIONS

| DIM | Millimeters | | | Inches | | | DIM | Millimeters | | | Inches | | |
|-----|-------------|------|------|--------|-------|--------|----------|-------------|-----|------|--------|-------|--------|
| | Min | Max | Typ. | Min | Max | Typ. | | Min | Max | Typ. | Min | Max | Typ. |
| A | - | 1.7 | - | - | 0.067 | - | e1 | - | - | 4.59 | - | - | 0.1807 |
| A1 | 0.02 | 0.1 | - | 0.008 | 0.004 | - | e2 | - | - | 1.53 | - | - | 0.0602 |
| b | - | - | 0.7 | - | - | 0.0275 | He | 6.7 | 7.3 | - | 0.264 | 0.287 | - |
| c | 0.24 | 0.32 | - | 0.009 | 0.013 | - | Lp | 0.9 | - | - | 0.035 | - | - |
| D | 6.3 | 6.7 | - | 0.248 | 0.264 | - | α | - | 15° | - | - | 15° | - |
| E | 3.3 | 3.7 | - | 0.130 | 0.145 | - | β | - | - | 10° | - | - | 10° |

© Zetex Semiconductors plc 2004

| Europe | Americas | Asia Pacific | Corporate Headquarters |
|---|--|--|---|
| Zetex GmbH Streifeldstraße 19 D-81673 München Germany | Zetex Inc 700 Veterans Memorial Hwy Hauppauge, NY 11788 USA | Zetex (Asia) Ltd 3701-04 Metroplaza Tower 1 Hing Fong Road, Kwai Fong Hong Kong | Zetex plc Lansdowne Road, Chadderton Oldham, OL9 9TY United Kingdom |
| Telephone: (49) 89 45 49 49 0 Fax: (49) 89 45 49 49 49 europe.sales@zetex.com | Telephone: (1) 631 360 2222 Fax: (1) 631 360 8222 usa.sales@zetex.com | Telephone: (852) 26100 611 Fax: (852) 24250 494 asia.sales@zetex.com | Telephone (44) 161 622 4444 Fax: (44) 161 622 4446 hq@zetex.com |

These offices are supported by agents and distributors in major countries world-wide.

This publication is issued to provide outline information only which (unless agreed by the Company in writing) may not be used, applied or reproduced for any purpose or form part of any order or contract or be regarded as a representation relating to the products or services concerned. The Company reserves the right to alter without notice the specification, design, price or conditions of supply of any product or service.

For the latest product information, log on to www.zetex.com