The RF Line 77-Channel (550 MHz) CATV Input/Output Trunk Amplifier

. . . designed specifically for 550 MHz CATV applications. Features ion–implanted arsenic emitter transistors with 7 GHz fT and an all gold metallization system.

- Specified for 77–Channel Performance
- Broadband Power Gain @ f = 40-550 MHz G_p = 17.2 dB (Typ)
- Broadband Noise Figure @ f = 550 MHz NF = 6 dB (Typ)
- Superior Gain, Return Loss and DC Current Stability with Temperature
- All Gold Metallization
- 7 GHz Ion-Implanted Transistors

CASE 714-06, STYLE 1

OTOROLA

ABSOLUTE MAXIMUM RATINGS


Rating	Symbol	Value	Unit
RF Voltage Input (Single Tone)	V _{in}	+70	dBmV
DC Supply Voltage	VCC	+28	Vdc
Operating Case Temperature Range	т _С	-20 to +100	°C
Storage Temperature Range	T _{stg}	-40 to +100	°C

ELECTRICAL CHARACTERISTICS ($V_{CC} = 24$ Vdc, $T_{C} = +30^{\circ}$ C, 75 Ω system unless otherwise noted)

Characteristic		Symbol	Min	Тур	Max	Unit
Frequency Range		BW	40	—	550	MHz
Power Gain	50 MHz	Gp	16.8	17.2	17.8	dB
Slope		S	0	+0.5	2.0	dB
Gain Flatness (Peak To Valley)		—	—	0.2	0.4	dB
Return Loss — Input/Output (Z ₀ = 75 Ohms)	40-550 MHz	IRL/ORL	18	_	—	dB
Second Order Intermodulation (V _{out} = +46 dBmV per ch., Ch 2, M13, M22) (V _{out} = +44 dBmV per ch., Ch 2, M30, M39)		IMD	=	-80 -78	 _70	dB
Cross Modulation Distortion (V _{out} = +46 dBmV per ch.) (V _{out} = +44 dBmV per ch.)	60–Channel FLAT 77–Channel FLAT	XMD ₆₀ XMD ₇₇	=	-63 -65	 _62	dB
Composite Triple Beat Noise (V _{out} = +46 dBmV per ch.) (V _{out} = +44 dBmV per ch.)	60–Channel FLAT 77–Channel FLAT	СТВ ₆₀ СТВ ₇₇	=	-62 -60	 _59	dB
Noise Figure	450 MHz 550 MHz	NF		5.5 6	7	dB
DC Current		IDC	—	210	240	mA

17 dB GAIN 550 MHz 77–CHANNEL CATV AMPLIFIER

PACKAGE DIMENSIONS



Motorola reserves the right to make changes without further notice to any products herein. Motorola makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Motorola assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters can and do vary in different applications. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Motorola does not convey any license under its patent rights nor the rights of others. Motorola products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Motorola product could create a situation where personal injury or death may occur. Should Buyer purchase or use Motorola products for any such unintended or unauthorized application, Buyer shall indemnify and hold Motorola and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death Motorola was negligent regarding the design or manufacture of the part. Motorola and are registered trademarks of Motorola, Inc. Motorola, Inc. is an Equal Opportunity/Affirmative Action Employer.

Literature Distribution Centers:

USA: Motorola Literature Distribution; P.O. Box 20912; Phoenix, Arizona 85036. EUROPE: Motorola Ltd.; European Literature Centre; 88 Tanners Drive, Blakelands, Milton Keynes, MK14 5BP, England. JAPAN: Nippon Motorola Ltd.; 4-32-1, Nishi-Gotanda, Shinagawa-ku, Tokyo 141, Japan. ASIA PACIFIC: Motorola Semiconductors H.K. Ltd.; Silicon Harbour Center, No. 2 Dai King Street, Tai Po Industrial Estate, Tai Po, N.T., Hong Kong.



٥

