



features

- 390nm wavelength
- $\pm 35^\circ$ emission angle
- Cathodes connected to case
- RoHS compliant

applications

- identifying petroleum deposits in down-hole drilling operations
- currency validation
- security
- water purification
- UV epoxy curing

description

The CLE509 contains nine, parallel connected, 390nm LED die mounted on a TO-46 header. Custom variations are available which can contain from one to nine elements. Special lenses and multiple lead packages are also available. Call Clairex for more information.

absolute maximum ratings ($T_A = 25^\circ\text{C}$ unless otherwise stated)

storage temperature	-40°C to +150°C
operating temperature	-40°C to +125°C
lead soldering temperature ⁽¹⁾	260°C
continuous forward current, each diode ⁽²⁾	20mA
peak forward current, each diode (1.0ms pulse width, 10% duty cycle)	0.5A
reverse voltage	5.0V
continuous power dissipation ⁽³⁾	350mW

notes:

1. 0.06" (1.5mm) from case for 5 seconds maximum.
2. Derate linearly 0.21mA/°C from 25°C free air temperature to $T_A = +125^\circ\text{C}$.
3. Derate linearly 3.73mW/°C from 25°C free air temperature to $T_A = +125^\circ\text{C}$.

**Exercise caution when applying power to this unit.
It emits high amounts of UV radiation.**

electrical characteristics ($T_A = 25^\circ\text{C}$ unless otherwise noted)

symbol	parameter	min	typ	max	units	test conditions
P_o	Total power output ⁽⁴⁾	13.5	-	-	mW	$I_F = 180\text{mA}^{(5)}$
V_F	Forward voltage	-	3.0	3.9	V	$I_F = 180\text{mA}^{(5)}$
I_R	Reverse current (per diode)	-	-	10	μA	$V_R = 5.0\text{V}$
λ_p	Peak emission wavelength	375	390	405	nm	$I_F = 180\text{mA}^{(5)}$
θ_{HP}	Emission angle at half power points	-	70	-	deg.	$I_F = 180\text{mA}^{(5)}$

note: 4. Measured with both anode leads connected together.

5. This equates to 20mA per diode.