

CET



CEP1165/CEB1165 □ CEF1165

N-Channel Enhancement Mode Field Effect Transistor

FEATURES

Type	V _{DSS}	R _{DS(ON)}	I _D	@V _{GS}
CEP1165	600V	0.9Ω	10A	10V
CEB1165	600V	0.9Ω	10A	10V
CEF1165	600V	0.9Ω	10A ^e	10V

- Super high dense cell design for extremely low R_{DS(ON)}.
- High power and current handing capability.
- Lead free product is acquired.

CEB SERIES
TO-263(DD-PAK)CEP SERIES
TO-220CEF SERIES
TO-220F

ABSOLUTE MAXIMUM RATINGS T_C = 25°C unless otherwise noted

Parameter	Symbol	Limit		Units
		TO-220/263	TO-220F	
Drain-Source Voltage	V _{DS}	600		V
Gate-Source Voltage	V _{GS}	±30		V
Drain Current-Continuous	I _D	10	10 ^e	A
Drain Current-Pulsed ^a	I _{DM} ^f	40	40 ^e	A
Maximum Power Dissipation @ T _C = 25°C - Derate above 25°C	P _D	167 1.33	50 0.4	W W/°C
Operating and Store Temperature Range	T _{J,Tstg}	-55 to 150		°C

Thermal Characteristics

Parameter	Symbol	Limit		Units
Thermal Resistance, Junction-to-Case	R _{θJC}	0.75	2.5	°C/W
Thermal Resistance, Junction-to-Ambient	R _{θJA}	62.5	65	°C/W



CEP1165/CEB1165

CEF1165

Electrical Characteristics $T_C = 25^\circ\text{C}$ unless otherwise noted

4

Parameter	Symbol	Test Condition	Min	Typ	Max	Units
Off Characteristics						
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{\text{GS}} = 0\text{V}, I_D = 250\mu\text{A}$	600			V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{\text{DS}} = 600\text{V}, V_{\text{GS}} = 0\text{V}$			10	μA
Gate Body Leakage Current, Forward	I_{GSSF}	$V_{\text{GS}} = 30\text{V}, V_{\text{DS}} = 0\text{V}$			100	nA
Gate Body Leakage Current, Reverse	I_{GSSR}	$V_{\text{GS}} = -30\text{V}, V_{\text{DS}} = 0\text{V}$			-100	nA
On Characteristics^b						
Gate Threshold Voltage	$V_{\text{GS(th)}}$	$V_{\text{GS}} = V_{\text{DS}}, I_D = 250\mu\text{A}$	2		4	V
Static Drain-Source On-Resistance	$R_{\text{DS(on)}}$	$V_{\text{GS}} = 10\text{V}, I_D = 5\text{A}$		0.75	0.9	Ω
Dynamic Characteristics^c						
Forward Transconductance	g_{FS}	$V_{\text{DS}} = 5\text{V}, I_D = 10\text{A}$		6		S
Input Capacitance	C_{iss}	$V_{\text{DS}} = 25\text{V}, V_{\text{GS}} = 0\text{V}, f = 1.0 \text{ MHz}$		1780		pF
Output Capacitance	C_{oss}			170		pF
Reverse Transfer Capacitance	C_{rss}			25		pF
Switching Characteristics^c						
Turn-On Delay Time	$t_{\text{d(on)}}$	$V_{\text{DD}} = 300\text{V}, I_D = 10\text{A}, V_{\text{GS}} = 10\text{V}, R_{\text{GEN}} = 10\Omega$		18	36	ns
Turn-On Rise Time	t_r			8	16	ns
Turn-Off Delay Time	$t_{\text{d(off)}}$			37	64	ns
Turn-Off Fall Time	t_f			7	14	ns
Total Gate Charge	Q_g	$V_{\text{DS}} = 480\text{V}, I_D = 10\text{A}, V_{\text{GS}} = 10\text{V}$		30	38	nC
Gate-Source Charge	Q_{gs}			9.2		nC
Gate-Drain Charge	Q_{gd}			7.8		nC
Drain-Source Diode Characteristics and Maximum Ratings						
Drain-Source Diode Forward Current ^g	I_S				10	A
Drain-Source Diode Forward Voltage ^b	V_{SD}	$V_{\text{GS}} = 0\text{V}, I_S = 10\text{A}$ ^g			1.5	V

Notes :

- a.Repetitive Rating : Pulse width limited by maximum junction temperature .
- b.Pulse Test : Pulse Width $\leq 300\mu\text{s}$, Duty Cycle $\leq 2\%$.
- c.Guaranteed by design, not subject to production testing.
- e.Limited only by maximum temperature allowed .
- f.Pulse width limited by safe operating area .
- g.Full package $I_{\text{S(max)}} = 4.7\text{A}$.

CEP

CEP1165/CEB1165 □

CEF1165




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Capacitance




Figure 4. On-Resistance Variation with Temperature




Figure 5. Gate Threshold Variation with Temperature




Figure 6. Body Diode Forward Voltage Variation with Source Current




Figure 7. Gate Charge




Figure 8. Maximum Safe Operating Area




Figure 9. Switching Test Circuit




Figure 10. Switching Waveforms




Figure 11. Normalized Thermal Transient Impedance Curve