Rail Mounted Terminal Blocks 9503310000



KDKS 1 (TS35)

Email to a Friend	View Catalog Page	
Sales Information	Back to StepSearch	
Catalog Home		



Representative Phot

Technical Information

Clamping Type Screw Clamp
Series W Series
Rail Type TS 35

Function Circuit Protection Disconnect

Configuration Fuse and Feed Through Lever and Feed Through

Wire Size #22...12 AWG

Current 10 A upper level, 20 A lower level

Voltage 300 V Color/Material Beige PA

Technical Data

	UL	CSA	VDE
Rated Voltage	300 V	300 V	500 V
Rated Current	10 A 20 A	10 A 25 A	
Wire Size	#2212 AWG	#2212 AWG	4 mm²

Additional Data

Width/Length/Height mm (in.) 8/73.5/55.7 (.31"/2.89"/2.19")

Insulation Stripping Length mm (in.) 9 (.35")

Torque Nm (lb. in) 0.6 (5.5)

Clamping Screw M 3

Flammability Class UL 94 (V2)

Suggested Accessories

DIN-rail
End bracket

End plate/partition (AP/TW)

<u>Ferrules</u>

<u>Fuses</u>

Marking pens

Marking tags (DEK)
Mounting brackets

Tools

Product Liability The above information describes our products. It does not constitute guaranteed properties and is not intended to a the suitability of a product for a particular application. Regrettably, omissions and exceptions cannot be completely ruled out. Techni data are always specified by their average values. Exact data and the tolerances which apply to our processes can be requested from

Weidmüller - North America United States 001 (800) 849-9343 Canada 001 (800) 268-4080

or

Weidmüller - Germany Telephone operator 0049 (-5252) 960-0