




AMERICAN MICROSEMICONDUCTOR INC.

P. O. Box 104  
 Madison, New Jersey 07940 U. S. A.  
<http://www.americanmicrosemi.com>  
 email:sales@americanmicrosemi.com

Phone: (973) 377-9566 Fax: (973) 377-3078

ADA1107P

Switching Diode Array



FEATURES

- Dual 8 Diode Array
- Standard 14 pin Dual-In-Line Package
- UL 94V-0 Flammability Classification

MECHANICAL

- Molded 14 Pin Dip
- Weight: 0.997 grams (approximate)
- Marking: Logo, device number, date code
- Pin #1 defined by DOT on top of package


MAXIMUM RATINGS

- Operating Temperatures: -55°C to +150°C
- Storage Temperature: -55°C to +150°C
- Forward Surge Current: 2.0 Amps (8.3 mS)
- Minimum Breakdown Voltage  $V_{(BR)}$ : 90V
- Working Peak Reverse Voltage  $V_{RWM}$ : 75V
- Continuous forward current  $I_F$ : 400 mA
- Power dissipation ( $P_D$ ): 500 mW
- Derating factor: 4.0 mW/°C

PACKAGING

- Carrier tube 25 pcs per (STANDARD)

CIRCUIT DIAGRAM



ELECTRICAL CHARACTERISTICS @ 25°C Unless otherwise specified

Part Number	$V_{(BR)}$ @100 $\mu$ A V	$V_{RWM}$ V	$I_R$ +25°C $\mu$ A		$I_R$ +150°C $\mu$ A		CAP @0V pF	$V_F$ @ $I_f = 10$ mA V	$V_F$ @ $I_f = 100$ mA V
	MIN	MAX	MAX	@ $V_R$	MAX	@ $V_R$	MAX	MAX	MAX
ADA1107P	90	75	.100	20	200	20	4.0	1.00	1.20

