


High power Quasi-CW operation

■ FEATURES

- High optical power : 50 to 100W/bar in average
- High stability
- Long life
- High cost performance

■ APPLICATIONS

- Pumping source for solid state lasers
- Materials processing
- Welding
- Soldering
- Medical systems



Our high power Quasi-CW laser diode, L8411, features several advantages such as high stability with long life, high cost performance with compact structure, and higher peak intensity. It can be applied as light source to pump solid state lasers, for material processing like welding or soldering, and for medical systems. The lasing areas consist of small laser emitters arranged in line and are thus called "Bar" structure. A high Quasi-CW output power as high as 10kW at peak was achieved by stacking ten Bars. Cooling methods can be selected from Peltier-cooling, water-cooling and Funryu-cooling (patent pending : Japan 8-139479, WO 00/11717). A high power laser module with a focusing lens and a driving electronics are optionally available.

■ ABSOLUTE MAXIMUM RATINGS (Each bar)

Parameter	Symbol	Low Duty Ratio Type	High Duty Ratio Type	Unit
Radiant Output Power / bar	ϕ_e	105	55	W
Reverse Voltage	V_R	2.0	2.0	V
Pulse Duration	T_w	200	200	μsec
Duty Ratio	DR	1	20	%
Operating Temperature	T_{op}	+15 to +35		$^{\circ}\text{C}$
Storage Temperature	T_{stg}	-20 to +40		$^{\circ}\text{C}$

■ CHARACTERISTICS (Each bar, $T_a=20^{\circ}\text{C}$)

Parameter	Symbol	Low Duty Ratio Type		High Duty Ratio Type		Unit
		Conditions	Value	Conditions	Value	
Radiant Output Power / bar	ϕ_e		100		50	W
Forward Current	I_F	$\phi_e=100\text{W}$	120	$\phi_e=50\text{W}$	80	A
Peak Emission Wavelength	λ_p	$\phi_e=100\text{W}$	808	$\phi_e=50\text{W}$	808	nm
Spectral Radiation Half Bandwidth	$\Delta\lambda$	$\phi_e=100\text{W}$	4	$\phi_e=50\text{W}$	5	nm
Forward Voltage	V_F	$\phi_e=100\text{W}$	2.0	$\phi_e=50\text{W}$	1.9	V
Beam Spread Angle : Parallel	$\theta_{//}$	FWHM	10	FWHM	10	$^{\circ}$ (degree)
: Vertical	θ_{\perp}		35		35	$^{\circ}$ (degree)
Lasing Threshold Current	I_{th}		25		20	A
Array Length	-		10		10	mm
Maximum Number of Stacks	-		25		6	stack

*Contact sales staff for emitting wave-length and radiant output power (ϕ_e) other than above.

HIGH POWER QUASI-CW LASER DIODE L8411

Figure 1: Radiant Output Power vs. Forward Current
Low Duty Ratio Type (Typ.)




Figure 2: Radiant Output Power vs. Forward Current
High Duty Ratio Type (Typ.)




Figure 3: Typical Emission Spectrum




Figure 4: Relationship Between Total Optical Output Power and Duty Ratio






Figure 5: Dimensional Outline (Unit : mm)

Low Duty Ratio Type (Peltier-cooling)



High Duty Ratio Type (Water-cooling)



HAMAMATSU

<http://www.hamamatsu.com>

HAMAMATSU PHOTONICS K.K., International Sales Division

325-6, Sunayama-cho, Hamamatsu City, 430-8587, Japan, Telephone: (81)53-452-2141, Fax: (81)53-456-7889

U.S.A.: Hamamatsu Corporation, 360 Foothill Road, P.O. BOX 6910, Bridgewater, N.J. 08807-0910, U.S.A. Telephone: (1)908-231-0960, Fax: (1)908-231-1218 E-mail: usa@hamamatsu.com

Germany: Hamamatsu Photonics Deutschland GmbH, Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49)8152-375-0, Fax: (49)8152-2658, E-mail: info@hamamatsu.de

France: Hamamatsu Photonics France S.A.R.L.: 8, Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: 33(1) 69 53 71 00, Fax: 33(1) 69 53 71 10, E-mail: france@hamamatsu.com

United Kingdom: Hamamatsu Photonics UK Limited: 2 Howard Court, 10 Tewin Road, Welwyn Garden City, Hertfordshire AL7 1BW, United Kingdom, Telephone: (44)1707-294888, Fax: (44)1707-325777, E-mail: info@hamamatsu.co.uk

North Europe: Hamamatsu Photonics Norden AB: Smidesvägen 12, SE-171-41 Solna, Sweden, Telephone: (46)8-509-031-00, Fax: (46)8-509-031-01, E-mail: info@hamamatsu.se

Italy: Hamamatsu Photonics Italia S.R.L.: Strada della Moia, 1/E, 20020 Arese, (Milano), Italy, Telephone: (39)02-935 81 733, Fax: (39)02-935 81 741, E-mail: info@hamamatsu.it

Cat. No. LLD1008E01

OCT. 2000 SI

Printed in Japan (200)