



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089
<http://www.nteinc.com>

NTE1459 Integrated Circuit Low Noise, Equalizer Amp

Features:

- High Open Loop Gain, Low Distortion
- High S/N Because of High Gain at 1st Stage
- Excellent Characteristics for Supply Voltage and Temperature

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Supply Voltage, V_{CC} 15V
 Power Dissipation ($T_A \leq 80^\circ\text{C}$), P_D 100mW
 Operating Temperature Range, T_{opr} -20° to $+80^\circ\text{C}$
 Storage Temperature Range, T_{stg} -40° to $+125^\circ\text{C}$

Recommended Operating Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Supply Voltage, V_{CC} 9V
 Load Resistance, R_L 10k Ω

Electrical Characteristics: ($T_A = +25^\circ\text{C}$, $V_{CC} = 9\text{V}$, $R_L = 10\text{k}\Omega$, $f = 1\text{kHz}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Dissipation Current	I_{CC}		-	1.2	2.3	mA
Voltage Gain	V_G	Open Loop	75	79	-	dB
		Closed Loop	43	45	47	dB
Output Voltage	V_O	THD = 1.0%	1.0	1.5	-	V
Total Harmonic Distortion	THD	$V_O = 0.5\text{V}$	-	0.1	-	%
Input Resistance	r_i		-	120	-	k Ω
Noise Voltage Converted to Input	V_{NI}	$R_g = 2.2\text{k}\Omega$, NAB	-	1	2	μV

Pin Connection Diagram

