



## NTE7024 Integrated Circuit Module, 2 Output Positive Voltage Regulator for VCR

### Features:

- 2 Outputs
- Output Voltage Select Function

### Absolute Maximum Ratings: ( $T_A = +25^\circ\text{C}$ unless otherwise specified)

Maximum DC Input Voltage, $V_{IN}$ (DC) Max .....	30V
Maximum Average Output Current, $I_O$ Max .....	
$V_{O1}$ .....	1.0A
$V_{O2}$ .....	2.0A
Operating Case Temperature, $T_C$ Max .....	+105°C
Junction Temperature, $T_J$ Max .....	+150°C
Storage Temperature Range, $T_{stg}$ .....	-30° to +105°C
Thermal Resistance, Junction-to-Case, $R_{thJC}$ .....	4.5°C/W

### Electrical Characteristics: ( $T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Test Conditions	Min	Typ	Max	Unit
Output Voltage Setting $V_{O1}$ $V_{O2}$	$V_{IN}$ (DC) = $V_B$ = 18V, $I_{O1}$ = 0.2A, $I_{O2}$ = 0.4A	9.7	9.8	9.9	V
Output Cutoff Residual Voltage		11.6	11.7	11.8	
Ripple Compression Ratio		—	—	0.1	V
Temperature Coefficient		—	—	0.3	%
Load Regulation	—	—	0.02	%/°C	
Input Regulation	Condition 1	—	—	35	mV/A
	Condition 2	—	—	35	mV/V
Minimum Input-Output Voltage Difference	$V_B$ = 18V, $I_{O1}$ = 1A	1.5	—	—	V

### Test Conditions:

Condition 1:  $V_{IN}$  (DC) =  $V_B$  = 15V to 22V,  $I_{O1}$  = 0.2A,  $I_{O2}$  = 0.4A

Condition 2:  $V_{IN}$  (DC) =  $V_B$  = 18V,  $I_{O1}$  = 0 to 1A,  $I_{O2}$  = 0 to 1A

**Pin Connection Diagram**  
(Front View)

8	GND
7	V <sub>IN</sub> (DC)
6	V <sub>B</sub>
5	V <sub>O</sub> 2 (11.7V @ 2A)
4	V <sub>O</sub> 2 (11.7V @ 2A)
3	V <sub>B</sub>
2	V <sub>O</sub> 1 (9.8V @ 1A)
1	GND

