

PBSS301ND

20 V, 4 A NPN low V_{CEsat} (BISS) transistor

Rev. 02 — 25 April 2005

Product data sheet

1. Product profile

1.1 General description

NPN low V_{CEsat} Breakthrough in Small Signal (BISS) transistor in a SOT457 (SC-74) SMD plastic package.

PNP complement: PBSS301PD.

1.2 Features

- Very low collector-emitter saturation resistance
- Ultra low collector-emitter saturation voltage
- 4 A continuous collector current
- Up to 15 A peak current
- High efficiency due to less heat generation

1.3 Applications

- Power management functions
- Charging circuits
- DC-to-DC conversion
- MOSFET gate driving
- Power switches (e.g. motors, fans)
- Thin Film Transistor (TFT) backlight inverter

1.4 Quick reference data

Table 1: Quick reference data

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
V_{CEO}	collector-emitter voltage	open base	-	-	20	V
I_C	collector current (DC)		[1]	-	-	A
I_{CM}	peak collector current	single pulse; $t_p \leq 1 \text{ ms}$	-	-	15	A
R_{CEsat}	collector-emitter saturation resistance	$I_C = 4 \text{ A};$ $I_B = 400 \text{ mA}$	[2]	-	50	$\text{m}\Omega$

[1] Device mounted on a ceramic Printed-Circuit Board (PCB), Al_2O_3 , standard footprint.


[2] Pulse test: $t_p \leq 300 \mu\text{s}$; $\delta \leq 0.02$.

PHILIPS

2. Pinning information

Table 2: Pinning

Pin	Description	Simplified outline	Symbol
1	collector		
2	collector		
3	base		
4	emitter		
5	collector		
6	collector		



3. Ordering information

Table 3: Ordering information

Type number	Package			Version
	Name	Description		
PBSS301ND	SC-74	plastic surface mounted package; 6 leads		SOT457

4. Marking

Table 4: Marking codes

Type number	Marking code
PBSS301ND	C6

5. Limiting values

Table 5: Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions	Min	Max	Unit
V_{CBO}	collector-base voltage	open emitter	-	20	V
V_{CEO}	collector-emitter voltage	open base	-	20	V
V_{EBO}	emitter-base voltage	open collector	-	5	V
I_C	collector current (DC)		[1]	-	A
I_{CM}	peak collector current	single pulse; $t_p \leq 1 \text{ ms}$	-	15	A
I_B	base current (DC)		-	0.8	A
I_{BM}	peak base current	single pulse; $t_p \leq 1 \text{ ms}$	-	2	A
P_{tot}	total power dissipation	$T_{amb} \leq 25^\circ\text{C}$	[2]	-	mW
			[3]	-	600 mW
			[4]	-	750 mW
			[1]	-	1.1 W
			[2][5]	-	2.5 W


Table 5: Limiting values ...continued

In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions	Min	Max	Unit
T_j	junction temperature		-	150	°C
T_{amb}	ambient temperature		-65	+150	°C
T_{stg}	storage temperature		-65	+150	°C

[1] Device mounted on a ceramic PCB, Al_2O_3 , standard footprint.

[2] Device mounted on an FR4 PCB, single-sided copper, tin-plated and standard footprint.

[3] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for collector 1 cm^2 .[4] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for collector 6 cm^2 .[5] Operated under pulsed conditions: Duty cycle $\delta \leq 10\%$ and pulse width $t_p \leq 10\text{ ms}$.(1) Ceramic PCB, Al_2O_3 , standard footprint(2) FR4 PCB; mounting pad for collector 6 cm^2 (3) FR4 PCB; mounting pad for collector 1 cm^2

(4) FR4 PCB; standard footprint

Fig 1. Power derating curves

6. Thermal characteristics

Table 6: Thermal characteristics

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
$R_{th(j-a)}$	thermal resistance from junction to ambient	in free air	[2]	-	350	K/W
			[3]	-	208	K/W
			[4]	-	160	K/W
			[1]	-	113	K/W
			[2][5]	-	50	K/W
$R_{th(j-sp)}$	thermal resistance from junction to solder point		-	-	45	K/W


[1] Device mounted on a ceramic PCB, Al_2O_3 , standard footprint.

[2] Device mounted on an FR4 PCB, single-sided copper, tin-plated and standard footprint.

[3] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for collector 1 cm^2 .

[4] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for collector 6 cm^2 .


[5] Operated under pulsed conditions: Duty cycle $\delta \leq 10\%$ and pulse width $t_p \leq 10\text{ ms}$.



FR4 PCB; standard footprint

- (1) $\delta = 1$
- (2) $\delta = 0.75$
- (3) $\delta = 0.5$
- (4) $\delta = 0.33$
- (5) $\delta = 0.2$
- (6) $\delta = 0.1$
- (7) $\delta = 0.05$
- (8) $\delta = 0.02$
- (9) $\delta = 0.01$
- (10) $\delta = 0$


Fig 2. Transient thermal impedance from junction to ambient as a function of pulse time; typical values



FR4 PCB; mounting pad for collector 1 cm²

- (1) $\delta = 1$
- (2) $\delta = 0.75$
- (3) $\delta = 0.5$
- (4) $\delta = 0.33$
- (5) $\delta = 0.2$
- (6) $\delta = 0.1$
- (7) $\delta = 0.05$
- (8) $\delta = 0.02$
- (9) $\delta = 0.01$
- (10) $\delta = 0$

Fig 3. Transient thermal impedance from junction to ambient as a function of pulse time; typical values



FR4 PCB; mounting pad for collector 6 cm²

- (1) $\delta = 1$
- (2) $\delta = 0.75$
- (3) $\delta = 0.5$
- (4) $\delta = 0.33$
- (5) $\delta = 0.2$
- (6) $\delta = 0.1$
- (7) $\delta = 0.05$
- (8) $\delta = 0.02$
- (9) $\delta = 0.01$
- (10) $\delta = 0$

Fig 4. Transient thermal impedance from junction to ambient as a function of pulse time; typical values

7. Characteristics

Table 7: Characteristics $T_{amb} = 25^\circ C$ unless otherwise specified.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
I_{CBO}	collector-base cut-off current	$V_{CB} = 20 \text{ V}; I_E = 0 \text{ A}$	-	-	0.1	μA
		$V_{CB} = 20 \text{ V}; I_E = 0 \text{ A}; T_j = 150^\circ \text{C}$	-	-	50	μA
I_{CES}	collector-emitter cut-off current	$V_{CE} = 20 \text{ V}; V_{BE} = 0 \text{ V}$	-	-	0.1	μA
I_{EBO}	emitter-base cut-off current	$V_{EB} = 5 \text{ V}; I_C = 0 \text{ A}$	-	-	0.1	μA
h_{FE}	DC current gain	$V_{CE} = 2 \text{ V}; I_C = 0.5 \text{ A}$	300	450	-	
		$V_{CE} = 2 \text{ V}; I_C = 1 \text{ A}$	[1] 300	430	-	
		$V_{CE} = 2 \text{ V}; I_C = 2 \text{ A}$	[1] 250	400	-	
		$V_{CE} = 2 \text{ V}; I_C = 4 \text{ A}$	[1] 200	310	-	
		$V_{CE} = 2 \text{ V}; I_C = 6 \text{ A}$	[1] 100	230	-	
V_{CEsat}	collector-emitter saturation voltage	$I_C = 0.5 \text{ A}; I_B = 50 \text{ mA}$	-	30	50	mV
		$I_C = 1 \text{ A}; I_B = 50 \text{ mA}$	-	60	90	mV
		$I_C = 2 \text{ A}; I_B = 200 \text{ mA}$	-	110	150	mV
		$I_C = 4 \text{ A}; I_B = 400 \text{ mA}$	[1] -	200	280	mV
		$I_C = 6 \text{ A}; I_B = 600 \text{ mA}$	[1] -	300	420	mV
R_{CEsat}	collector-emitter saturation resistance	$I_C = 4 \text{ A}; I_B = 400 \text{ mA}$	[1] -	50	70	$\text{m}\Omega$
V_{BEsat}	base-emitter saturation voltage	$I_C = 0.5 \text{ A}; I_B = 50 \text{ mA}$	-	0.79	0.85	V
		$I_C = 1 \text{ A}; I_B = 50 \text{ mA}$	-	0.81	0.9	V
		$I_C = 1 \text{ A}; I_B = 100 \text{ mA}$	[1] -	0.83	1	V
		$I_C = 4 \text{ A}; I_B = 400 \text{ mA}$	[1] -	1.0	1.1	V
V_{BEon}	base-emitter turn-on voltage	$V_{CE} = 2 \text{ V}; I_C = 2 \text{ A}$	-	0.79	1	V
t_d	delay time	$V_{CC} = 12.5 \text{ V}; I_C = 3 \text{ A}; I_{Bon} = 0.15 \text{ A}; I_{Boff} = -0.15 \text{ A}$	-	12	-	ns
t_r	rise time		-	36	-	ns
t_{on}	turn-on time		-	48	-	ns
t_s	storage time		-	230	-	ns
t_f	fall time		-	50	-	ns
t_{off}	turn-off time		-	280	-	ns
f_T	transition frequency	$V_{CE} = 10 \text{ V}; I_C = 0.1 \text{ A}; f = 100 \text{ MHz}$	-	100	-	MHz
C_c	collector capacitance	$V_{CB} = 10 \text{ V}; I_E = i_e = 0 \text{ A}; f = 1 \text{ MHz}$	-	60	-	pF

[1] Pulse test: $t_p \leq 300 \mu\text{s}; \delta \leq 0.02$.




Fig 5. DC current gain as a function of collector current; typical values




Fig 6. Base-emitter voltage as a function of collector current; typical values




Fig 7. Collector-emitter saturation voltage as a function of collector current; typical values






Fig 8. Collector-emitter saturation voltage as a function of collector current; typical values




- $I_C/I_B = 20$
- (1) $T_{amb} = -55^\circ\text{C}$
 - (2) $T_{amb} = 25^\circ\text{C}$
 - (3) $T_{amb} = 100^\circ\text{C}$

Fig 9. Base-emitter saturation voltage as a function of collector current; typical values



- $T_{amb} = 25^\circ\text{C}$
- (1) $I_C/I_B = 100$
 - (2) $I_C/I_B = 50$
 - (3) $I_C/I_B = 10$


Fig 10. Collector-emitter saturation resistance as a function of collector current; typical values



$T_{amb} = 25^\circ\text{C}$

- (1) $I_B = 80 \text{ mA}$
- (2) $I_B = 72 \text{ mA}$
- (3) $I_B = 64 \text{ mA}$
- (4) $I_B = 56 \text{ mA}$
- (5) $I_B = 48 \text{ mA}$
- (6) $I_B = 40 \text{ mA}$
- (7) $I_B = 32 \text{ mA}$
- (8) $I_B = 24 \text{ mA}$
- (9) $I_B = 16 \text{ mA}$
- (10) $I_B = 8 \text{ mA}$

Fig 11. Collector current as a function of collector-emitter voltage; typical values



$I_C/I_B = 20$

- (1) $T_{amb} = 100^\circ\text{C}$
- (2) $T_{amb} = 25^\circ\text{C}$
- (3) $T_{amb} = -55^\circ\text{C}$

Fig 12. Collector-emitter saturation resistance as a function of collector current; typical values

8. Test information





Fig 13. BISS transistor switching time definition



$V_{CC} = 12.5 \text{ V}$; $I_C = 3 \text{ A}$; $I_{B(on)} = 0.15 \text{ A}$; $I_{B(off)} = -0.15 \text{ A}$

Fig 14. Test circuit for switching times

9. Package outline

Plastic surface mounted package; 6 leads

SOT457




Fig 15. Package outline SOT457 (SC-74)



10. Packing information

Table 8: Packing methods

The indicated -xxx are the last three digits of the 12NC ordering code. [1]

Type number	Package	Description	Packing quantity	
				3000
PBSS301ND	SOT457	4 mm pitch, 8 mm tape and reel; T1	[2] -115	
		4 mm pitch, 8 mm tape and reel; T2	[3] -125	-165

[1] For further information and the availability of packing methods, see [Section 16](#).

[2] T1: normal taping

[3] T2: reverse taping



11. Revision history

Table 9: Revision history

Document ID	Release date	Data sheet status	Change notice	Doc. number	Supersedes
PBSS301ND_2	20050425	Product data sheet	-	9397 750 14958	PBSS301ND_1
Modifications:			<ul style="list-style-type: none">• Section 1.3: acronym TFT explained• Figure 2, 3 and 4: Z_{th} renamed to $Z_{th(j-a)}$• Figure 11: figure notes amended• Section 15: added		
PBSS301ND_1	20050405	Product data sheet	-	9397 750 14487	-

12. Data sheet status

Level	Data sheet status [1]	Product status [2][3]	Definition
I	Objective data	Development	This data sheet contains data from the objective specification for product development. Philips Semiconductors reserves the right to change the specification in any manner without notice.
II	Preliminary data	Qualification	This data sheet contains data from the preliminary specification. Supplementary data will be published at a later date. Philips Semiconductors reserves the right to change the specification without notice, in order to improve the design and supply the best possible product.
III	Product data	Production	This data sheet contains data from the product specification. Philips Semiconductors reserves the right to make changes at any time in order to improve the design, manufacturing and supply. Relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN).

[1] Please consult the most recently issued data sheet before initiating or completing a design.

[2] The product status of the device(s) described in this data sheet may have changed since this data sheet was published. The latest information is available on the Internet at URL <http://www.semiconductors.philips.com>.

[3] For data sheets describing multiple type numbers, the highest-level product status determines the data sheet status.

13. Definitions

Short-form specification — The data in a short-form specification is extracted from a full data sheet with the same type number and title. For detailed information see the relevant data sheet or data handbook.

Limiting values definition — Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 60134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.

Application information — Applications that are described herein for any of these products are for illustrative purposes only. Philips Semiconductors make no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips Semiconductors for any damages resulting from such application.

Right to make changes — Philips Semiconductors reserves the right to make changes in the products - including circuits, standard cells, and/or software - described or contained herein in order to improve design and/or performance. When the product is in full production (status 'Production'), relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN). Philips Semiconductors assumes no responsibility or liability for the use of any of these products, conveys no license or title under any patent, copyright, or mask work right to these products, and makes no representations or warranties that these products are free from patent, copyright, or mask work right infringement, unless otherwise specified.

15. Trademarks

Notice — All referenced brands, product names, service names and trademarks are the property of their respective owners.

14. Disclaimers

Life support — These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips Semiconductors

16. Contact information

For additional information, please visit: <http://www.semiconductors.philips.com>

For sales office addresses, send an email to: sales.addresses@www.semiconductors.philips.com



17. Contents

1	Product profile	1
1.1	General description.....	1
1.2	Features	1
1.3	Applications	1
1.4	Quick reference data.....	1
2	Pinning information.....	2
3	Ordering information.....	2
4	Marking	2
5	Limiting values.....	2
6	Thermal characteristics.....	4
7	Characteristics.....	7
8	Test information.....	11
9	Package outline	12
10	Packing information.....	13
11	Revision history.....	14
12	Data sheet status	15
13	Definitions	15
14	Disclaimers.....	15
15	Trademarks.....	15
16	Contact information	15

© Koninklijke Philips Electronics N.V. 2005

All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Date of release: 25 April 2005
Document number: 9397 750 14958



Published in The Netherlands