



# SPN3446 N-Channel Enhancement Mode MOSFET

## DESCRIPTION

The SPN3446 is the N-Channel logic enhancement mode power field effect transistors are produced using high cell density , DMOS trench technology.

This high density process is especially tailored to minimize on-state resistance.

These devices are particularly suited for low voltage application such as cellular phone and notebook computer power management and other battery powered circuits, and low in-line power loss are needed in a very small outline surface mount package.



## APPLICATIONS

- Power Management in Note book
- Portable Equipment
- Battery Powered System
- DC/DC Converter
- Load Switch
- DSC
- LCD Display inverter


## FEATURES

- ◆ 20V/5.3A,R<sub>DS(ON)</sub>=48mΩ@V<sub>GS</sub>=4.5V
- ◆ 20V/3.4A,R<sub>DS(ON)</sub>=65mΩ@V<sub>GS</sub>=2.5V
- ◆ 20V/2.8A,R<sub>DS(ON)</sub>=90mΩ@V<sub>GS</sub>=1.8V
- ◆ Super high density cell design for extremely low R<sub>DS (ON)</sub>
- ◆ Exceptional on-resistance and maximum DC current capability
- ◆ TSOP-6P package design

## PIN CONFIGURATION( TSOP- 6P )



## PART MARKING



Y : Year Code  
W : Week Code



# SPN3446

## N-Channel Enhancement Mode MOSFET

### PIN DESCRIPTION

| Pin | Symbol | Description |
|-----|--------|-------------|
| 1   | D      | Drain       |
| 2   | D      | Drain       |
| 3   | G      | Gate        |
| 4   | S      | Source      |
| 5   | D      | Drain       |
| 6   | D      | Drain       |

### ORDERING INFORMATION

| Part Number  | Package | Part Marking |
|--------------|---------|--------------|
| SPN3446ST6RG | TSOP-6P | 46YW         |

※ Week Code : A ~ Z( 1 ~ 26 ) ; a ~ z( 27 ~ 52 )

※ SPN3446ST6RG : Tape Reel ; Pb – Free

### ABSOULTE MAXIMUM RATINGS

(TA=25°C Unless otherwise noted)

| Parameter                                       | Symbol               | Typical        | Unit |
|---|----------------------|----------------|------|
| Drain-Source Voltage                            | V <sub>DSS</sub>     | 20             | V    |
| Gate –Source Voltage                            | V <sub>GSS</sub>     | ±12            | V    |
| Continuous Drain Current(T <sub>J</sub> =150°C) | T <sub>A</sub> =25°C | ID             | A    |
|   | T <sub>A</sub> =70°C |                |      |
| Pulsed Drain Current                            | I <sub>DM</sub>      | 25             | A    |
| Continuous Source Current(Diode Conduction)     | I <sub>S</sub>       | 1.7            | A    |
| Power Dissipation                               | T <sub>A</sub> =25°C | P <sub>D</sub> | W    |
|   | T <sub>A</sub> =70°C |                |      |
| Operating Junction Temperature                  | T <sub>J</sub>       | 150            | °C   |
| Storage Temperature Range                       | T <sub>STG</sub>     | -55/150        | °C   |
| Thermal Resistance-Junction to Ambient          | R <sub>θJA</sub>     | 90             | °C/W |



# SPN3446

## N-Channel Enhancement Mode MOSFET

### ELECTRICAL CHARACTERISTICS

(TA=25°C Unless otherwise noted)





| Parameter                       | Symbol   | Conditions                                   | Min. | Typ   | Max.  | Unit |
|---------------------------------|----------|--|------|-------|-------|------|
| <b>Static</b>                   |          |  |      |       |       |      |
| Drain-Source Breakdown Voltage  | V(BR)DSS | VGS=0V, ID=250uA                             | 20   |       |       | V    |
| Gate Threshold Voltage          | VGS(th)  | VDS=VGS, ID=250uA                            | 0.4  |       | 1.0   |      |
| Gate Leakage Current            | IGSS     | VDS=0V, VGS=±12V                             |      |       | ±100  | nA   |
| Zero Gate Voltage Drain Current | IDSS     | VDS=20V, VGS=0V                              |      |       | 1     | uA   |
|                                 |          | VDS=20V, VGS=0V<br>TJ=55°C                   |      |       | 5     |      |
| On-State Drain Current          | ID(on)   | VDS≤5V, VGS=4.5V                             | 6    |       |       | A    |
| Drain-Source On-Resistance      | RDS(on)  | VGS=4.5V, ID=5.3A                            |      | 0.038 | 0.048 | Ω    |
|                                 |          | VGS=2.5V, ID=3.4A                            |      | 0.050 | 0.065 |      |
|                                 |          | VGS=1.8V, ID=2.8A                            |      | 0.075 | 0.090 |      |
| Forward Transconductance        | gfs      | VDS=5V, ID=-3.6A                             |      | 10    |       | S    |
| Diode Forward Voltage           | VSD      | Is=1.6A, VGS=0V                              |      | 0.8   | 1.2   | V    |
| <b>Dynamic</b>                  |          |  |      |       |       |      |
| Total Gate Charge               | Qg       | VDS=6V, VGS=4.5V<br>ID=2.8A                  |      | 4.8   | 8     | nC   |
| Gate-Source Charge              | Qgs      |  |      | 1.0   |       |      |
| Gate-Drain Charge               | Qgd      |  |      | 1.0   |       |      |
| Input Capacitance               | Ciss     | VDS=6V, VGS=0V<br>f=1MHz                     |      | 485   |       | pF   |
| Output Capacitance              | Coss     |  |      | 85    |       |      |
| Reverse Transfer Capacitance    | Crss     |  |      | 40    |       |      |
| Turn-On Time                    | td(on)   | VDD=6V, RL=6Ω<br>ID=1.0A, VGEN=4.5V<br>RG=6Ω |      | 8     | 14    | ns   |
|                                 | tr       |  |      | 12    | 18    |      |
| Turn-Off Time                   | td(off)  |  |      | 30    | 35    |      |
|                                 | tf       |  |      | 12    | 16    |      |



# SPN3446

## N-Channel Enhancement Mode MOSFET

### TYPICAL CHARACTERISTICS









# SPN3446

## N-Channel Enhancement Mode MOSFET

### TYPICAL CHARACTERISTICS








# SPN3446

## N-Channel Enhancement Mode MOSFET

### TYPICAL CHARACTERISTICS







# SPN3446

## N-Channel Enhancement Mode MOSFET

### TSOP- 6P PACKAGE OUTLINE



| Dim            | MILLIMETERS |      |      | INCHES     |       |       |
|----------------|-------------|------|------|------------|-------|-------|
|                | Min         | Nom  | Max  | Min        | Nom   | Max   |
| A              | 0.91        | -    | 1.10 | 0.036      | -     | 0.043 |
| A <sub>1</sub> | 0.01        | -    | 0.10 | 0.0004     | -     | 0.004 |
| A <sub>2</sub> | 0.90        | -    | 1.00 | 0.035      | 0.038 | 0.039 |
| b              | 0.30        | 0.32 | 0.45 | 0.012      | 0.013 | 0.018 |
| c              | 0.10        | 0.15 | 0.20 | 0.004      | 0.006 | 0.008 |
| D              | 2.95        | 3.05 | 3.10 | 0.116      | 0.120 | 0.122 |
| E              | 2.70        | 2.85 | 2.98 | 0.106      | 0.112 | 0.117 |
| E <sub>1</sub> | 1.55        | 1.65 | 1.70 | 0.061      | 0.065 | 0.067 |
| e              | 1.00 BSC    |      |      | 0.0394 BSC |       |       |
| e <sub>1</sub> | 1.90        | 2.00 | 2.10 | 0.075      | 0.080 | 0.085 |
| L              | 0.35        | -    | 0.50 | 0.014      | -     | 0.020 |
| L <sub>1</sub> | 0.60 Ref    |      |      | 0.024 Ref  |       |       |
| L <sub>2</sub> | 0.25 BSC    |      |      | 0.010 BSC  |       |       |
| R              | 0.10        | -    | -    | 0.004      | -     | -     |
| θ              | 0°          | 4°   | 8°   | 0°         | 4°    | 8°    |
| θ <sub>1</sub> | 7° Nom      |      |      | 7° Nom     |       |       |



# SPN3446

## N-Channel Enhancement Mode MOSFET

---

Information provided is alleged to be exact and consistent. SYNC Power Corporation presumes no responsibility for the penalties of use of such information or for any violation of patents or other rights of third parties which may result from its use. No license is granted by allegation or otherwise under any patent or patent rights of SYNC Power Corporation. Conditions mentioned in this publication are subject to change without notice. This publication surpasses and replaces all information previously supplied. SYNC Power Corporation products are not authorized for use as critical components in life support devices or systems without express written approval of SYNC Power Corporation.

©The SYNC Power logo is a registered trademark of SYNC Power Corporation

©2004 SYNC Power Corporation – Printed in Taiwan – All Rights Reserved

SYNC Power Corporation

9F-5, No.3-2, Park Street

NanKang District (NKSP), Taipei, Taiwan, 115, R.O.C

Phone: 886-2-2655-8178

Fax: 886-2-2655-8468

©<http://www.syncpower.com>