



TS79L00 series

3-Terminal Low Current Negative Voltage Regulator

TO-92



SOT-89



SOP-8



Voltage Range - 5V to - 24V
Output Current up to 100mA

General Description

The TS79L00 Series of negative voltage regulators are inexpensive, easy-to-use devices suitable for a multitude of applications that require a regulated supply of up to 100mA. Like their higher power TS7900 and TS79M00 Series cousins, these regulators feature internal current limiting and thermal shutdown making them remarkably rugged. No external components are required with the TS79L00 devices in many applications.


These devices offer a substantial performance advantage over the traditional zener diode-resistor combination, as output impedance and quiescent current are substantially reduced.

This series is offered in 3-pin TO-92, SOT-89 and 8-pin SOP-8 package.

Features

- ◊ Output current up to 100mA
- ◊ No external components required
- ◊ Internal thermal overload protection
- ◊ Internal short-circuit current limiting
- ◊ Output transistor safe-area compensation
- ◊ Output voltage offered in 4% tolerance

Standard Application



Ordering Information

Part No.	Operating Temp. (Ambient)	Package
TS79LxxCT		TO-92
TS79LxxCY	-20 ~ +85 °C	SOT-89
TS79LxxCS		SOP-8

Note: Where xx denotes voltage option.

A common ground is required between the input and the output voltages. The input voltage must remain typically 2.0V above the output voltage even during the low point on the Input ripple voltage.

XX = these two digits of the type number indicate voltage.

* = Cin is required if regulator is located an appreciable distance from power supply filter.

** = Co is not needed for stability; however, it does improve transient response.

Pin Assignment

Pin No.			Pin Description
TS79L00CT	TS79L00CY	TS79L00CS	
3	3	1	Output
2	2	2, 3, 6, 7	Input
1	1	5	Ground
		4, 8	Non connected

Absolute Maximum Rating

Input Voltage		Vin *	- 35	V
Input Voltage		Vin **	- 40	V
Power Dissipation	TO-92	Pd	0.625	W
	TO-89		0.5	
	SOP-8		0.5	
Operating Junction Temperature Range		T _J	0 ~ +125	°C
Storage Temperature Range		T _{STG}	-65 ~ +150	°C
Note : * TS79L05 to TS79L18 ** TS79L24				

TS79L05 Electrical Characteristics

(Vin= -10V, Iout=40mA, 0 °C≤Tj≤125 °C, Cin=0.33uF, Cout=0.1uF; unless otherwise specified.)

Parameter	Symbol	Test Conditions		Min	Typ	Max	Unit
Output voltage	Vout	Tj=25 °C		- 4.80	- 5	- 5.20	V
		-7.5V≤Vin≤ -20V, 5mA≤Iout≤100mA		- 4.75	- 5	- 5.25	
Line Regulation	REGline	Tj=25 °C	-7.5V≤Vin≤ -20V, Io=40mA	--	50	150	mV
Load Regulation	REGload	Tj=25 °C	5mA≤Iout≤100mA	--	20	60	
			5mA≤Iout≤40mA	--	10	30	
Quiescent Current	Iq	Iout=0, Tj=25 °C		--	3	6	mA
Quiescent Current Change	ΔIq	-8V≤Vin≤ -20V		--	--	1.5	
		1mA≤Iout≤40mA		--	--	0.1	
Output Noise Voltage	Vn	10Hz≤f≤100KHz, Tj=25 °C		--	40	--	uV
Ripple Rejection Ratio	RR	f=120Hz, -8V≤Vin≤ -18V		41	49	--	dB
Voltage Drop	Vdrop	Tj=25 °C		--	1.7	--	V
Peak Output Current	I _o peak	Tj=25 °C		--	0.15	--	A

- Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible, and thermal effects must be taken into account separately.
- This specification applies only for DC power dissipation permitted by absolute maximum ratings.

TS79L06 Electrical Characteristics

($V_{in} = -11V$, $I_{out} = 40mA$, $0^{\circ}C \leq T_j \leq 125^{\circ}C$, $C_{in} = 0.33\mu F$, $C_{out} = 0.1\mu F$; unless otherwise specified.)

Parameter		Test Conditions		Min	Typ	Max	Unit
Output voltage	V_{out}	$T_j = 25^{\circ}C$		- 5.76	- 6	- 6.24	V
		$-8.5V \leq V_{in} \leq -21V$, $5mA \leq I_{out} \leq 100mA$		- 5.70	- 6	- 6.30	
Line Regulation	REG_{line}	$T_j = 25^{\circ}C$	$-8.5V \leq V_{in} \leq -21V$, $I_o = 40mA$	--	50	150	mV
Load Regulation	REG_{load}	$T_j = 25^{\circ}C$	$5mA \leq I_{out} \leq 100mA$	--	20	60	
			$5mA \leq I_{out} \leq 40mA$	--	10	30	
Quiescent Current	I_q	$I_{out} = 0$, $T_j = 25^{\circ}C$		--	3	6	mA
Quiescent Current Change	ΔI_q	$-9V \leq V_{in} \leq -21V$		--	--	1.5	
		$1mA \leq I_{out} \leq 40mA$		--	--	0.1	
Output Noise Voltage	V_n	$10Hz \leq f \leq 100KHz$, $T_j = 25^{\circ}C$		--	40	--	uV
Ripple Rejection Ratio	RR	$f = 120Hz$, $-9V \leq V_{in} \leq -19V$		41	49	--	dB
Voltage Drop	V_{drop}	$T_j = 25^{\circ}C$		--	1.7	--	V
Peak Output Current	$I_o \text{ peak}$	$T_j = 25^{\circ}C$		--	0.15	--	A

TS79L08 Electrical Characteristics

($V_{in} = -14V$, $I_{out} = 40mA$, $0^{\circ}C \leq T_j \leq 125^{\circ}C$, $C_{in} = 0.33\mu F$, $C_{out} = 0.1\mu F$; unless otherwise specified.)

Parameter	Symbol	Test Conditions		Min	Typ	Max	Unit
Output Voltage	V_{out}	$T_j = 25^{\circ}C$		- 7.69	- 8	- 8.32	V
		$-10.5V \leq V_{in} \leq -23V$, $5mA \leq I_{out} \leq 100mA$		- 7.61	- 8	- 8.40	
Line Regulation	REG_{line}	$T_j = 25^{\circ}C$	$-10.5V \leq V_{in} \leq -23V$, $I_o = 40mA$	--	80	160	mV
Load Regulation	REG_{load}	$T_j = 25^{\circ}C$	$5mA \leq I_{out} \leq 100mA$	--	25	80	
			$5mA \leq I_{out} \leq 40mA$	--	10	40	
Quiescent Current	I_q	$I_{out} = 0$, $T_j = 25^{\circ}C$		--	3	6	mA
Quiescent Current Change	ΔI_q	$-11V \leq V_{in} \leq -23V$		--	--	1.5	
		$1mA \leq I_{out} \leq 40mA$		--	--	0.1	
Output Noise Voltage	V_n	$10Hz \leq f \leq 100KHz$, $T_j = 25^{\circ}C$		--	60	--	uV
Ripple Rejection Ratio	RR	$f = 120Hz$, $-13V \leq V_{in} \leq -23V$		37	57	--	dB
Voltage Drop	V_{drop}	$T_j = 25^{\circ}C$		--	1.7	--	V
Peak Output Current	$I_o \text{ peak}$	$T_j = 25^{\circ}C$		--	0.15	--	A

- Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible, and thermal effects must be taken into account separately.
- This specification applies only for DC power dissipation permitted by absolute maximum ratings.

TS79L09 Electrical Characteristics

(Vin= -15V, Iout=40mA, 0 °C≤Tj≤125 °C, Cin=0.33uF, Cout=0.1uF; unless otherwise specified.)

Parameter	Symbol	Test Conditions		Min	Typ	Max	Unit
Output Voltage	Vout	Tj=25 °C		- 8.65	- 9	- 9.36	V
		-11.5V≤Vin≤ -24V, 5mA≤Iout≤100mA		- 8.57	- 9	- 9.45	
Line Regulation	REGline	Tj=25 °C	-11.5V≤Vin≤ -24V, Io=40mA	--	90	180	mV
Load Regulation	REGload	Tj=25 °C	5mA≤Iout≤100mA	--	30	90	
			5mA≤Iout≤40mA	--	15	45	
Quiescent Current	Iq	Iout=0, Tj=25 °C		--	3	6	mA
Quiescent Current Change	ΔIq	-12V≤Vin≤ -24V		--	--	1.5	
		5mA≤Iout≤40mA		--	--	0.1	
Output Noise Voltage	Vn	10Hz≤f≤100KHz, Tj=25 °C		--	60	--	uV
Ripple Rejection Ratio	RR	f=120Hz, -14V≤Vin≤ -24V		37	57	--	dB
Voltage Drop	Vdrop	Tj=25 °C		--	1.7	--	V
Peak Output Current	Io peak	Tj=25 °C		--	0.15	--	A

TS79L12 Electrical Characteristics

(Vin= -19V, Iout=40mA, 0 °C≤Tj≤125 °C, Cin=0.33uF, Cout=0.1uF; unless otherwise specified.)

Parameter	Symbol	Test Conditions		Min	Typ	Max	Unit
Output Voltage	Vout	Tj=25 °C		- 11.53	- 12	- 12.48	V
		-14.5V≤Vin≤ -27V, 5mA≤Iout≤100mA		- 11.42	- 12	- 12.60	
Line Regulation	REGline	Tj=25 °C	-14.5V≤Vin≤ -27V, Io=40mA	--	120	240	mV
Load Regulation	REGload	Tj=25 °C	5mA≤Iout≤100mA	--	40	120	
			5mA≤Iout≤40mA	--	20	60	
Quiescent Current	Iq	Tj=25 °C, Iout=0		--	3	6.5	mA
Quiescent Current Change	ΔIq	-16V≤Vin≤ -27V		--	--	1.5	
		5mA≤Iout≤40mA		--	--	0.1	
Output Noise Voltage	Vn	10Hz≤f≤100KHz, Tj=25 °C		--	80	--	uV
Ripple Rejection Ratio	RR	f=120Hz, -15V≤Vin≤ -25V		37	42	--	dB
Voltage Drop	Vdrop	Tj=25 °C		--	1.7	--	V
Peak Output Current	Io peak	Tj=25 °C		--	0.15	--	A

- Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible, and thermal effects must be taken into account separately.
- This specification applies only for DC power dissipation permitted by absolute maximum ratings.

TS79L15 Electrical Characteristics

(Vin= -23V, Iout=40mA, 0 °C≤Tj≤125 °C, Cin=0.33uF, Cout=0.1uF; unless otherwise specified.)

Parameter	Symbol	Test Conditions		Min	Typ	Max	Unit
Output Voltage	Vout	Tj=25 °C		- 14.42	- 15	- 15.60	V
		-17.5V≤Vin≤ -30V, 5mA≤Iout≤100mA		- 14.28	- 15	- 15.75	
Line Regulation	REGline	Tj=25 °C	-17.5V≤Vin≤ -30V, Io=40mA	--	150	300	mV
Load Regulation	REGload	Tj=25 °C	5mA≤Iout≤100mA	--	50	150	
			5mA≤Iout≤40mA	--	25	75	
Quiescent Current	Iq	Tj=25 °C, Iout=0		--	3	6.5	mA
Quiescent Current Change	ΔIq	-20V≤Vin≤ -30V		--	--	1.5	
		5mA≤Iout≤40mA		--	--	0.1	
Output Noise Voltage	Vn	10Hz≤f≤100KHz, Tj=25 °C		--	90	--	uV
Ripple Rejection Ratio	RR	f=120Hz, -18V≤Vin≤ -28V		34	39	--	dB
Voltage Drop	Vdrop	Tj=25 °C		--	1.7	--	V
Peak Output Current	Io peak	Tj=25 °C		--	0.15	--	A

TS79L18 Electrical Characteristics

(Vin= -27V, Iout=40mA, 0 °C≤Tj≤125 °C, Cin=0.33uF, Cout=0.1uF; unless otherwise specified.)

Parameter	Symbol	Test Conditions		Min	Typ	Max	Unit
Output Voltage	Vout	Tj=25 °C		- 17.30	- 18	- 18.72	V
		-21V≤Vin≤ -33V, 5mA≤Iout≤100mA		- 17.14	- 18	- 18.90	
Line Regulation	REGline	Tj=25 °C	-21V≤Vin≤ -33V, Io=40mA	--	180	360	mV
Load Regulation	REGload	Tj=25 °C	5mA≤Iout≤100mA	--	60	180	
			5mA≤Iout≤40mA	--	30	90	
Quiescent Current	Iq	Tj=25 °C, Iout=0		--	3	6.5	mA
Quiescent Current Change	ΔIq	-21V≤Vin≤ -33V		--	--	1.5	
		5mA≤Iout≤40mA		--	--	0.1	
Output Noise Voltage	Vn	10Hz≤f≤100KHz, Tj=25 °C		--	150	--	uV
Ripple Rejection Ratio	RR	f=120Hz, -23V≤Vin≤ -33V		33	48	--	dB
Voltage Drop	Vdrop	Tj=25 °C		--	1.7	--	V
Peak Output Current	Io peak	Tj=25 °C		--	0.15	--	A

- Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible, and thermal effects must be taken into account separately.
- This specification applies only for DC power dissipation permitted by absolute maximum ratings.


TS79L24 Electrical Characteristics

($V_{in} = -33V$, $I_{out} = 40mA$, $0^{\circ}C \leq T_j \leq 125^{\circ}C$, $C_{in} = 0.33\mu F$, $C_{out} = 0.1\mu F$; unless otherwise specified.)

Parameter	Symbol	Test Conditions		Min	Typ	Max	Unit
Output Voltage	V_{out}	$T_j = 25^{\circ}C$		- 23.07	- 24	- 24.96	V
		$-27V \leq V_{in} \leq -38V$, $5mA \leq I_{out} \leq 100mA$		- 22.85	- 24	- 25.20	
Line Regulation	REG_{line}	$T_j = 25^{\circ}C$	$-27V \leq V_{in} \leq -38V$, $I_{o} = 40mA$	--	200	400	mV
Load Regulation	REG_{load}	$T_j = 25^{\circ}C$	$5mA \leq I_{out} \leq 100mA$	--	80	240	
			$5mA \leq I_{out} \leq 40mA$	--	40	120	
Quiescent Current	I_q	$I_{out} = 0$, $T_j = 25^{\circ}C$		--	4	7	mA
Quiescent Current Change	ΔI_q	$-28V \leq V_{in} \leq -38V$		--	--	1.5	
		$5mA \leq I_{out} \leq 40mA$		--	--	0.1	
Output Noise Voltage	V_n	$10Hz \leq f \leq 100KHz$, $T_j = 25^{\circ}C$		--	200	--	uV
Ripple Rejection Ratio	RR	$f = 120Hz$, $-29V \leq V_{in} \leq -35V$		31	45	--	dB
Voltage Drop	V_{drop}	$T_j = 25^{\circ}C$		--	1.7	--	V
Peak Output Current	$I_{o peak}$	$T_j = 25^{\circ}C$		--	0.15	--	A


- Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible, and thermal effects must be taken into account separately.
- This specification applies only for DC power dissipation permitted by absolute maximum ratings.

TO-92 Mechanical Drawing




TO-92 DIMENSION				
DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	4.30	4.70	0.169	0.185
B	4.30	4.70	0.169	0.185
C	14.30(typ)		0.563(typ)	
D	0.43	0.49	0.017	0.019
E	2.19	2.81	0.086	0.111
F	3.30	3.70	0.130	0.146
G	2.42	2.66	0.095	0.105
H	0.37	0.43	0.015	0.017

SOT-89 Mechanical Drawing



SOT-89 DIMENSION				
DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	4.40	4.60	0.173	0.181
B	1.50	1.7	0.059	0.070
C	2.30	2.60	0.090	0.102
D	0.40	0.52	0.016	0.020
E	1.50	1.50	0.059	0.059
F	3.00	3.00	0.118	0.118
G	0.89	1.20	0.035	0.047
H	4.05	4.25	0.159	0.167
I	1.4	1.6	0.055	0.068
J	0.35	0.44	0.014	0.017

SOP-8 Mechanical Drawing



SOP-8 DIMENSION				
DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	4.80	5.00	0.189	0.196
B	3.80	4.00	0.150	0.157
C	1.35	1.75	0.054	0.068
D	0.35	0.49	0.014	0.019
F	0.40	1.25	0.016	0.049
G	1.27 (typ)		0.05 (typ)	
K	0.10	0.25	0.004	0.009
M	0°	7°	0°	7°
P	5.80	6.20	0.229	0.244
R	0.25	0.50	0.010	0.019