

VSX40MD23

40 Watt Dual Output Quarter Brick DC/DC Converter



- 2.5V & 3.3V Dual Output
- 2.3" x 1.5" x 0.5"
- 89% Efficiency
- Low Output Noise
- Input Filtering
- Remote On/Off, Input Side
- Output Voltage Trim, +/-10%
- Fixed Frequency Operation
- -40C° to +100C° Baseplate Temp.
- Output Current Limit, Self-Start
- 1,500 Vdc Isolation, Input to Output
- UL/CUL 1950, EN60 950
- 36 to 75 Vdc Input Models
- Continuous Short Circuit Protection
- Non-latching Protection: Input Undervoltage, Input Overvoltage, Output Overvoltage, Overtemperature
- Output Voltage Tracking at Turn-on and Turn-off
- No Minimum Load Current

APPLICATIONS

- Distributed Power Architectures
- Workstations
- EDP Equipment
- Telecommunications

OPTIONS

- Choice of Remote On/Off logic Configuration
- Heatsink Available for Extended Operation

ADDITIONAL INFORMATION

- See Application Note DCAN-41 at www.cdpowerelectronics.com

The VSX40 Series are dual output converters with a 36-75V input. The industry quarter-pak size of 2.3" x 1.5" x 0.5" coupled with 89% efficiency is an industry high-density breakthrough.

These converters utilize Vx high density technology. This technology has been featured in our highly efficient VKP and VKA series now successfully in use worldwide. The very high 89% efficiency minimizes the requirement for

heat-sinking and the low output ripple minimizes the need for additional filtering. For maximum flexibility, power can be traded between outputs as required. The VSX40 series feature virtually all of the options required by design engineers but not at the competition's typical additional price for each option. This multitude of features are standard on the VSX40 series.

ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	MIN	MAX	UNIT
Input Voltage: VSX40MD23	V_i		100	Vdc
I/O Isolation Voltage			1500	Vdc
I/P to case			1500	Vdc
O/P to case			200	Vdc
Operating Case Temperature	T	-40	100	°C

SPECIFICATIONS, ALL MODELS

Specifications are at $T_{CASE} = +40^{\circ}C$ nominal input voltage unless otherwise specified.

INPUT	PARAMETER	SYMBOL	MIN	TYP	MAX	UNITS
	Operating Input Voltage VSX40MD23	V_i	36	48	75	VDC
	Maximum Input Current ($V_i=0V$ to V_i max, $I_o=I_o$ max) VSX40MD23	I_i max			1.5	A
	I/P Reflected Ripple Current				260	mA p-p
	No Load Input Current	I_{iNL}		35		mA
	On/Off Activated Input Current	I_{iQ}		20		mA

OUTPUT Under any conditions, the voltage of V1 will always be greater or equal to that of V2.	PARAMETER	SYMBOL	MIN	TYP	MAX	UNITS	
	Output voltage (Note 1) Over all conditions of I/P voltage, load and temperature)						
	2.5 Vout (V2)	2.5 V_o	2.375	–	2.555	Vdc	
	3.3 Vout (V1)	3.3 V_o	3.225	–	3.450	Vdc	
	Output Voltage Setpoint ($V_i=48V$, $I_{o2}=9A$, $I_{o3}=6A$, $T_c=25^{\circ}C$)						
	2.5 (V2)	2.5 $V_{o,set}$	2.450		2.510	Vdc	
	3.3 (V1)	3.3 $V_{o,set}$	3.310		3.390	Vdc	
	Output Ripple and Noise Voltage (peak-to-peak, 100 MHz BW)						
	2.5 (V2)	–	–	–	60	mv p-p	
	3.3 (V1)	–	–	–	80	mv p-p	
	Output Current (Total module O/P power should not exceed 40 Watts)						
	2.5 (V2)	I_{o2}	–	–	16	A	
	3.3 (V1)	I_{o3}	–	–	12.12	A	
	Output Current Limit Inception ($V_o=95\%$ of V_o nom)						
	2.5 (V2)	$I_{o2,cli}$	16.8	18.5	21.0	A	
	3.3 (V1)	$I_{o3,cli}$	12.7	14.0	15.9	A	
	Output Short Ckt Current (Max impedance across short circuit = 65m Ω)						
	2.5 V_o		15	19	22	A	
	3.3 V_o		11	13.2	17	A	
	Efficiency ($V_i=48V$, $I_{o2}=8A$, $I_{o3}=6A$, $T_c=40^{\circ}C$)	η	88	89	–	%	
Dynamic Response ($\Delta I_o/\Delta t=0.2A/\mu sec$, $V_i=48V$, $T_c=25^{\circ}C$, either O/P) Load change of 50% I_o max; at any operating load up to $I_{o,max}$ or $P_{o,max}$ Peak Deviation outside settling point	–	–	2	–	% V_o nom		



NOTE: 1. Worst case voltage conditions occur with full load drawn from one output only, zero being drawn from the other. For worst case voltages at less extreme loading conditions, consult the factory.

GENERAL	PARAMETER	SYMBOL	MIN	TYP	MAX	UNITS
		Isolation Specifications				
	Isolation Capacitance	–	–	1000	–	pF
	Isolation Resistance	–	10	–	–	MΩ
	Feature Specifications					
	Remote On/Off (open collector equivalent, signal referenced to -Vin terminal)					
	VSx40MD23 Preferred Logic (negative)					
	Logic Low - Module On					
	Logic High - Module Off					
	VSX40MD23-1 - Optional Logic (positive)					
	Logic Low - Module Off					
	Logic High - Module On					
	Logic Low: At Von/off = 0V	Von/off	0	–	50	Vdc
		Ion/off		–	200	μA
	Turn On Time (Vo within 1% of steady state)					
	From Application of Vin	–	–	7	10	mSecs
	From Remote On/Off Activation)	–	–	3	4	mSecs
	Input Undervoltage Lockout (Turn Off & Turn On Voltages Track)					
	Turn On	–	30	33	36	Vdc
	Turn Off	–	27	30	33	Vdc
	Input Overvoltage Lockout (Turn Off & Turn On Voltages Track)					
	Turn Off	–	76	80	84	Vdc
	Turn On	–	74.5	78.5	82.5	Vdc
	Output Overvoltage Set Point (Non-latching independent control loop)					
	2.5 Vo	VO2OV clamp	2.7	2.9	3.2	Vdc
	3.3 Vo	VO3OV clamp	3.6	3.9	4.2	Vdc
	Overtemperature Shutdown	Tc	105	115	125	°C
	Hysteresis			10		°C
	Weight					
	VSX40MD23, VSX40MD23-1			67		Grams
	VSX40MD23-U, VSX40MD23-1U					
	Output Trim					
	Tie Trim to +2.5 Vo for trim down	2.5 Vo	VO ₂ td	–	-10	%
		3.3 Vo	VO ₃ td	–	-10	%
	Tie Trim to O/P RTN for trim up	2.5 Vo	VO ₂ td	–	10	%
		3.3 Vo	VO ₃ td	–	10	%

MECHANICAL

Dimensions are in inches (millimeters).

Tolerances: x.xx in. \pm 0.02 in.
x.xxx in. \pm 0.01 in.



Pinout Key	
1	+Vin
2	On/Off
3	-Vin
4	+2.5 Vout
5	O/P RTN
6	Trim
7	+3.3 Vout

NOTES:

1. Marked with: specific model ordered, date code, job code.
2. **MATERIAL:** Units are encapsulated in a low thermal resistance molding compound which has excellent chemical resistance and electrical properties in high humidity environments and over a wide operating temperature range. The encapsulant and outer shell of the unit have UL94V-0 ratings. Lead material is solder plated to allow ease of solderability.
3. **IMPORTANT:** When utilizing the PEM nuts for board mounting, it is required to follow guidelines in application note DCAN-41 available on the web at www.cdpowerelectronics.com.

ORDERING INFORMATION

To Find Model Number

Device Family VSX40MD23 - 1 U

VSX40MD23 (Quarter Brick, 40 Watt DC/DC)

Logic: No Number = Preferred Logic (Negative);
1 = Optional Logic (Positive)

Package _____

No Letter = Encapsulated; U = Unencapsulated

Model Numbers

VSX40MD23
VSX40MD23-U
VSX40MD23-1
VSX40MD23-1U

Power Electronics Division, United States
3400 E Britannia Drive, Tucson, Arizona 85706
Tel: 800.547.2537 Fax: 520.295.4160

C&D Technologies, (NCL)
Milton Keynes MK14 5BU UK
Tel: +44 (0)1908 615232 Fax: +44 (0)1908 617545

Any data, prices, descriptions or specifications presented herein are subject to revision by C&D Technologies, Inc. without notice. While such information is believed to be accurate as indicated herein, C&D Technologies, Inc. makes no warranty and hereby disclaims all warranties, express or implied, with regard to the accuracy or completeness of such information. Further, because the product(s) featured herein may be used under conditions beyond its control, C&D Technologies, Inc. hereby disclaims all warranties, either express or implied, concerning the fitness or suitability of such product(s) for any particular use or in any specific application or arising from any course of dealing or usage of trade. The user is solely responsible for determining the suitability of the product(s) featured herein for user's intended purpose and in user's specific application. C&D Technologies, Inc. does not warrant or recommend that any of its products be used in any life support or aviation or aerospace applications.