



ELECTRONICS, INC.
44 FARRAND STREET
BLOOMFIELD, NJ 07003
(973) 748-5089
<http://www.nteinc.com>

NTE1463 Integrated Circuit AF Power Amp for Tape Recorder

Features:

- AF Output Power: 2.7W/3.2Ω, or 2.3W/4Ω
- Small op Noise by Muting CRT
- High Ripple Reduction
- Good Supply Voltage Characteristics
- No Switching Distortion at High Frequency

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Supply Voltage, V_{CC}

Quiescent	13V
Operating	11V

Allowable Power Distortion, $P_{Dmax(1)}$ 1.2W

Allowable Power Distortion (Note 1), $P_{Dmax(2)}$ 2.25W

Current at Pin 11 ($R_L \geq 330\Omega$), I_{11} 30mA

Operating Temperature Range, T_{opr} -20° to $+70^\circ\text{C}$

Storage Temperature Range, T_{stg} -40° to $+150^\circ\text{C}$

Note 1. 50 x 50 x 1.5mm³ printed board used.

Recommended Operating Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Supply Voltage, V_{CC} 9V

Load Resistance, R_L 3.2 to 8.0Ω

Electrical Characteristics: ($T_A = +25^\circ\text{C}$, $V_{CC} = 9V$, $R_L = 3.2\Omega$, $f = 1\text{kHz}$, $R_g = 600\Omega$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Quiescent Current	I_{CC0}		—	15	25	mA
Voltage Gain	$V_{G(1)}$	Open Loop	—	68	—	dB
	$V_{G(2)}$	Closed Loop	42	45	48	dB
Output Power	P_O	$R_L = 3.2\Omega$, THD = 10%	2.1	2.7	—	W
		$R_L = 4\Omega$, THD = 10%	1.7	2.3	—	W
Input Resistance	r_i		12	20	—	kΩ
Total Harmonic Distortion	THD	$P_O = 300\text{mW}$	—	—	2.0	%
Output Noise Voltage	$V_{NO(1)}$	$R_g = 10\text{k}\Omega$	—	—	2.5	mV
	$V_{NO(2)}$	$R_g = 0\Omega$	—	—	0.8	mV

Pin Connection Diagram

