


Part No.	AL-103IR-85030C2	Diff No. 002
10 mm	Round	Type : LED Lamps

Package Dimension :



■ Features :

■ Descriptions :

■ Applications :

- Choice of various viewing angles.
- Available on Tape and Reel.
- Reliable and robust.
- The series is specially designed for application requiring higher brightness.
- The LED lamps are available with different color, intensities, epoxy colors etc.
- TV set
- Monitor
- Telephone

Part No. **AL-103IR-85030C2**

Diff No. 002

10 mm

Round

Type : LED Lamps

PART NO.	Chip		Lens Color
	Material	Emitted Color	
AL-103IR-85030C2	GaAlAs	Infrared	Water Clear

■ Absolute Maximum Ratings at Ta=25°C

Parameter	Symbol	Rating	Unit
Forward Current	I _F	350	mA
Operating Temperature	T _{opr}	-40 to +85	°C
Storage Temperature	T _{stg}	-40 to +85	°C
Soldering Temperature	T _{sol}	260 ± 5	°C
Power Dissipation	P _D	1260	mW
Peak Forward Current (Duty 1/10@1KHz)	I _F (Peak)	1	A
Reverse Voltage	V _R	5	V

■ Electronic Optical Characteristics :

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Radiated Output Power	P _O	/	65	/	mW/sr	I _F =350mA
Viewing Angle	2θ _{1/2}	/	30	/	deg	I _F =50mA
Peak Wavelength	λ _p	/	850	/	nm	I _F =50mA
Spectrum Radiation Bandwidth	△λ	/	40	/	nm	I _F =50mA
Forward Voltage	V _F	/	1.5	1.8	V	I _F =350mA
Reverse Current	I _R	/	/	50	μA	V _R =5V

Part No. **AL-103IR-85030C2**

Diff No. 002

10 mm

Round

Type : LED Lamps

■ Reliability test items and conditions :

NO	Item	Test Conditions	Test Hours/Cycle	Sample Size	Ac/Re
1	Solder Heat	TEMP : 260±5℃	5 SEC	76 PCS	0/1
2	Temperature Cycle	H : +85℃ 30min └ 5min L : -55℃ 30min	50 CYCLES	76 PCS	0/1
3	Thermal Shock	H : +100℃ 5min └ 10set L : -10℃ 5min	50 CYCLES	76 PCS	0/1
4	High Temperature Storage	TEMP : 100℃	1000 HRS	76 PCS	0/1
5	Low Temperature Storage	TEMP : -55℃	1000 HRS	76 PCS	0/1
6	DC Operating Life	TEMP : 25℃ I _F =20mA	1000 HRS	76 PCS	0/1
7	High Temperature / High Humidity	85℃ / 85%RH	1000 HRS	76 PCS	0/1

Part No. **AL-103IR-85030C2**



Diff No. 002

10 mm

Round

Type : LED Lamps

◆ TYPICAL ELECTRICAL-OPTICAL CHARACTERISTICS CURVES



RELATIVE INTENSITY VS. WAVELENGTH(λ_p)

- (1) GaAsP/GaAs 655nm/Red
- (2) GaP 568nm/ Yellow Green
- (3) GaAsP/GaP 585nm/Yellow
- (4) GaAsP/GaP 635nm/Orange & Hi-Eff Red
- (5) GaP 700nm/Bright Red
- (6) GaAlAs/GaAs 660nm/Super Red
- (8) GaAsP/GaP 610nm/Super Red

- (9)- GaAlAs 880nm
- (10)-GaAs/GaAs&GaAlAs/GaAs 940nm
- (A)- GaN 430nm/Blue
- (B)- InGaN 470nm/Blue
- (C)- InGaN 502nm/Ultra Green
- (D)- InGaN 523nm/Ultra Green

Part No. **AL-103IR-85030C2**

Diff No. 002


10 mm

Round


Type : LED Lamps

◆ CHARACTERISTICS DIAGRAMS

FORWARD CURRENT VS. FORWARD VOLTAGE



RELATIVE LUMINOUS INTENSITY VS. FORWARD CURRENT



FORWARD CURRENT VS. AMBIENT TEMPERATURE

