

## **PLL Product Specification**

Model: PLL400-1800 Rev: B Date: 4/17/2003

Customer: SIRENZA MICRODEVICES, INC. AppNote: 108

Operating Temperature Range: (-35 ° to 85 ° C)

| Parameter                       | Min  | Тур  | Max  | Units  | Х | Remarks |
|---------------------------------|------|------|------|--------|---|---------|
| Frequency Range -               | 1600 | 1800 | 2000 | MHz    | Х |         |
| Step Size -                     |      | 1000 |      | kHz    | Х |         |
| Settling Time - To within 1 kHz |      | 2    | 10   | mSec   |   |         |
| Output Power -                  | -4   | -1   | 2    | dBm    | Х |         |
| Output Phase Noise:             |      |      |      |        |   |         |
| 10 kHz                          |      | -85  | -81  | dBc/Hz |   |         |
| 100 kHz                         |      | -110 | -104 | dBc/Hz | Х |         |
| Power Supply -                  | 4.75 | 5    | 5.25 | Volts  |   |         |
| Supply Current -                |      | 25   | 40   | mA     | Х |         |
| Spurious Product - 1000 kHz     |      | -65  | -60  | dBc    | Х |         |
| Reference Feedthrough -         |      | -80  | -70  | dBc    |   |         |
| Harmonic Suppression:           |      |      |      |        |   |         |
| 2nd Harmonic                    |      | -10  | -8   | dBc    | Х |         |
| 3rd Harmonic                    |      | -15  | -10  | dBc    | Х |         |
| Ref Osc Signal:                 |      |      |      |        |   |         |
| Frequency                       |      | 10   |      | MHz    |   |         |
| Amplitude                       | 0.4  |      | 2    | Vp-p   |   |         |
| Phase Noise - 1 kHz             |      | -145 |      | dBc/Hz |   |         |
| Input Impedance                 |      | 10   |      | kΩ     |   |         |
| Output Impedance -              |      | 50   |      | Ω      |   |         |

## **Package Information**

| Package Type: | PLL400                  | Drawing Number:   | 60080 |
|---------------|-------------------------|-------------------|-------|
| Dimensions:   | 0.6 x 0.6 x 0.14 inches | Drawing Revision: | В     |

## Comments

X Indicates parameter to be tested 100% in production

Performance tests and ratings for Sirenza Microdevices' products were performed internally by Sirenza and measured using specific computer systems and/or components and reflect the approximate performance of the the products as measured by those tests. Any difference in circuit implementation, test software, or test equipment may affect actual performance. The information provided herein is believed to be reliable at press time and Sirenza Microdevices assumes no responsibility for the use of this information. All such use shall be entirely at the user's own risk. Prices and specifications for Sirenza Microdevices' products are subject to change without notice. Buyers should consult Sirenza Microdevices' standard terms and conditions of sale for Sirenza's limited warranty with regard to its products. These products may be patented or include patented technology. No patent rights or licenses to any of the circuits described herein are implied or granted to any third party. Sirenza Microdevices does not authorize or warrant any product for use in life-support devices and/or systems.

Page 1 of 1