


Specifications

Parameter	Unit	Minimum	Typical	Maximum
Center Frequency	MHz	239.85	240	240.15
Insertion Loss	dB	-	25.7	30
1 dB Bandwidth	MHz	-	8.8	-
1.5 dB Bandwidth	MHz	9	9.04	-
3 dB Bandwidth	MHz	9.2	9.35	-
40 dB Bandwidth	MHz	-	10.93	11
50 dB Bandwidth	MHz	-	11.1	-
Passband Variation($f_0 \pm 14.5\text{MHz}$)	dB	-	0.8	1.0
Absolute Delay	usec	-	2.66	-
Group Delay Variation($f_0 \pm 14.5\text{MHz}$)	nsec	-	100	120
Ultimate Rejection	dB	50	57	-
Material Temperature coefficient	KHz/°C	-4.32		
Ambient Temperature	°C	25		
Package Size	DIP3512 (35.0x12.8x4.7mm3)			

Notes:


1. All specifications are based on the test circuit shown
2. In production, devices will be tested at room temperature to a guardbanded specification to ensure electrical compliance over temperature
3. Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances
4. This is the optimum impedance in order to achieve the performance show

Matching Configuration




L1 = 18nH
C1 = C2 = 15pF
Source/Load Impedance = 50 ohm

Notes - Component values may change depending on board layout.

	SIPAT Co., Ltd. (CETC No. 26 Research Institute) Nanping Huayuan Road No. 14 Chongqing, China, 400060	Part Number	LBT24002	
		Rev. Date	2005-12-15	
		Rev.	1.0	Page

Package Dimension



Input:1
Output:5




SIPAT Co., Ltd.
(CETC No. 26 Research Institute)
Nanping Huayuan Road No. 14
Chongqing, China, 400060


Part Number	LBT24002	
Rev. Date	2005-12-15	
Rev.	1.0	Page 2/3

Typical Performance


Frequency Respond




Passband Respond




Group Delay Variation($f_0 \pm 4.5\text{MHz}$)




Phase Linearity($f_0 \pm 4.5\text{MHz}$)



Smith Chart S11



Smith Chart S22



SIPAT Co., Ltd.
(CETC No. 26 Research Institute)
Nanping Huayuan Road No. 14
Chongqing, China, 400060

Part Number

LBT24002

Rev. Date

2005-12-15

Rev.

1.0

Page 3/3