

APPROVAL

PART NO.	DESCRIPTION	REMARKS
HS5701C-T	LCD MODULE (320 x RGBx 240) with Touch Screen	* This is ROHS compliant

CUSTOMER APPLICATION P/N	
APPROVED BY	
DATE	

PLEASE KINDLY FIND AND APPROVE THE SPECIFICATIONS INSERTED
HEREIN AND RETURN ONE COPY HERE OF WITH YOUR SIGNATURE OF APPROVAL.

PERPARED BY	CHECKED BY	CONFIRMED BY



HYES Optoelectronics, Inc.

2000 Wyatt Drive Suite 6
Santa Clara, CA 95054 USA

CONTENTS:

No.	Item
1	BASIC SPECIFICATION 1.1 Mechanical Specification 1.2 Display Specification 1.3 Outline Dimension 1.4 Block Diagram 1.5 Interface Pin
2	ELECTRICAL CHARACTERISTICS 2.1 Absolute Maximum Ratings 2.2 DC Characteristics 2.3 Back-light 2.4 AC Characteristics 2-5 Interface Timing Chart
3	OPTICAL CHARACTERISTICS 3.1 Condition 3.2 Definition of Optical Characteristics
4	RELIABILITY
5	PRODUCT HANDING AND APPLICATION
6	DATECODE
7	PACKING & LOTNO
8	INSPECTION STANDARD

1. BASIC SPECIFICATION

1.1 Mechanical specifications

Items	Nominal Dimension	Unit
Dot Matrix	320*RGB*240	dots
Module Size (W x H x T)	154.6 x 114.8 x 9.85	mm
Viewing Area (W x H)	118.18 x 89.38	mm
Active Area (W x H)	115.18 x 86.38	mm
Dot Size (W x H)	0.105 x 0.345	mm
Dot Pitch (W x H)	0.12 x 0.36	mm
Driving method	1/240	Duty
	1/16	Bias
Driving IC Package	TAB	

* Expose the driver IC under blaze (luminosity over than 1 cd) when using the LCM may cause IC operating failure.

1.2 Display specification

Display	Descriptions	Note
LCD Type	5.7" Color STN	
LCD Mode	Negative	
Polarizer Mode	Transmissive	
Polarizer UV-Cutting	With	
Polarizer Surface	Normal	
Background Color	Black	
Backlight Type	CCFL	
Backlight Color	White	
Viewing Direction	6 O'clock Direction	

Date : Sep. 10, 2007

TECHNICAL SPECIFICATION


HYES

LCM


HS5701C-T

Page 3 of 25

1.4 Block diagram:



Recommended Circuit for Contrast Adjustment



$R1+R2+VR=10 \sim 20K\Omega$
 $T_r=28A1202$ or equivalent

Date : Sep. 10, 2007

TECHNICAL SPECIFICATION

HYES

LCM

HS5701C-T

Page 5 of 25

1.5 Interface pin :

Pin No.	Pin Symbol	I/O	Description
1	FRM	I	It is active during the last line of each frame, and is shifted through the COM drivers one by one, to scan the display's common connections.
2	CL1	I	Latch pulse input pin for display data. Data is latched on the falling edge of the clock pulse.
3	CL2	I	Display data shift clock input pin for taking display data Data is read on the falling edge of the clock pulse
4	/DISP	I	Control input for deselect output level. H (On), L (Off)
5	VDD	P	Power supply input pin for the circuit system.(+5.0V)
6	VSS	P	Ground pin for the circuit system.
7	VLCD	P	Power supply for LCD driving voltage.
8~15	D7~D0	I	Display data input

Touch panel interface pin :

Pin No.	Pin Symbol	I/O	Description
1	Y+	-	Touch screen.
2	X-	-	Touch screen.
3	Y-	-	Touch screen.
4	X+	-	Touch screen.

Backlight interface pin :

Pin No.	Pin Symbol	I/O	Description
1	CCFL1	P	CCFLAC voltage power supply input. (From inverter)
2	NC	-	No connect
3	CCFL2	P	CCFLAC voltage ground line input. (From inverter)

2. ELECTRICAL CHARACTERISTICS

2.1 Absolute Maximum Ratings

Items	Symbol	Min.	Max.	Unit
Supply voltage for logics	VDD	-0.3	7.0	V
Supply voltage for driving LCD	VLCD	-0.3	40	V
Input voltage	V _I	-0.3	VDD+0.3	V
Operate temperature range	T _{OP}	-10	60	°C
Storage temperature range	T _{ST}	-20	70	°C

2.2 DC Characteristics

Items	Symbol	Min.	Typ.	Max.	Unit	Condition
Supply voltage (Logic)	VDD	2.5	5	5.5	V	-
Supply voltage (LCD)	VLCD	-	(24.95)	-	V	Top = 60°C
		25.5	26.5	27.5	V	*NOTE1
		-	(27.35)	-	V	Top = -10°C
Input high level voltage	V _{IH}	0.8VDD	-	-	V	-
Input low level voltage	V _{IL}	-	-	0.2VDD	V	-
Output high level voltage	V _{OH}	VDD-0.4	-	-	V	-
Output low level voltage	V _{OL}	-	-	0.4	V	-
Display data shift clock	XCK	-	2.268	-	MHZ	-
AC-converting signal input for LCD driver wavefrom(1)	FRAME	70	-	90	HZ	For 256 colors
AC-converting signal input for LCD driver wavefrom(2)	FRAME	120	-	150	HZ	For 4096 colors
AC-converting signal input for LCD driver wavefrom(3)	FRAME	160	-	240	HZ	For 65K colors
Power supply current	IDD	-	0.5	1	mA	*NOTE1
Power supply current(LCD)	ILCD	-	7	14	mA	*NOTE1

*NOTE1 : Min. and Max. Voltage is mean within the range will has optimum contrast at Ta:25°C

Typ. Voltage is specified as module driving condition: Ta=25°C, V_{OP} at Optimum Contrast,
the measuring condition as below, this value is **HYES** recommend when customer change the set
condition , the VLCD will be change.

NOTE2 :

Measuring Condition :

Standard Value MAX

Ta = 25°C

VDD-VSS = 5.0V

VLCD - GND = V_{OP} at optimum Contrast

Bias = 1/16

Duty = 1/240

Display Patten = Checkered pattern

Date : Sep. 10, 2007

TECHNICAL SPECIFICATION

HYES

LCM

HS5701C-T

Page 8 of 25

2.3 Back-light Specification

Items	Symbol	Min.	Typ.	Max.	Unit	Condition
Frequency	F_L	25	35	45	KHz	$T=25\pm 3^\circ\text{C}$
Lamp Current	I_L	-	5.0	-	mA rms	$T=25\pm 3^\circ\text{C}$
Start voltage	V_s	410	-	-	V rms	$T=25\pm 3^\circ\text{C}$
Output Open Voltage	V_{open}	-	-	460	V rms	$T=25\pm 3^\circ\text{C}$
Lamp Voltage	V_{Load}	320	340	360	V rms	$T=25\pm 3^\circ\text{C}$
Brightness	B	2500	-	-	cd/m^2	$T=25\pm 3^\circ\text{C}$ $I_L=5\text{mA}$ (*Note3)
Brightness Uniformity	B_U	75	-	-	%	(*Note4)
Operating Life	TB	50000	-	-	Hrs	$T=25\pm 3^\circ\text{C}$ $I_L=5\text{mA}$ (*Note5)

*Note3: These specifications are on the surface of the Backlight unit.

*Note4: Brightness uniformity = $(B_{min} / B_{max}) \times 100\%$

*Note5: Until half of initial brightness

*Recommend the inverter type number: TDK XAD018SR-1


2.4 AC Characteristics

NT7705

Common Mode ($V_{SS} = V_5 = 0V$, $V_{DD} = 2.5 - 5.5V$, $V_0 = 15$ to $40V$ and $T_A = -30$ to $+85^\circ C$, unless otherwise noted)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Shift clock period	tWLP	250	-	-	ns	$t_r, t_f \leq 20ns$
Shift clock "H" pulse width	tWLPH	15	-	-	ns	$V_{DD} = +5.0V \pm 10\%$
		30	-	-	ns	$V_{DD} = +2.5 - +4.5V$
Data setup time	t _{SU}	30	-	-	ns	
Data hole time	t _H	50	-	-	ns	
Input signal rise time	t _r		-	50	ns	
Input signal fall time	t _f		-	50	ns	
$\overline{DISPOFF}$ Removal time	t _{SD}	100	-	-	ns	
$\overline{DISPOFF}$ enable pulse width	t _{WDL}	1.2	-	-	μs	
Output delay time (1)	t _{DL}	-	-	200	ns	$C_L = 15pF$
Output delay time (2)	t _{pd1} , t _{pd2}	-	-	1.2	μs	$C_L = 15pF$
Output delay time (3)	t _{pd3}	-	-	1.2	μs	$C_L = 15pF$

Timing Characteristics of Common Mode



Date : Sep. 10, 2007

TECHNICAL SPECIFICATION

HYES

LCM

HS5701C-T

Page 10 of 25

NT7706

Segment Mode 1 ($V_{SS} = V_5 = 0V$, $V_{DD} = 4.5 - 5.5V$, $V_0 = 15$ to $40V$, and $T_A = -30$ to $+85^\circ C$, unless otherwise noted)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Shift clock period	twck	50	-		ns	tr, tf \leq 10ns, Note 1
Shift clock "H" pulse width	twckH	15	-		ns	
Shift clock "L" pulse width	twckL	15	-		ns	
Data setup time	tDS	10	-		ns	
Data hole time	tDH	12	-		ns	
Latch pulse "H" pulse width	twLPH	15	-		ns	
Shift clock rise to Latch pulse rise time	tLD	0	-		ns	
Shift clock fall to Latch pulse fall time	tSL	30	-		ns	
Latch pulse rise to Shift clock rise time	tLS	25	-		ns	
Latch pulse fall to Shift clock rise time	tLH	25	-		ns	
Input signal rise time	tr		-	50	ns	Note 2
Input signal fall time	tr		-	50	ns	Note 2
Enable setup time	tS	10	-		ns	
$\overline{\text{DISPOFF}}$ Removal time	tSD	100	-		ns	
$\overline{\text{DISPOFF}}$ enable pulse width	twDL	1.2	-		μs	
Output delay time (1)	tD		-	30	ns	CL = 15pF
Output delay time (2)	tpd1, tpd2		-	1.2	μs	CL = 15pF
Output delay time (3)	tpd3		-	1.2	μs	CL = 15pF

Note

1. Take the cascade connection into consideration.
2. $(t_{CK} - tw_{ckH} - tw_{ckL})/2$ is the maximum in the case of high speed operation.

Date : Sep. 10, 2007

TECHNICAL SPECIFICATION


HYES

LCM


HS5701C-T

Page 11 of 25

Timing waveform of the Segment Mode



2-5 Interface Timing Chart



Date : Sep. 10, 2007

TECHNICAL SPECIFICATION

HYES

LCM

HS5701C-T

Page 13 of 25

3. OPTICAL CHARACTERISTICS

3.1 Characteristics

Driving condition

Item	Duty	Bias	Note
Value	1/240	1/16	1

Electrical and Optical Characteristics

No.	Item	symbol / temp.		Min.	Typ.	Max.	Unit	Note	
2	Response Time	Tr	25 °C	-	145	290	ms	2	
		Tf	25 °C	-	80	160			
3	Viewing Angle	Front-Rear	$\Theta 1$	$\Phi = 270^\circ$	-10	-	30	degree	3
		Left-Right	$\Theta 2$		-30	-	30		
4	Contrast Ratio	Cr	25 °C	-	25	-	-	4	
5	Red x-code	Rx	25 °C	0.55	0.60	0.65	-	5	
	Red y-code	Ry		0.28	0.33	0.38			
	Green x-code	Gx		0.24	0.29	0.34			
	Green y-code	Gy		0.52	0.57	0.62			
	Blue x-code	Bx		0.10	0.15	0.20			
	Blue y-code	By		0.04	0.09	0.14			
	White x-code	Wx		0.27	0.32	0.37			
	White y-code	Wy		0.28	0.33	0.38			
	Brightness	Y		65	80	-			cd/m ²
6	Brightness Uniformity		25 °C	80	-	-	%	6	

Date : Sep. 10, 2007

TECHNICAL SPECIFICATION

HYES

LCM


HS5701C-T

Page 14 of 25


3.2 Definition of optical characteristics

Measurement condition :


Transmissive and Transflective type



[Note 1] Definition of LCD Driving Vop and Waveform :





[Note 2] Definition of Response Time



[Note 3] Definition of Viewing Angle :

[Note 4] Definition of Contrast Ratio :



$$\text{Contrast Ratio} = \frac{TH}{TL}$$

Date : Sep. 10, 2007

TECHNICAL SPECIFICATION


HYES

LCM


HS5701C-T

Page 15 of 25

[Note 5] Definition of measurement of Color Chromaticity and Brightness




[Note 6] Definition of Brightness Uniformity



$$\text{Brightness Uniformity} = \frac{\text{Minimum Brightness of Point 1~9}}{\text{Maximum Brightness of Point 1~9}}$$

[Note 7] Definition of Measurement of Reflectance



4. RELIABILITY :

Item No	Items	Condition	Remark
1	High temperature operating	70 °C , 200 hours	Finish product (With polarizer)
2	Low temperature operating	-20 °C , 200 hours	Finish product (With polarizer)
3	High temperature storage	60 °C , 200 hours	Finish product (With polarizer)
4	Low temperature storage	-10 °C , 200 hours	Finish product (With polarizer)
5	High temperature & humidity storage	60°C, 90%RH, 100 hours	Finish product (With polarizer)
6	Thermal Shock storage	-10°C, 30min.<=> 60°C, 30min. 10 Cycles	Finish product (With polarizer)
7	Vibration test	10 => 55 =>10 => 55 => 10 Hz , within 1 minute Amplitude : 1.5mm. 15 minutes for each Direction (X,Y,Z)	Finish product (With polarizer)
8	Drop test	Packed, 100CM free fall, 6 sides, 1 corner, 3edges	Finish product (With polarizer)
9	Life time	50,000 hours 25°C , 70%RH below , specification condition driving	Finish product (With polarizer)

- * One single product test for only one item.
- * Judgment after test : keep in room temperature for more than 2 hours.
 - Current consumption < 2 times of initial value
 - Contrast > 1/2 initial value
 - Function : work normally

Date : Sep. 10, 2007

TECHNICAL SPECIFICATION

HYES

LCM

HS5701C-T

Page 17 of 25

5. PRODUCT HANDLING AND APPLICATION

PRECAUTION FOR HANDLING LCM

- The LCD module contains a C-MOS LSI. People who operate the LCM should wear ESD protection equipment to prevent ESD hurt on products.
- Do not input any signal before power is turned on.
- Do not take LCM from its packaging bag until it is assembled.
- Peel off the LCM protective film slowly since static electricity may be generated.
- Pay attention to the humidity of the work shop, 50~60%RH is satisfactory.
- Use a non-leak iron for soldering LCM.
- Do not touch the display surface or connection terminals area with bare hands. Smudges on the display surface reduce the insulation between terminals.
- Cautions for soldering to LCM:
Condition for soldering I/O terminals:
Temperature at iron tip :280°C±10°C.
Soldering time : 3~4sec./ terminals.
Type of solder : Eutectic solder(rosin flux filled).

PRECAUTION IN USE OF LCD

- Do not contact or scratch the front surface and the contact pads of a LCD panel with hard materials such as metal or glass or with one's nail.
- To clean the surface , wipe it gently with soft cloth dampened by alcohol.
- Do not attempt to wipe off the contact pads.
- Keep LCD panels away from direct sunlight , also avoid them in high-temperature & high humidity environment for a long period.
- Do not drive LCD panels by DC voltage.
- Do not expose LCD panels to organic solvent.
- Liquid in LCD is hazardous substance. In case a contact with liquid crystal material is occurred, be sure to immediately wash such material away by soap and water.
- The polarizer is easily damaged and should be handle with special care. Don't press or rub it with hard objects.

PRECAUTION FOR STORING LCM

- To avoid degradation of the device , do not store the module under the conditions of direct sunlight , high temperature or high humidity . Keep the module in bags designed to prevent static electricity charging under low temperature / normal humidity conditions(avoid high temperature / high humidity and low temperature below 0°C)

USING ON MEDICAL CARE , SAFETY OR HAZARDOUS APPLICATION OR SYSTEM

- For the application in medical care, safety and hazardous products or systems, an authorization from **HYES** is required. **HYES** will not responsible for any damage or loss which caused by the products without any authorization given by **HYES**.
- This product is not allowed to be designed and used for military application and/or purpose.
- The delivery of this product to the countries and/or regions where the embargoes are imposed by U.N. is prohibited.

Date : Sep. 10, 2007

TECHNICAL SPECIFICATION

HYES

LCM

HS5701C-T

Page 18 of 25

6. DATE CODE OF PRODUCTS

- Date code will be shown on each product :


- **Y MM DD - XXX**

Year Month Day - Production lots


- Example: 2 1 2 2 3 - 0 0 3 ==>Year 2002, Dec.,23rd , Batch no.03

7. PACKING



Instruction of lot number:



Label of carton:



Packing tray must be stacked with alternated direction to each others.
To tacks packing trays in same direction will cause product damaged.



Date : Sep. 10, 2007

TECHNICAL SPECIFICATION

HYES

LCM


HS5701C-T

Page 20 of 25

NOTE:

T.B.D pcs / Tray
 T.B.D Tray / Box
 T.B.D Box / Carton
 T.B.D pcs / Carton

- (1) Be warned, the direction of the tray has to turn it by 180 degree before stack it up. Otherwise, it will be packager's responsibility!!
- (2) Safe Stack : 5 cartons only



Date : Sep. 10, 2007

TECHNICAL SPECIFICATION

HYES

LCM

HS5701C-T

Page 21 of 25

8. INSPECTION STANDARD

8.1. QUALITY :

THE QUALITY OF GOODS SUPPLIED TO PURCHASER SHALL COME UP TO THE FOLLOWING STANDARD.

8.1.1. THE METHOD OF PRESERVING GOODS

AFTER DELIVERY OF GOODS FROM **HYES** TO PURCHASER. PURCHASER SHALL CONTROL THE LCM AT -10 °C ~ 40 °C ,AND IT MIGHT BE DESIRABLE TO KEEP AT THE NORMAL ROOM TEMPERATURE AND HUMIDITY UNTIL INCOMING INSPECTION OR THROWING INTO PROCESS LINE.

8.1.2. INCOMING INSPECTION

(A) THE METHOD OF INSPECTION

IF PURCHASER MAKE AN INCOMING INSPECTION , A SAMPLING PLAN SHALL BE APPLIED ON THE CONDITION THAT QUALITY OF ONE DELIVERY SHALL BE REGARDED AS ONE LOT.

(B) THE STANDARD OF QUALITY

ISO-2859-1 (or MIL-STD-105D) , LEVEL II SINGLE PLAN.

CLASS	AQL(%)
CRITICAL	0.4 %
MAJOR	0.65 %
MINOR	1.5 %
TOTAL	1.5 %

EVERY ITEM SHALL BE INSPECTED ACCORDING TO THE CLASS.

(C) MEASURE

IF AS THE RESULT OF ABOVE RECEIVING INSPECTION , A LOT OUT IS DISCOVERED. PURCHASER SHALL BE INFORM SELLER OF IT WITHIN SEVEN DAYS. BUT FIRST SHIPMENT WITHIN FOURTEEN DAYS.

8.1.3. WARRANTY POLICY

HYES WILL PROVIDE ONE-YEAR WARRANTY FOR THE PRODUCTS ONLY IF UNDER SPECIFICATION OPERATING CONDITIONS. **HYES** WILL REPLACE NEW PRODUCTS FOR THESE DEFECT PRODUCTS WHICH UNDER WARRANTY PERIOD AND BELONG TO THE RESPONSIBILITY OF **HYES**.

8.2. CHECKING CONDITION

8.2.1. CHECKING DIRECTION SHALL BE IN THE 45 DEGREE AREA TO FACE THE SAMPLE.

8.2.2. CHECKER SHALL SEE OVER 30 cm. WITH BARE EYES FAR FROM SAMPLE AND USING 2 PCS. OF 20W FLUORESCENT LAMP.

Date : Sep. 10, 2007

TECHNICAL SPECIFICATION

HYES

LCM

HS5701C-T

Page 22 of 25

8.3. INSPECTION PLAN :

CLASS	ITEM	JUDGEMENT	CLASS
PACKING & INDICATE	1. OUTSIDE AND INSIDE PACKAGE	"MODEL NO." , "LOT NO." AND "QUANTITY" SHOULD INDICATE ON THE PACKAGE.	Minor
	2. MODEL MIXED AND QUANTITY	OTHER MODEL MIXED.....REJECTED QUANTITY SHORT OR OVER.....REJECTED	Critical
	3. PRODUCT INDICATION	"MODEL NO." SHOULD INDICATE ON THE PRODUCT	Major
ASSEMBLY	4. DIMENSION, LCD GLASS SCRATCH AND SCRIBE DEFECT.	ACCORDING TO SPECIFICATION OR DRAWING.	Major
APPEARANCE	5. VIEWING AREA	POLARIZER EDGE OR LCD'S SEALING LINE IS VISABLE IN THE VIEWING AREAREJECTED	Minor
	6. BLEMISH · BLACK SPOT · WHITE SPOT IN THE LCD AND LCD GLASS CRACKS	ACCORDING TO STANDARD OF VISUAL INSPECTION (INSIDE VIEWING AREA)	Minor
	7. BLEMISH · BLACK SPOT WHITE SPOT AND SCRATCH ON THE POLARIZER	ACCORDING TO STANDARD OF VISUAL INSPECTION (INSIDE VIEWING AREA)	Minor
	8. BUBBLE IN POLARIZER	ACCORDING TO STANDARD OF VISUAL INSPECTION (INSIDE VIEWING AREA)	Minor
	9. LCD'S RAINBOW COLOR	STRONG DEVIATION COLOR (OR NEWTON RING) OF LCD.....REJECTED. OR ACCORDING TO LIMITED SAMPLE (IF NEEDED, AND INSIDE VIEWING AREA)	Minor
ELECTRICAL	10. ELECTRICAL AND OPTICAL CHARACTERISTICS (CONTRAST · VOP · CHROMATICITY ... ETC)	ACCORDING TO SPECIFICATION OR DRAWING . (INSIDE VIEWING AREA)	Critical
	11. MISSING PATTERN	MISSING DOT · LINE · CHARACTERREJECTED	Critical
	12. SHORT CIRCUIT · WRONG PATTERN DISPLAY	NON DISPLAY · WRONG PATTERN DISPLAY · CURRENT CONSUMPTION OUT OF SPECIFICATION..... REJECTED	Critical
	13. PIN HOLE · PATTERN DEFORMITY	ACCORDING TO STANDARD OF VISUAL INSPECTION	Minor

Date : Sep. 10, 2007

TECHNICAL SPECIFICATION


HYES

LCM

HS5701C-T

Page 23 of 25

8.4. STANDARD OF VISUAL INSPECTION

NO.	CLASS	ITEM	JUDGEMENT															
8.4.1	MINOR	· BLEMISH · BLACK SPOT · WHITE SPOT IN THE LCD.	(A) ROUND TYPE: unit : mm. <table border="1"> <thead> <tr> <th>DIAMETER (mm.)</th> <th>ACCEPTABLE Q'TY</th> </tr> </thead> <tbody> <tr> <td>$\Phi \leq 0.1$</td> <td>DISREGARD</td> </tr> <tr> <td>$0.1 < \Phi \leq 0.2$</td> <td>2</td> </tr> <tr> <td>$0.2 < \Phi \leq 0.25$</td> <td>1</td> </tr> <tr> <td>$0.25 < \Phi$</td> <td>0</td> </tr> </tbody> </table> NOTE: $\Phi = (\text{LENGTH} + \text{WIDTH})/2$	DIAMETER (mm.)	ACCEPTABLE Q'TY	$\Phi \leq 0.1$	DISREGARD	$0.1 < \Phi \leq 0.2$	2	$0.2 < \Phi \leq 0.25$	1	$0.25 < \Phi$	0					
		DIAMETER (mm.)	ACCEPTABLE Q'TY															
$\Phi \leq 0.1$	DISREGARD																	
$0.1 < \Phi \leq 0.2$	2																	
$0.2 < \Phi \leq 0.25$	1																	
$0.25 < \Phi$	0																	
		· BLEMISH · BLACK SPOT · WHITE SPOT AND SCRATCH ON THE POLARIZER	(B) LINER TYPE: unit : mm. <table border="1"> <thead> <tr> <th>LENGTH</th> <th>WIDTH</th> <th>ACCEPTABLE Q'TY</th> </tr> </thead> <tbody> <tr> <td>-----</td> <td>$W \leq 0.03$</td> <td>DISREGARD</td> </tr> <tr> <td>$L \leq 5.0$</td> <td>$0.03 < W \leq 0.05$</td> <td>3</td> </tr> <tr> <td>$L \leq 5.0$</td> <td>$0.05 < W \leq 0.07$</td> <td>1</td> </tr> <tr> <td>-----</td> <td>$0.07 < W$</td> <td>FOLLOW ROUND TYPE</td> </tr> </tbody> </table>	LENGTH	WIDTH	ACCEPTABLE Q'TY	-----	$W \leq 0.03$	DISREGARD	$L \leq 5.0$	$0.03 < W \leq 0.05$	3	$L \leq 5.0$	$0.05 < W \leq 0.07$	1	-----	$0.07 < W$	FOLLOW ROUND TYPE
LENGTH	WIDTH	ACCEPTABLE Q'TY																
-----	$W \leq 0.03$	DISREGARD																
$L \leq 5.0$	$0.03 < W \leq 0.05$	3																
$L \leq 5.0$	$0.05 < W \leq 0.07$	1																
-----	$0.07 < W$	FOLLOW ROUND TYPE																
8.4.2	MINOR	BUBBLE IN POLARIZER	unit : mm. <table border="1"> <thead> <tr> <th>DIAMETER</th> <th>ACCEPTABLE Q'TY</th> </tr> </thead> <tbody> <tr> <td>$\Phi \leq 0.15$</td> <td>DISREGARD</td> </tr> <tr> <td>$0.15 < \Phi \leq 0.5$</td> <td>2</td> </tr> <tr> <td>$0.5 < \Phi$</td> <td>0</td> </tr> </tbody> </table>	DIAMETER	ACCEPTABLE Q'TY	$\Phi \leq 0.15$	DISREGARD	$0.15 < \Phi \leq 0.5$	2	$0.5 < \Phi$	0							
DIAMETER	ACCEPTABLE Q'TY																	
$\Phi \leq 0.15$	DISREGARD																	
$0.15 < \Phi \leq 0.5$	2																	
$0.5 < \Phi$	0																	
8.4.3	MINOR	PIN HOLE · PATTERN DEFORMITY	<div style="display: flex; align-items: center;">  <table border="1" style="margin-left: 20px;"> <thead> <tr> <th colspan="2">DIAMETER</th> <th>ACC. Q'TY</th> </tr> </thead> <tbody> <tr> <td>$\Phi \leq 0.1$</td> <td></td> <td>DISREGARD</td> </tr> <tr> <td>$0.1 < \Phi \leq 0.25$</td> <td></td> <td>3</td> </tr> <tr> <td>$0.25 < \Phi$</td> <td></td> <td>0</td> </tr> </tbody> </table> </div> <p style="text-align: center;">$\Phi = (a+b)/2$</p>	DIAMETER		ACC. Q'TY	$\Phi \leq 0.1$		DISREGARD	$0.1 < \Phi \leq 0.25$		3	$0.25 < \Phi$		0			
DIAMETER		ACC. Q'TY																
$\Phi \leq 0.1$		DISREGARD																
$0.1 < \Phi \leq 0.25$		3																
$0.25 < \Phi$		0																

Date : Sep. 10, 2007








TECHNICAL SPECIFICATION

HYES

LCM

HS5701C-T

Page 24 of 25

NO.	CLASS	ITEM	JUDGEMENT
8.4.4	MINOR	CHIPPING	 $Y > S$ REJ.
8.4.5	MINOR	CHIPPING	 $X \text{ or } Y > S$ REJ.
8.4.6	MAJOR	GLASS CRACK	 $Y > (1/2) T$ REJ.
8.4.7	MAJOR	SCRIBE DEFECT	 <ol style="list-style-type: none"> $a > L/3$, $A > 1.5\text{mm}$. REJ. B : ACCORDING TO DIMENSION
8.4.8	MINOR	CHIPPING (ON THE TERMINAL AREA)	 $\Phi = (x+y)/2 > 2.5 \text{ mm}$ REJ.
8.4.9	MINOR	CHIPPING (ON THE TERMINAL SURFACE)	 $Y > (1/3) T$ REJ.
8.4.10	MINOR	CHIPPING	 $Y > T$ REJ.

Date : Sep. 10, 2007

TECHNICAL SPECIFICATION

HYES

LCM

HS5701C-T

Page 25 of 25