


**PART NUMBER:** CPE-750P

**DESCRIPTION:** panel mount piezo indicators

**SPECIFICATONS**


|                         |                           |                  |
|-------------------------|---------------------------|------------------|
| operating frequency     | 3.6 ± 0.5 KHz             |                  |
| operating voltage range | 4 ~ 28 V DC               |                  |
| current consumption     | 7 mA max.                 | at 12 V DC       |
| sound pressure level    | 80 db min.                | at 30 cm/12 V DC |
| rated voltage           | 12 V DC                   |                  |
| tone                    | continuous                | at 12 V DC       |
| operating temperature   | -30 ~ +85° C              |                  |
| storage temperature     | -40 ~ +95° C              |                  |
| dimensions              | Ø37.8 x H23.5 mm          |                  |
| weight                  | 18.5 g max.               |                  |
| material                | ABS UL-94 1/16" HB (gray) |                  |
| terminal                | pin type (Sn plating)     |                  |
| RoHS                    | yes                       |                  |

**APPEARANCE DRAWING**

 tolerance: ±0.5  
 units: mm


**PART NUMBER:** CPE-750P

**DESCRIPTION:** panel mount piezo indicators

**MEASUREMENT METHOD**


S.P.L. Measuring Circuit  
 Mic: RION S.P.L. meter UC30 or equivalent  
 S.G.: Hewlett Packard 33120A function generator or equivalent


**MECHANICAL CHARACTERISTICS**

| item                         | test condition  | evaluation standard  |
|------------------------------|---|--|
| solderability                | Lead terminals are immersed in rosin for 5 seconds and then immersed in solder bath of $270 \pm 5^\circ\text{C}$ for $3 \pm 1$ seconds.   | 90% min. of the lead terminals will be wet with solder (except the edge of the terminal).  |
| soldering heat resistance    | Lead terminals are immersed up to 1.5mm from buzzer's body in solder bath of $300 \pm 5^\circ\text{C}$ for $3 \pm 0.5$ seconds or $260 \pm 5^\circ\text{C}$ for $10 \pm 1$ seconds. | No interference in operation.  |
| terminal mechanical strength | For 10 seconds, the force of 9.8N (1.0kg) is applied to each terminal in axial direction.   | No damage or cutting off.  |
| vibration                    | The buzzer shall be measured after applying a vibration amplitude of 1.5 mm with 10 to 55 Hz band of vibration frequency to each of the 3 perpendicular directions for 2 hours.     | The value of oscillation frequency/current consumption should be $\pm 10\%$ of the initial measurements. The SPL should be within $\pm 10\text{dB}$ compared with the initial measurement. |
| drop test                    | The part will be dropped from a height of 75 cm onto a 40 mm thick wooden board 3 times in 3 axes (X, Y, Z) for a total of 9 drops.   |  |

**PART NUMBER:** CPE-750P

**DESCRIPTION:** panel mount piezo indicators

**ENVIRONMENT TEST**

| item             | test condition   | evaluation standard   |
|------------------|--|---|
| high temp. test  | After being placed in a chamber at +95°C for 240 hours.  | The buzzer will be measured after being placed at +25°C for 4 hours. The value of the oscillation frequency/current consumption should be $\pm 10\%$ compared to the initial measurements. The SPL should be within $\pm 10\text{dB}$ compared to the initial measurements. |
| low temp. test   | After being placed in a chamber at -40°C for 240 hours.  |   |
| humidity test    | After being placed in a chamber at +40°C and 90 $\pm$ 5% relative humidity for 240 hours.  |   |
| temp. cycle test | The part shall be subjected to 5 cycles. One cycle will consist of:<br><br> |   |

**RELIABILITY TEST**



| item                  | test condition   | evaluation standard   |
|-----------------------|--|---|
| operating (life test) | 1. Continuous life test:<br>The part will be subjected to 48 hours of continuous operation at +70°C with rated voltage applied.<br><br>2. Intermittent life test:<br>A duty cycle of 1 minute on, 1 minutes off, a minimum of 5,000 times at room temp (+25 $\pm$ 2°C) with rated voltage applied. | The buzzer will be measured after being placed at +25°C for 4 hours. The value of the oscillation frequency/current consumption should be $\pm 10\%$ compared to the initial measurements. The SPL should be within $\pm 10\text{dB}$ compared to the initial measurements. |

**TEST CONDITIONS**

|                          |                               |                       |                            |
|--------------------------|-------------------------------|-----------------------|----------------------------|
| standard test condition  | a) temperature: +5 ~ +35°C    | b) humidity: 45 - 85% | c) pressure: 860-1060 mbar |
| judgement test condition | a) temperature: +25 $\pm$ 2°C | b) humidity: 60 - 70% | c) pressure: 860-1060 mbar |

**PART NUMBER:** CPE-750P

**DESCRIPTION:** panel mount piezo indicators

**PACKAGING**


|            |                   |                 |
|------------|-------------------|-----------------|
| Out Box    | 310mmx248mmx49mm  | 1x50PCS=50PCS   |
| Carton Box | 550mmx330mmx290mm | 50PCSx10=500PCS |