



NOTE:
 A. 020173MR004 G 04ZU(2573A-04 G -D)
 1. Selective plating
 'G1,-05u" Min. gold in contact area.
 'G2,-Gold flash in contact area.
 'G3,-10u" Min. gold in contact area.
 'G4-15u" Min. gold in contact area.
 *'G5-30u" Min. gold in contact area.
 *'G6-50u" Min. gold in contact area.
 * 符合 USB 協會認證

NO.	DESCRIPTION	MATERIAL	COLOR	REMARK
4				
3	Shell	Brass	—	Nickel Plated
2	Terminal	Pho.Bronze	—	Gold Plated
1	Plastic	LCP	Black	UL 94V-0

SUYIN CONNECTOR

CUSTOMER COPY TITLE: USB Conn. R/A DIP Female Type (Reverse Type)

ECN (DCN) NO.	REV	DATE	DESCRIPTION	CHANGE	APPRO.	GENERAL TOLERANCE UNLESS OTHERWISE NOTED	APPRO.	宋權哲	02/01/21	
	B		B1:修正PIN位; B2,B3: 增加系列表, 變更料號, 重標重點尺寸			Angle ±2°		DRAW	鄭家奇	02/01/21
EC1T-020328-12	A	02/03/28	A1:業務用成品圖補上凹槽線條	廖宏昌	宋權哲	30 ~ ±0.50		DESIGN	鄭家奇	02/01/21
	O	02/01/21	NEW	鄭家奇	宋權哲	10 ~ 30 ±0.30		CHECK	宋權哲	02/01/21
						~ 10 ±0.15		APPRO.	宋權哲	02/01/21

PART NO.	020173MR004GX04ZU
PART NO. (OLD)	2573A-04GX-D
DRAWING NO. ^D / _{ING}	020173MR004GX04ZU
SCALE	4:1
UNIT	mm
A4	