


5 JVR VARISTOR

Part Number	Maximum Allowable Voltage		Varistor Voltage V@0.1mA		Maximum Clamping Voltage V@ 5A (V)	Withstanding Surge Current		Rated Wattage (W)	Energy 10/1000 s (J)	UL	CSA	VDE
	ACrms (V)	DC (V)	(V)	Tolerance Range		1Time (A)	2 Times (A)					
JVR05S180M65□△△	11	14	18	+ 20%	• 40	250	125	0.01	0.7	✓		✓
JVR05S220L 65□△△	14	18	22	± 15%	• 48	250	125	0.01	0.8	✓		✓
JVR05S270K65□△△	17	22	27	+10%	• 60				1.1	✓	✓	
JVR05S330K65□△△	20	26	33		• 73				1.3	✓	✓	
JVR05S390K65□△△	25	31	39		• 86				1.5	✓	✓	
JVR05S470K65□△△	30	38	47		• 104				1.8	✓	✓	
JVR05S560K65□△△	35	45	56		• 123				2.2	✓	✓	
JVR05S680K65□△△	40	56	68		• 150				2.6	✓	✓	
JVR05S820K65□△△	50	65	82		145	3.5	✓	✓				
JVR05S101K65□△△	60	85	100	175	4.5	✓	✓					
JVR05S121K65□△△	75	100	120	210	5.5	✓	✓					
JVR05S151K65□△△	95	125	150	260	6.5	✓	✓					
JVR05S181K65□△△	115	150	180	320	8.0	✓	✓					
JVR05S201K65□△△	130	170	200	355	8.5	✓	✓					
JVR05S221K65□△△	140	180	220	380	9.0	✓	✓					
JVR05S241K65□△△	150	200	240	415	10.5	✓	✓					
JVR05S271K65□△△	175	225	270	475	11.0	✓	✓					
JVR05S301K65□△△	195	250	300	525	12.0	✓	✓					
JVR05S331K65□△△	210	275	330	575	13.0	✓	✓					
JVR05S361K65□△△	230	300	360	620	16.0	✓	✓					
JVR05S391K65□△△	250	320	390	675	17.0	✓	✓					
JVR05S431K65□△△	275	350	430	745	20.0	✓	✓					
JVR05S471K65□△△	300	385	470	810	21.0	✓	✓					
JVR05S511K65□△△	320	418	510	880	22.0	✓	✓					
JVR05S561K65□△△	350	460	560	940	25.0	✓	✓					
JVR05S621K65□△△	385	505	620	1050	27.0	✓	✓					
JVR05S681K65□△△	420	560	680	1150	28.0	✓	✓					
JVR05S751K65□△△	460	615	750	1290	29.0	✓	✓					

1) The clamping voltage from 180M to 680K are tested with current 1A.
For application required ratings not shown, contact RFE application engineering.

- : Lead Style
 - Y: vertical kink (standard)
 - P: straight leads
- △△ : Lead Length / Packing Method



PULSE RATING CURVES

