# ARK-6620-6M015 Compact Intel® Core™ 2 Duo Mini-ITX System with Front Accessible I/0



#### **Features**

- Intel® 945GM Platform
  - Supports Intel® Core™ 2 Duo processor up to 2.16 GHz
  - Supports DDR2 SDRAM up to 2 GB
- Compact & Innovative New Design
  - Front accessible I/O and supports additional interface with extra cutouts
  - Ruggedized handle for easy maintenance and enhanced mobility
  - Shock-resistent 3.5" drive bay
  - Easy-to-maintain system fan and reusable filter design
  - Power cord hook to keep PSU power cord in place

# $\begin{picture}(100,0) \put(0,0){\line(1,0){100}} \put(0,0){\line(1,0){1$







#### **Specifications**

| Form Factor              |                          | Wallmount  |                                 |
|--------------------------|--------------------------|--|---------------------------------|
| Computing System         | Chipset                  | Intel 945GM + ICH7M                                |                                 |
|                          | CPU                      | Supports Intel Core 2 Duo processor up to 2.16 GHz |                                 |
|                          | Front Side Bus           | 533/667 MHz  |                                 |
|                          | L2 Cache                 | 2 / 4 MB   |                                 |
|                          | Memory                   | DDR2 533/667 MHz SDRAM up to 2 GB                  |                                 |
| Graphics                 | Controller               | Intel 945GM Integrated                             |                                 |
|                          | VRAM                     | Dynamically shared system memory up to 224 MB      |                                 |
| Storage                  | Optical Drive (support)  | -  |                                 |
|                          | Floppy Disk (support)    | -  |                                 |
|                          | HDD (support)            | SATA   |                                 |
| Drive Bay                | 5.25" (front-accessible) |  |                                 |
|                          | 3.5" (internal)          | 1  |                                 |
| Ethernet                 | Interface                | 10/100/1000Base-T Gigabit Ethernet                 |                                 |
|                          | Controller               | Intel 82573L x 2                                   |                                 |
|                          | USB                      | 2  |                                 |
|                          | PS/2                     | 2  |                                 |
|                          | COM                      | 1 + 2 (available thru extra cutouts)               |                                 |
| Front I/O Ports          | Parallel                 | 1  |                                 |
|                          | RJ-45                    | 2  |                                 |
|                          | Audio                    | 3 (Mic-in, Line-in, Line-out)                      |                                 |
|                          | VGA                      | 1  |                                 |
|                          | Reserved Cutouts         | 1 x DVI/LVDS, 1 x S/C-Video, 1 x WLAN Antenna      |                                 |
| Operating System         |                          | Microsoft Windows XP                               |                                 |
| Watchdog Timer           | Output                   | Interrupt, System Reset                            |                                 |
|                          | Interval                 | Programmable 1 ~ 255 sec                           |                                 |
| Power Supply             | Power Output Wattage     | 180 W  |                                 |
|                          | Туре                     | AC 100 ~ 240 V                                     |                                 |
| Cooling                  | Chassis Fan              | 2 (27.72 CFM each)                                 |                                 |
|                          | Air Filter               | Yes  |                                 |
| Miscellaneous            | Overheating Protection   | System shut-down when over-heated                  |                                 |
|                          | LED Indicators           | Power, HDD, Temperature                            |                                 |
|                          | Control                  | Power On/Off switch                                |                                 |
| Environment              |                          | Operating  | Non-Operating                   |
|                          | Temperature              | 0 ~ 40° C (32 ~ 104° F)                            | -20 ~ 60° C (-4 ~ 140° F)       |
|                          | Humidity                 | 10 ~ 85% @ 40° C non-condensing                    | 10 ~ 95% @ 40° C non-condensing |
| Physical Characteristics | Dimensions (W x H x D)   | 272 x 88 x 232 mm (10.7" x 3.5" x 9.1")            |                                 |
|                          | Weight                   | 3.5 kg (7.7 lb)                                    |                                 |

#### ARK-6620-6M01S





#### **Ordering Information**

Please visit Advantech CTOS portal for order entry. http://www.advantech.com/ctos

# **System Content**

| Item        | Part Number     |
|-------------|-----------------|
| Chassis     | ARK-6620-18ZE   |
| Motherboard | AIMB-253L-00A1E |

### **Power Cord Options**

| Part Number | Descriptions                    |
|-------------|---------------------------------|
| 1702002600  | Power cord 125V/10A 1.8m, USA   |
| 1702002605  | Power cord 250V/6A 1.8m, Europe |
| 1702031801  | Power cord 250V/5A 1.8m, UK     |
| 1702002605  | Power cord 125V/12A 1.8m, Japan |



