


Part Number	Maximum Allowable Voltage		Varistor Voltage V@0.1mA		Maximum Clamping Voltage V@ 5A	Withstanding Surge Current		Rated Wattage (W)	Energy 10/1000 s (J)	UL	CSA	VDE
	ACrms (V)	DC (V)	(V)	Tolerance Range		1Time (A)	2 Times (A)					
JVR20N180M11□△△	11	14	18	+ 20%	•36	2000	1000	0.2	7.0	✓		✓
JVR20N220L 11□△△	14	18	22	+ 15%	•43				8.0	✓		✓
JVR20N270K11□△△	17	22	27		•53				10.0	✓		✓
JVR20N330K11□△△	20	26	33		•65				12.0	✓		✓
JVR20N390K11□△△	25	31	39		•77				14.0	✓		✓
JVR20N470K11□△△	30	38	47		•93				17.0	✓		✓
JVR20N560K11□△△	35	45	56		•110				20.0	✓		✓
JVR20N680K11□△△	40	56	68		•135				24.0	✓		✓
JVR20N820K11□△△	50	65	82		135				44.0	✓		✓
JVR20N101K11□△△	60	85	100		165				56.0	✓		✓
JVR20N121K11□△△	75	100	120		200	64.0	✓		✓			
JVR20N151K11□△△	95	125	150		250	88.0	✓		✓			
JVR20N181K11□△△	115	150	180		300	104.0	✓		✓			
JVR20N201K11□△△	130	170	200	+10%	340	114.0	✓	✓	✓			
JVR20N221K11□△△	140	180	220		360	124.0	✓	✓	✓			
JVR20N241K11□△△	150	200	240		395	134.0	✓	✓	✓			
JVR20N271K11□△△	175	225	270		455	158.0	✓	✓	✓			
JVR20N301K11□△△	195	250	300		505	168.0	✓	✓	✓			
JVR20N331K11□△△	210	275	330		550	184.0	✓	✓	✓			
JVR20N361K11□△△	230	300	360		595	208.0	✓	✓	✓			
JVR20N391K11□△△	250	320	390		650	240.0	✓	✓	✓			
JVR20N431K11□△△	275	350	430		710	264.0	✓	✓	✓			
JVR20N471K11□△△	300	385	470		775	280.0	✓	✓	✓			
JVR20N511K11□△△	320	418	510	842	296.0	✓	✓	✓				
JVR20N561K11□△△	350	460	560	920	312.0	✓	✓	✓				
JVR20N621K11□△△	385	505	620	1025	328.0	✓	✓	✓				
JVR20N681K11□△△	420	560	680	1120	344.0	✓	✓	✓				
JVR20N751K11□△△	460	615	750	1240	360.0	✓	✓	✓				
JVR20N781K11□△△	485	640	780	1290	368.0	✓	✓	✓				
JVR20N821K11□△△	510	670	820	1355	376.0	✓	✓	✓				
JVR20N911K11□△△	550	745	910	1500	408.0	✓	✓	✓				
JVR20N102K11□△△	625	825	1000	1650	448.0	✓	✓	✓				
JVR20N112K11□△△	680	895	1100	1815	496.0	✓	✓	✓				
JVR20N182K11□△△	1000	1465	1800	2970	695.0							

1) The clamping voltage from 180M to 680K are tested with current 20A.
For application required ratings not shown, contact RFE application engineering.

- : Lead Style
Y: vertical kink (standard)
P: straight leads
- △△ : Lead Length / Packing Method



PULSE RATING CURVES

