



# Single Junction Drop-In Isolator

800MHz, 900MHz, 1800MHz, 1900MHz, 2100MHz


## Features

- 20dB Isolation
- 0.35dB Insertion Loss
- Low cost package
- Custom products available with alternative configurations such as couplers, attenuators, high power termination and reverse circulation.

## Description

M/A COM's drop-in circulators and isolators, designed for Wireless base station and power amplifier applications, feature high reliability performance at a low cost. These designs feature a low cost package ideally suited for high volume manufacturing. M/A Com is one of the largest suppliers of isolator and circulators in the world.

## Outline Drawing



## Electrical Specifications: $Z_0 = 50\Omega$

Parameter	-30°C to +85°C
Isolation	20dB minimum
Insertion Loss	0.35dB maximum
VSWR, all ports	1.22:1
Circulation	Clockwise

## Absolute Maximum Ratings <sup>1</sup>

Parameter	Absolute Maximum
Forward Power	250 Watts
Reflected Power	20 Watts
Operating Temperature	-30°C to +85°C
Storage Temperature	-45°C to +100°C

1. Operation of this device above any one of these parameters

## Ordering Information

Part Number	Frequency Range (MHz)
FR12-0001	869—894
FR12-0002	925—960
FR12-0003	1805—1880
FR12-0004	1930—1990
FR12-0009	2110—2170