


CHARACTERISTICS

Temperature Rise	40°C max at rated current
Storage Temperature	-25°C to +85°C
Operating Temperature	-20°C to +80°C
Pin Strength	1.0KG min

PIN OUT DIAGRAM



Part Number	L (mH) min.	RDC (W) max	Rated Current (Aac)
UU0913H-501Y	0.5	0.2	1.4
UU0913H-102Y	1	0.4	1
UU0913H-202Y	2	0.8	0.7
UU0913H-502Y	5	1.6	0.5
UU0913H-802Y	8	2.5	0.4
UU0913H-103Y	10	3.6	0.3
UU0917V-501Y	0.5	0.2	1.4
UU0917V-102Y	1	0.4	1
UU0917V-202Y	2	0.8	0.7
UU0917V-502Y	5	1.6	0.5
UU0917V-802Y	8	2.5	0.4
UU0917V-103Y	10	3.6	0.3
UU1022V-102Y	1	0.2	1.6
UU1022V-202Y	2	0.4	1.0
UU1022V-302Y	3	0.5	0.8
UU1022V-502Y	5	1.0	0.7
UU1022V-802Y	8	1.7	0.5
UU1022V-103Y	10	2.5	0.4
UU1020V-801Y	0.8	0.2	1.6
UU1020V-162Y	1.6	0.4	1.0
UU1020V-252Y	2.5	0.5	0.8
UU1020V-402Y	4.0	1.0	0.7
UU1020V-502Y	5.0	1.5	0.5
UU1020V-802Y	8.0	2.4	0.4
UU1527V-152Y	1.5	0.15	1.8
UU1527V-252Y	2.5	0.20	1.6
UU1527V-402Y	4.0	0.30	1.2
UU1527V-602Y	6.0	0.50	0.8
UU1527V-103Y	10.0	1.00	0.7
UU1527V-203Y	20.0	2.00	0.5
UU1527V4-152Y	1.5	0.15	1.8
UU1527V4-252Y	2.5	0.20	1.6
UU1527V4-402Y	4.0	0.30	1.2
UU1527V4-602Y	6.0	0.50	0.8
UU1527V4-103Y	10.0	1.00	0.7
UU1527V4-203Y	20.0	2.00	0.5

