1801 Morgan Street Rockford, Illinois 61102 800-435-2931 www.molexkits.com



Datasheet for 76650-0046

General Information

Part Number: 76650-0046

Manufacturer: Molex / Waldom

Title: Solderless Terminal Kit

.187" Tab Size Nylon Insulated and Fully Insulated Quick Disconnect Solderless

Description: Terminals

Product Family: Quick Disconnects

Certificates: (Molex Parts within this kit) - EU RoHS Compliant, UL and CSA

Country of Origin: Kit assembled in U.S.A.

Specifications

Design

Configuration: Wire-to-Wire / Solderless Terminals

Tab Size: .187"

Connector Type: Male and Female

Insulation: Nylon

Current Rating: (3-15) Amps - Dependant on Wire Gauge

Voltage: 300 Volts

Wire size: (22-18) and (16-14) AWG

Product Highlights

Quick disconnects allow for quickly connecting or disconnecting a terminal. The front end of the terminal has a female-type receptacle which allows the terminal to slide onto and off of a male blade.

Features and Benefits

- Color-coded insulator allows easy identification of terminal size and wire gauge.
- A wire stop stamped into the crimp barrel prevents insertion of over-stripped wires.
- Terminal's funnel entrance is designed for increased crimping rates by speeding wire delivery into the crimp section and eliminating wire strand fold back.

Applications

- MRO (Maintenance Repair and Operations)
- Consumer applications
- Power applications
- Motor applications



Datasheet for 76650-0046

Bill of Materials for Part No. 76650-0046

| Country | Co | untry | |
|---------|----|-------|--|
|---------|----|-------|--|

| | oou | | |
|----------------|-----------|---|-----------------|
| Molex Part No. | of Origin | Description | Quantity in Kit |
| | | | |
| 19002-0005 | USA | Fully Insulated .187" Female Quick Disconnects, 22-18 AWG | 5 |
| | | | |
| 19002-0028 | USA | Fully Insulated .187" Female Quick Disconnects, 16-14 AWG | 5 |
| | | | |
| 19019-0006 | USA | Insulated .187" Female Quick Disconnects, 22-18 AWG | 20 |
| | | | |
| 19019-0027 | USA | Insulated .187" Female Quick Disconnects, 16-14 AWG | 20 |
| | | | |
| 19025-0002 | USA | Insulated .187" Male Quick Disconnects, 22-18 AWG | 25 |
| | | | |
| 19025-0008 | USA | Insulated .187" Male Quick Disconnects, 16-14 AWG | 25 |

Recommended Molex Tool(s) for Part No. 76650-0046*

Country

| Molex Part No. | of Origin | Description |
|----------------|-----------|----------------------------|
| 64001-0100 * | USA | Hand Crimp Tool (RHT-1990) |
| 64001-0200 * | USA | Hand Crimp Tool (RHT-1991) |
| 64001-0800 * | USA | Hand Crimp Tool (RHT-5760) |
| 64001-1100 * | USA | Hand Crimp Tool (RHT-5762) |
| 64001-1400 * | USA | Hand Crimp Tool (RHT-2100) |
| 64001-1700 * | USA | Hand Crimp Tool (RHT-5757) |
| 64001-2000 * | USA | Hand Crimp Tool (RHT-5758) |

^{*}Tool(s) not included in kit. Tool(s) ordered separately.