



Notes:

- any open miswiring & short & intermittent are not permitted
- cirris 1000H+or equivalent cable tester using following parameters: 300V DC 1mS,10Mohm min & 2.0ohm max.
- CPK Measure point Y1-Y4.

6	EZPVC50PR9011ZH	PVC MOLDING 50P COLOR:BLACK,需符合EN71 & EN1122 & EPA3050B.	G	25
5	EZPE5321	PE 5321 CLEAR 需符合EN71 & EN1122 & EPA3050B.	G	7
4	EF120220045F5B	F5B RH 12*20*4.5cm 需符合EN71 & EN1122 & EPA3050B.	EA	1
3	ECMSB05M0025	MINI USB B TYPE 5P MALE G/F,INSULATOR COLOR:BLACK 需符合EN71 & EN1122 & EPA3050B.	EA	1
2	ECUSB04M0005	USB A TYPE 4Pin MALE,G/F,SHELL:NI.PLATED INSULATOR COLOR:BLACK 需符合EN71 & EN1122 & EPA3050B.	EA	1
1	EK2804BK350096	CABLE UL2725 28AWG*1P+28AWG*2C+AEB PVC JACKET COLOR FOR BLACK OD=3.5±0.15mm. 需符合EN71 & EN1122 & EPA3050B.	MM	1500
NO	PART NO	DESCRIPTION	U'T	Q'TY
MATERIAL SPECIFICATION				

2	USB	BLACK	
1	CABLE	PVC	BLACK UL2725#28
NO.	DESCRIPTION	MATERIAL	COLOR
			REMARK

<b>SUYIN</b> CONNECTOR				
CUSTOMER COPY	TITLE: USB A+CORE+MINI USB 3PIN CABLE			
PART NO.	CBL30094-1500			
PART NO.(OLD)				
DRAWING NO.	D	CBL30094-1500		
SCALE	2:1	UNIT	mm	A4

				Angle	±2°	DRAW	
				30 ~	±0.50	DESIGN	
				10 ~ 30	±0.30	CHECK	
	0		NEW	~ 10	±0.15	APPRO.	
ECN(DCN) NO.	REV	DATE	DESCRIPTION	CHANGE	APPRO.	GENERAL TOLERANCE UNLESS OTHERWISE NOTED	