# SYS-2U2010-2A01 20 Intel® Pentium® 4 System with 3 PCI slots



### **Specifications**


#### **Features**

- Intel 945G Platform
  - Supports Intel® Pentium® 4 up to 3.8 GHz
  - Supports DDR2 SDRAM up to 4 GB (dual channels)
  - One integrated gigabit Ethernet delivers excellent network performance
- Expandability for today and the future
  - Supports three PCI slots
  - Provides great scalability for 3.5" and 5.25" drive bays

| Form Factor              |                          | 2U   |  |
|--------------------------|--------------------------|--|--|
| Computing System         | Chipset                  | Intel 945G + ICH7R   |  |
|                          | CPU*                     | Supports Intel Pentium 4 processor up to 3.8 GHz (LGA775)                              |  |
|                          | Front Side Bus           | 533/800 MHz  |  |
|                          | L2 Cache                 | 2 MB   |  |
|                          | Memory*                  | Supports up to 4 GB DDR2 533/667 SDRAM (dual channels)                                 |  |
| Graphics                 | Controller               | Intel 945G Integrated  |  |
|                          | VRAM                     | Dynamically shared system memory up to 224 MB  |  |
| Expansion Slot           | ISA                      | None   |  |
|                          | PCI                      | 3 × 32-bit   |  |
| Storage                  | Optical Drive*           | Supports CD-ROM/ DVD-ROM/ CD-RW  |  |
|                          | Floppy Disk              | Supports 3.5" 1.44 MB FDD  |  |
|                          | HDD*                     | Supports SATA HDD  |  |
| Drive Bay                | 5.25" (front-accessible) | 1  |  |
|                          | 3.5" (front-accessible)  | 1  |  |
|                          | 3.5" (mobile rack)       | 1  |  |
| Ethernet                 | Interface                | 10/100/1000Base-T Gigabit Ethernet   |  |
|                          | Controller               | Intel 82573V   |  |
| I/O Port                 | Front I/O Ports          | 2 x USB  |  |
|                          | Rear I/O Ports           | 4 x USB, 2 x PS/2, 1 x COM, 1 x VGA, 1 x Parallel, 1 x RJ-45, 1 x Line-Out, 1 x Mic-In |  |
| )perating System*        |                          | Microsoft <sup>®</sup> Windows <sup>®</sup> XP/2000/2003                               |  |
| Vatab da a Timar         | Output                   | System reset   |  |
| Watchdog Timer           | Interval                 | Programmable 1 ~ 255 sec   |  |
| Power Supply             | Power Output Wattage     | 300 W  |  |
|                          | Туре                     | Single ATX/PFC Auto-Switching power supply   |  |
| Cooling                  | Chassis Fan              | 2  |  |
|                          | Air Filter               | Yes  |  |
| Environment              |                          | Operating  | Non-Operating                                  |
|                          | Temperature              | 0 ~ 40° C (32 ~ 104° F)  | -20 ~ 60° C (-4 ~ 140° F)                      |
|                          | Humidity                 | 10 ~ 85% @ 40° C non-condensing  | $10 \sim 95\%$ @ $40^{\circ}$ C non-condensing |
| Physical Characteristics | Color                    | Black  |  |
|                          | Dimensions (W x H x D)   | 482 x 88 x 480 mm (19" x 3.46" x 18.9")  |  |
|                          | Weight                   | 15 kg (33 lb)  |  |

\* Configurations are variable upon regions. Please contact Advantech sales for more details.

#### SYS-2U2010-2A01




#### **Ordering Information**

Please visit Advantech CTOS portal for order entry. http://www.advantech.com/ctos

#### **System Content**

| ltem        | Part Number      |
|-------------|------------------|
| Chassis     | ACP-2010MB0-30ZE |
| Motherboard | AIMB-762VG-00A1E |
| Riser card  | AIMB-R430P-03A1E |

#### **Front View**



## **Rear View**



Rear view of ACP-2010MB