

## Datasheet for 76650-0001

### General Information

<b>Part Number:</b>	76650-0001
<b>Manufacturer:</b>	Molex / Waldom
<b>Title:</b>	HCS-125 Power Connector Kit
<b>Description:</b>	Single Row Plug and Receptacle with Universal Crimp Tool
<b>Product Family:</b>	HCS-125
<b>Certificates:</b>	(Molex Parts within this kit) - EU RoHS Compliant, UL and CSA
<b>Country of Origin:</b>	Kit assembled in U.S.A.

### Specifications

<b>Design</b>	
<b>Configuration:</b>	Wire-to-Wire
<b>Pitch:</b>	8.38mm (.330")
<b>Connector Type:</b>	Plugs and Receptacles
<b>Circuit Sizes:</b>	1, 2, 3 and 4
<b>Current Rating:</b>	(12 and 20) Amps - Dependent on Wire Gauge
<b>Voltage:</b>	600 Volts
<b>Wire size:</b>	(18-16) and (14-10) AWG

### Product Highlights

HCS-125 is a high current, economical power pin and socket wire-to-wire power connector. Capable of carrying up to 20 amperes per circuit in a wire-to-wire configuration. These connectors are Dual gender housings, can take either pins or sockets.

#### Features and Benefits

- The HCS-125 is an enhanced version of the Molex proven .125" system and meets the need for a connector system rated at greater than the industry standard 12.0A per circuit
- Positive locks prevent accidental unmating
- Fully isolated terminals protect terminals
- Pull tabs

#### Applications

- Residential or commercial appliances
- HVAC equipment
- Computer servers
- Networking equipment
- Office equipment
- Fitness equipment
- Medical equipment
- Retail Security Scanning Systems

**Datasheet for 76650-0001**

**Bill of Materials for Part No. 76650-0001**

<b>Molex Part No.</b>	<b>Country of Origin</b>	<b>Description</b>	<b>Quantity in Kit</b>
03-12-1016	USA	8.38mm (.330") Pitch HCS-125 Receptacle 1 Circuit	10
03-12-1026	USA	8.38mm (.330") Pitch HCS-125 Receptacle 2 Circuit	5
03-12-1036	USA	8.38mm (.330") Pitch HCS-125 Receptacle 3 Circuit	5
03-12-1046	USA	8.38mm (.330") Pitch HCS-125 Receptacle 4 Circuit	5
03-12-2016	USA	8.38mm (.330") Pitch HCS-125 Free Hanging Plug 1 Circuit	10
03-12-2026	USA	8.38mm (.330") Pitch HCS-125 Free Hanging Plug 2 Circuit	5
03-12-2035	USA	8.38mm (.330") Pitch HCS-125 Panel Mount Plug 3 Circuit	5
03-12-2045	USA	8.38mm (.330") Pitch HCS-125 Panel Mount Plug 4 Circuit	5
18-12-1222	USA	3.18mm (.125") Diameter Female Crimp Terminals, 18-16 AWG	25
18-12-1602	USA	3.18mm (.125") Diameter Female Crimp Terminals, 14-10 AWG	25
18-12-2222	USA	3.18mm (.125") Diameter Male Crimp Terminals, 18-16 AWG	25
18-12-2602	USA	3.18mm (.125") Diameter Male Crimp Terminals, 14-10 AWG	25
CT-4071-1R^	TAIWAN	Universal Crimping, Bolt Cutter, Wire Stripping Tool	1

^ = Tool Provided by Waldom

**Recommended Molex Tool(s) for Part No. 76650-0001\***

<b>Molex Part No.</b>	<b>Country of Origin</b>	<b>Description</b>
11-03-0008 *	USA	Extraction Tool (HT-2066-A)
63811-1100 *	Germany	Hand Crimper (14-10)
63819-1100 *	Sweden	Hand Crimper (18-16)

\*Tool(s) not included in kit. Tool(s) ordered separately.