

FEATURES


- The three-layer, two-terminal, axial-lead, hermetically sealed diacs are designed specifically for triggering thyristors. They demonstrate low breakover current at breakover voltage as they withstand peak pulse current. The breakover symmetry is within three volts(DB3,DC34,DB4) or four volts(DB6). These diacs are intended for use in thyristor phase control, circuits for lamp dimming, universal motor speed control and heat control.
- JF's DB3/DC34/DB4/DB6 are bi-directional triggered diode designed to operate in conjunction with Triacs and SCR's
- High temperature soldering guaranteed: 260°C/10 seconds at terminals
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC

MECHANICAL DATA

- Case: DO-35 glass case
- Weight: Approx. 0.13 gram



DO-35(GLASS)



Dimensions in inches and (millimeters)

ABSOLUTE RATINGS(LIMITING VALUES)

Symbols	Parameters	Value				Units
		DB3	DC34	DB4	DB6	
P _c	Power Dissipation on Printed Circuit(L=10mm)	T _A =50°C		150		mW
I _{TRM}	Repetitive Peak on-state Current	t _p =10μs f=100Hz	2.0	2.0	2.0	1.6
T _{STG/TJ}	Storage and Operating Junction Temperature	-40 to +125/-40 to +110				°C

ELECTRICAL CHARACTERISTICS

Symbols	Parameters	Test Condition	Value				Units	
			DB3	DC34	DB4	DB6		
V _{B0}	Breakover Voltage (Note 2)	C=22nF(Note 2) See diagram 1	Min	28	30	35	56	V
			Typ	32	34	40	60	
			Max	36	38	45	70	
+V _{B0} - -V _{B0}	Breakover Voltage Symmetry	C=22nF(Note 2) See diagram 1	Max	±3			±4	V
±ΔV	Dynamic Breakover Voltage (Note1)	ΔI=(I _{BO} to I _F =10mA) See Diagram 1	Min	5			10	V
V _O	Output Voltage (Note 1)	See Diagram 2	Min	5				V
I _{BO}	Breakover Current (Note1)	C=22nF(Note 2)	Max	100				μA
tr	Rise Time (Note1)	See Diagram 3	Typ	1.5				μs
I _B	Leakage Current (Note1)	V _B =0.5 V _{B0} max see diagram 1	Max	10				μA

Notes: 1.Electrical characteristics applicable in both forward and reverse directions.

2.Connected in parallel with the devices.

RATINGS AND CHARACTERISTIC CURVES DB3/DC34/DB4/DB6

DIAGRAM 1: Current-voltage characteristics




FIG.1-Power dissipation versus ambient temperature (maximum values)




FIG.3-Peak pulse current versus pulse duration (maximum values)




DIAGRAM 2: Test circuit for output voltage




DIAGRAM 3: Test circuit see diagram2 adjust R for $|I_P|=0.5A$




FIG.2-Relative variation of V_{BO} versus junction temperature(typical values)

