

# 4V Drive Pch MOSFET

## **RSH070P05**

#### Structure

Silicon P-channel MOSFET

#### Features

- 1) Built-in G-S Protection Diode.
- 2) Small and Surface Mount Package (SOP8).

## Application

Power switching, DC / DC converter, Inverter

## Packaging specifications

	Package	Taping		
Type	Code	TB		
	Basic ordering unit (pieces)	2500		
RSH070P08	0			

## ●Absolute maximum ratings (Ta=25°C)

Parameter	Symbol		Limits	Unit		
Drain-source voltage		$V_{DSS}$		-45	V	
Gate-source voltage		$V_{GSS}$		±20	V	
Drain current	Continuous	$I_D$		±7.0	Α	
	Pulsed	$I_{DP}$	*1	±28	Α	
Source current	Continuous	Is		-1.6	Α	
(Body diode)	Pulsed	$I_{SP}$	*1	-28	Α	
Total power dissipation		$P_D$	*2	2	W	
Chanel temperature		$T_{ch}$		150	°C	
Range of Storage temperature		$T_{stg}$		-55 to +150	°C	


<sup>\*1</sup> PW $\leq$ 10 $\mu$ s, Duty cycle $\leq$ 1%

## ●Thermal resistance


Parameter	Symbol	Limits	Unit
Chanel to ambient	R <sub>th(ch-a)</sub> *	62.5	°C/W

<sup>\*</sup> Mounted on a ceramic board

## ●Dimensions (Unit : mm)



## ●Inner circuit



<sup>\*2</sup> Mounted on a ceramic board

RSH070P05 Data Sheet

## ●Electrical characteristics (Ta=25°C)

Parameter	Symbol	Min.	Тур.	Max.	Unit	Conditions
Gate-source leakage	Igss	-	_	±10	μА	Vgs=±20V, Vps=0V
Drain-source breakdown voltage	V <sub>(BR)</sub> DSS	-45	_	_	V	I <sub>D</sub> = -1mA, V <sub>G</sub> S=0V
Zero gate voltage drain current	IDSS	_	_	-1	μΑ	V <sub>DS</sub> = -45V, V <sub>GS</sub> =0V
Gate threshold voltage	V <sub>GS (th)</sub>	-1.0	_	-2.5	V	$V_{DS}=-10V$ , $I_{D}=-1mA$
Static drain-source on-state resistance		_	19	27	mΩ	I <sub>D</sub> = -7A, V <sub>G</sub> s= -10V
	R <sub>DS (on)</sub> *	_	25	35	mΩ	I <sub>D</sub> = -7A, V <sub>G</sub> S= -4.5V
		-	28	39	mΩ	I <sub>D</sub> = -7A, V <sub>G</sub> S= -4.0V
Forward transfer admittance	Y <sub>fs</sub> *	10.0	_	_	S	V <sub>DS</sub> = -10V, I <sub>D</sub> = -7A
Input capacitance	Ciss	_	4100	_	pF	Vps= -10V
Output capacitance	Coss	_	510	_	pF	V <sub>GS</sub> =0V
Reverse transfer capacitance	Crss	_	330	-	pF	f=1MHz
Turn-on delay time	t <sub>d (on)</sub> *	-	31	_	ns	Vpp≒ –25V
Rise time	tr *	_	35	_	ns	ID= -3.5A
Turn-off delay time	t <sub>d (off)</sub> *	_	135	_	ns	Vgs= -10V RL=-7Ω
Fall time	t <sub>f</sub> *	_	50	_	ns	R <sub>G</sub> =10Ω
Total gate charge	Qg *	_	34.0	47.6	nC	V <sub>DD</sub> ≒-25V V <sub>GS</sub> =-5V
Gate-source charge	Q <sub>gs</sub> *	_	9.5	_	nC	ID= -7A
Gate-drain charge	Qgd *	_	12	_	nC	RL=3.5Ω Rg=10Ω

<sup>\*</sup>Pulsed

## ●Body diode characteristics (Source-Drain) (Ta=25°C)

Parameter	Symbol	Min.	Тур.	Max.	Unit	Conditions
Forward voltage	Vsp*	-	-	-1.2	V	I <sub>S</sub> = -7A, V <sub>GS</sub> =0V

<sup>\*</sup>Pulsed

RSH070P05 **Data Sheet** 

#### •Electrical characteristic curves





Fig.1 Typical Transfer Characteristics

Fig.2 Static Drain-Source On-State Resistance vs. Drain Current (1)

Fig.3 Static Drain-Source On-State Resistance vs. Drain Current (2)



Ta=25°C Static Drain-Source On-State 150 Resistance R<sub>DS</sub>(on) [m\O] 100 -7.0A 50 0 0 5 10 15 Gate-Source Voltage : -V<sub>GS</sub> [V]

200






Fig.4 Static Drain-Source On-State Resistance vs. Drain Current (3)

Fig.5 Static Drain-Source On-State Resistance vs. Gate-Source Voltage

Fig.6 Source-Current vs. Source-Drain Voltage





Source-Drain Voltage




Fig.8 Switching Characteristics




Fig.9 Dynamic Input Characteristics

RSH070P05 Data Sheet

## Measurement circuits




Fig.10 Switching Time Test Circuit




Fig.12 Gate Charge Test Circuit




Fig.11 Switching Time Waveforms




Fig.13 Gate Charge Waveform

#### Notes

No copying or reproduction of this document, in part or in whole, is permitted without the consent of ROHM Co.,Ltd.

The content specified herein is subject to change for improvement without notice.

The content specified herein is for the purpose of introducing ROHM's products (hereinafter "Products"). If you wish to use any such Product, please be sure to refer to the specifications, which can be obtained from ROHM upon request.

Examples of application circuits, circuit constants and any other information contained herein illustrate the standard usage and operations of the Products. The peripheral conditions must be taken into account when designing circuits for mass production.

Great care was taken in ensuring the accuracy of the information specified in this document. However, should you incur any damage arising from any inaccuracy or misprint of such information, ROHM shall bear no responsibility for such damage.

The technical information specified herein is intended only to show the typical functions of and examples of application circuits for the Products. ROHM does not grant you, explicitly or implicitly, any license to use or exercise intellectual property or other rights held by ROHM and other parties. ROHM shall bear no responsibility whatsoever for any dispute arising from the use of such technical information.

The Products specified in this document are intended to be used with general-use electronic equipment or devices (such as audio visual equipment, office-automation equipment, communication devices, electronic appliances and amusement devices).

The Products specified in this document are not designed to be radiation tolerant.

While ROHM always makes efforts to enhance the quality and reliability of its Products, a Product may fail or malfunction for a variety of reasons.

Please be sure to implement in your equipment using the Products safety measures to guard against the possibility of physical injury, fire or any other damage caused in the event of the failure of any Product, such as derating, redundancy, fire control and fail-safe designs. ROHM shall bear no responsibility whatsoever for your use of any Product outside of the prescribed scope or not in accordance with the instruction manual.

The Products are not designed or manufactured to be used with any equipment, device or system which requires an extremely high level of reliability the failure or malfunction of which may result in a direct threat to human life or create a risk of human injury (such as a medical instrument, transportation equipment, aerospace machinery, nuclear-reactor controller, fuel-controller or other safety device). ROHM shall bear no responsibility in any way for use of any of the Products for the above special purposes. If a Product is intended to be used for any such special purpose, please contact a ROHM sales representative before purchasing.

If you intend to export or ship overseas any Product or technology specified herein that may be controlled under the Foreign Exchange and the Foreign Trade Law, you will be required to obtain a license or permit under the Law.



Thank you for your accessing to ROHM product informations.

More detail product informations and catalogs are available, please contact us.

## **ROHM Customer Support System**

http://www.rohm.com/contact/