






FEATURES

- High stability, High Accuracy, and High Reliability
- Resistance Values from 1K to 200K $\pm 1\sim 5\%$
- B-Constant 25/85 from 3000 to 4500 $\pm 1\sim 3\%$

CHARACTERISTICS

SS130 	Thermometer Sensor	
	Operating Temp. Range	-40 to +100°C
	Dissipation Constant	Approx. 0.7 mW/°C (Still air)
	Response Time	Approx. 0.8 sec. (Thermal bath)
SS133 I * 	Battery Charger Sensor	
	Operating Temp. Range	-40 to +100°C
	Dissipation Constant	Approx. 1.3 mW/°C (Still air)
	Response Time	Approx. 5 sec. (Thermal bath)
SS133 II * 	Air Conditioner Sensor / Quick Temp. Response	
	Operating Temp. Range	-30 to +100°C
	Dissipation Constant	Approx. 2.3 mW/°C (Still air)
	Response Time	Approx. 8 sec. (Thermal bath)
SS133 III * 	Air Conditioner Sensor	
	Operating Temp. Range	-30 to +100°C
	Dissipation Constant	Approx. 2.5 mW/°C (Still air)
	Response Time	Approx. 12 sec. (Thermal bath)
SS17A 	Air Conditioner Sensor	
	Operating Temp. Range	-30 to +100°C
	Dissipation Constant	Approx. 2.5 mW/°C (Still air)
	Response Time	Approx. 12 sec. (Thermal bath)

- * The Roman Numeral listed above are only used to differentiate dimensions.
- * Sensor and Wire Length can be customized.
- * Connectors are optional. (*1)