

## Filter Inductors High Current



### ELECTRICAL SPECIFICATIONS

**Inductance:** Measured at 1.0 V with zero DC current

**Incremental Current:** The typical current at which the inductance will be decreased by 5 % from its initial zero DC value

**Operating Temperature:** - 55 °C to + 125 °C (no load)  
- 55 °C to + 75 °C (at full rated current)

STANDARD ELECTRICAL SPECIFICATIONS					
MODEL	IND. at 1 kHz (μH)	TOL.	DCR MAX. (Ohms)	RATED CURRENT (Max. Amps)	INCREMENTAL CURRENT (Amps)
IH-3	5	± 10 %	0.015	10.0	25
IH-3	10	± 10 %	0.018	9.0	19
IH-3	27	± 10 %	0.035	7.0	12
IH-3	50	± 10 %	0.050	5.6	8
IH-3	100	± 10 %	0.065	5.2	6
IH-3	150	± 10 %	0.075	5.0	5
IH-3	250	± 10 %	0.090	5.0	4
IH-5	5	± 10 %	0.012	14.0	25
IH-5	10	± 10 %	0.015	12.0	19
IH-5	27	± 10 %	0.025	9.0	13
IH-5	50	± 10 %	0.030	8.0	10
IH-5	68	± 10 %	0.035	7.5	9
IH-5	100	± 10 %	0.050	7.5	7
IH-5	150	± 10 %	0.060	7.0	5
IH-10	5	± 10 %	0.010	19.0	25
IH-10	10	± 10 %	0.012	16.0	19
IH-10	27	± 10 %	0.018	12.5	12
IH-10	50	± 10 %	0.025	11.0	10
IH-10	68	± 10 %	0.027	10.0	8
IH-10	100	± 10 %	0.030	10.0	7
IH-15	5	± 10 %	0.008	24.0	25
IH-15	10	± 10 %	0.010	20.0	19
IH-15	27	± 10 %	0.015	16.0	14
IH-15	50	± 10 %	0.020	15.0	10

### MARKING

- Vishay Dale
- Model
- Inductance value
- Date code

### ORDERING INFORMATION

MODEL	INDUCTANCE VALUE	INDUCTANCE TOLERANCE	PACKAGE CODE	JEDEC LEAD (Pb)-FREE STANDARD
IH-5	10 μH	± 10 %	EB	e2

### GLOBAL PART NUMBER INFORMATION

I	H	0	5	E	B	1	0	0	K
MODEL				PACKING CODE		INDUCTANCE VALUE			TOL.

### FEATURES

- Printed circuit mounting
- Pre-tinned leads
- Protected by polyolefin tubing - flame retardant UL type VW-1 per MIL-I-23053/5, Class 3 requirements



**RoHS**  
COMPLIANT

### APPLICATIONS

Noise filtering for switching regulators, power amplifiers, power supplies and SCR and Triac control circuits

Current Rating: Maximum continuous operating current (DC or RMS) based on a 50 °C temperature rise

### MECHANICAL SPECIFICATIONS


**Wire:** Solid soft copper

**Terminals:** Extensions of the winding

**Core Material:** Ferrite

**Coating:** Polyolefin tubing

### DIMENSIONS in inches [millimeters]



MODEL	IND. (μH)	A (Max.)	B (Max.)	C ± 0.062 [1.57]	D ± 0.005 [0.127]
IH-3	5	0.875 [22.23]	0.600 [15.24]	0.500 [12.70]	0.042 [1.067]
IH-3	10	1.125 [28.58]	0.625 [15.88]	0.687 [17.45]	0.042 [1.067]
IH-3	27	0.875 [22.23]	0.800 [20.32]	0.437 [11.10]	0.042 [1.067]
IH-3	50	0.875 [22.23]	0.800 [20.32]	0.750 [19.05]	0.042 [1.067]
IH-3	100	1.125 [28.58]	0.800 [20.32]	0.937 [23.80]	0.042 [1.067]
IH-3	150	1.375 [34.93]	0.800 [20.32]	1.062 [26.97]	0.042 [1.067]
IH-3	250	1.625 [41.28]	0.800 [20.32]	1.312 [33.32]	0.042 [1.067]
IH-5	5	0.875 [22.23]	0.625 [15.88]	0.750 [19.05]	0.053 [1.35]
IH-5	10	1.125 [28.58]	0.625 [15.88]	1.000 [25.40]	0.053 [1.35]
IH-5	27	0.875 [22.23]	0.840 [21.34]	0.562 [14.27]	0.053 [1.35]
IH-5	50	1.125 [28.58]	0.840 [21.34]	0.750 [19.05]	0.053 [1.35]
IH-5	68	1.125 [28.58]	0.860 [21.84]	0.875 [22.23]	0.053 [1.35]
IH-5	100	1.375 [34.93]	0.860 [21.84]	1.000 [25.40]	0.053 [1.35]
IH-5	150	1.625 [41.28]	0.860 [21.84]	1.250 [31.75]	0.053 [1.35]
IH-10	5	1.125 [28.58]	0.635 [16.13]	0.812 [20.62]	0.065 [1.65]
IH-10	10	1.375 [34.93]	0.635 [16.13]	1.218 [30.94]	0.065 [1.65]
IH-10	27	1.125 [28.58]	0.935 [23.75]	0.687 [17.45]	0.065 [1.65]
IH-10	50	1.375 [34.93]	0.935 [23.75]	0.937 [23.80]	0.065 [1.65]
IH-10	68	1.375 [34.93]	0.935 [23.75]	1.125 [28.58]	0.065 [1.65]
IH-10	100	1.625 [41.28]	0.935 [23.75]	1.312 [33.32]	0.065 [1.65]
IH-15	5	1.375 [34.93]	0.700 [17.78]	0.937 [23.80]	0.082 [2.08]
IH-15	10	1.687 [42.85]	0.700 [17.78]	1.500 [38.10]	0.082 [2.08]
IH-15	27	1.375 [34.93]	1.000 [25.40]	0.937 [23.80]	0.082 [2.08]
IH-15	50	1.625 [41.28]	1.000 [25.40]	1.125 [28.58]	0.082 [2.08]



## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.