

**SPECIFICATION SHEET**  
**JFW MODEL 50DR-111**  
**DUAL ROTARY ATTENUATOR**

JFW Industries, Inc.  
 Phone: 317-887-1340  
 sales@jfwindustries.com  
 www.jfwindustries.com

Frequency Range	DC-2700 MHz
Impedance	50 Ohms nominal
Attenuation Range	0-60 dB in 1 dB steps
VSWR	1.35:1 maximum DC-1000 MHz 1.5:1 maximum 1000-2700 MHz
Insertion Loss	0.6 dB maximum DC-1000 MHz 1.2 dB maximum 1000-2700 MHz
Attenuation Accuracy	± 0.5 dB or 3%
RF Input Power	2 Watts average 1000 Watts peak
Direction of Rotation	Attenuation increases in a Clockwise direction
Indexing	30 degrees with stops at Minimum and maximum
RF Connector	SMA or N female
Operating Temperature Range	-20°C to +85°C
Physical Size	See outline drawing 092-327-05 (N) 092-440-05 (SMA)

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	11/17/2004		BAC 11/17/2004				
17283	06/04/2009	A	TRS 06/04/2009				