

GLASS PASSIVATED SILICON BRIDGE RECTIFIERS


VOLTAGE RANGE: 80 -- 1000 V

CURRENT: 0.8 A

FEATURES

- ◇ Rating to 1000 V
- ◇ Low forward voltage drop
- ◇ Small size, plastic case
- ◇ Glass passivated junction
- ◇ Weight: 0.0078 ounces, 0.22grams
- ◇ Mounting position: Any

TO - 269AA



inch(mm)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate current by 20%.

		S40	S80	S125	S250	S380	S500	UNITS
Maximum alternating input voltage	V_{VRMS}	50	110	170	420	560	700	V
Repetitive peak reverse voltage	V_{RRM}	80	160	250	600	800	1000	V
Maximum average forward rectified output current @ $T_C = 50^\circ C$	$I_{(AV)}$	0.8						A
Peak forward surge current 8.3ms single half-sine-wave	I_{FSM}	40						A
Maximum forward voltage drop per element at 0.4 A	V_F	1.2						V
Maximum reverse current @ $T_A = 25^\circ C$ at rated DC blocking voltage per element @ $T_A = 100^\circ C$	I_R	10.0 1.0						μA mA
Thermal resistance junction to ambient air	$R_{\theta JA}$	60						K/W
Operating temperature range	T_j	- 55 --- + 150						°C
Storage temperature range	T_{STG}	- 55 --- + 150						°C

www.galaxycn.com

FIG.1 --FORWARD DERATING CURVE




FIG.2 -- PEAK FORWARD SURGE CURRENT




FIG.3 -- TYPICAL FORWARD CHARACTERISTICS




FIG.4 -- TYPICAL REVERSE CHARACTERISTIC




FIG.5 -- TYPICAL JUNCTION CAPACITANCE PER ELEMENT

